

BZ33-HYP27HP3Z2



FEATURES

- Up to 3-zone compatibility
- Space-saving installation

COMPATIBLE UNITS



CONSOLE

BZ33ICM12



WALL MOUNT

BZ33-HYP09WALL2

BZ33-HYP12WALL2

BZ33-HYP18WALL2



DUCTED SYSTEM

BZ33-DIDU9

BZ33-DIDU12

BZ33-DIDU18



CASSETTE

BZ33-CASS09

BZ33-CASS12

BZ33-CASS18



CEILING & FLOOR SYSTEM

BZ33-IFMU18

MULTI-ZONE

The unit is compatible for multiple zone applications, up to 3 zones.

SPACE-SAVING INSTALLATION

Save space with the ability to connect up to 3 indoor units. Uses up to 50% less space than traditional outdoor units.

AMBIENT HEATING & COOLING

Low ambient heating down to -22°F. Ambient cooling as low as -22°F and as high as 122°F.



OUTDOOR HYPER PRO MULTI-ZONE UNIT

28,000 BTU

UNIT	ID NO.	MODEL
Outdoor	.3481263	BZ33-HYP27HP3Z2

COOLING

Capacity	BTU/H	28,000
EER	BTU/W	13
SEER	BTU/W	22

HEATING

Capacity	BTU/H	28,000
Input	W	2,345
Current	A	10.2
COP	W/W	3.5
HSPF4	BTU/W	10.4
HSPF5	BTU/W	9

COMPRESSOR

Type	Rotary	
Capacity	W	32,380
Input	W	2,600
Rated Current (RLA)	A	22
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 1000

REFRIGERANT PIPING

Liquid	In	3 x 1/4
Gas	In	3 x 3/8
Max. Length (All Rooms)	Ft	197
Max. Length (1 Indoor Unit)	Ft	98
Max. Height Difference (Between Indoor/Outdoor)	Ft	49
Max. Height Difference (Between Indoor Units)	Ft	33

AMBIENT TEMPERATURE

Cooling	°F	-22~122
Heating	°F	-22~86

SPECIFICATIONS

Refrigerant Type	R410A
Warranty	Yes*

OUTDOOR FAN MOTOR

Input	W	150
RLA	A	1.39
Speed	r/min	900 / 750 / 600
Air Flow	CFM	2,147
Noise Level	dBA	62.3

OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	37-1/4 x 16-1/10 x 31-9/10
Packaging (W x D x H)	In	42-9/10 x 19-7/10 x 34
Net/Gross Weight	Lbs	156.53 / 167.55

ELECTRICAL DATA

Min. Circuit Ampacity	A	30
Max. Fuse	A	45
Refrigerant Precharge	Ft	74
Additional Charge/Ft	Oz	0.161
Design Pressure	PSIG	550 / 340
Power Supply	Ph/V/Hz	1 / 208/230 / 60

*5 year warranty on parts. 7 year warranty on compressor.

