

BZ33-HYP36HP4Z2



FEATURES

- Up to 4-zone compatibility
- Space-saving installation

COMPATIBLE UNITS



CONSOLE

BZ33ICM12



WALL MOUNT

BZ33-HYP09WALL2

BZ33-HYP12WALL2

BZ33-HYP18WALL2

BZ33-HYP24WALL2



DUCTED SYSTEM

BZ33-DIDU9

BZ33-DIDU12

BZ33-DIDU18



CASSETTE

BZ33-CASS09

BZ33-CASS12

BZ33-CASS18

BZ33-CASS24



CEILING & FLOOR SYSTEM

BZ33-IFMU18

MULTI-ZONE

The unit is compatible for multiple zone applications, up to 4 zones.

SPACE-SAVING INSTALLATION

Save space with the ability to connect up to 4 indoor units. Uses up to 50% less space than traditional outdoor units.

AMBIENT HEATING & COOLING

Low ambient heating down to -22°F. Ambient cooling as low as -22°F and as high as 122°F.



OUTDOOR HYPER PRO MULTI-ZONE UNIT

36,000 BTU

UNIT	ID NO.	MODEL
Outdoor	.3481262	BZ33-HYP36HP4Z2

COOLING

Capacity	BTU/H	36,000
EER	BTU/W	13.5
SEER	BTU/W	21.5

HEATING

Capacity	BTU/H	36,000
Input	W	2,777
Current	A	12.1
COP	W/W	3.8
HSPF4	BTU/W	10.5
HSPF5	BTU/W	8.5

COMPRESSOR

Type	Rotary	
Capacity	W	38,214
Input	W	3,040
Rated Current (RLA)	A	21
Refrigerant Oil/Charge	mL	Ester Oil VG74 / 1400

REFRIGERANT PIPING

Liquid	In	4 x 1/4
Gas	In	3 x 3/8 + 1 x 1/2
Max. Length (All Rooms)	Ft	262
Max. Length (1 Indoor Unit)	Ft	115
Max. Height Difference (Between Indoor/Outdoor)	Ft	49
Max. Height Difference (Between Indoor Units)	Ft	33

AMBIENT TEMPERATURE

Cooling	°F	-22~122
Heating	°F	-22~86

SPECIFICATIONS

Refrigerant Type	R410A
Warranty	Yes*

OUTDOOR FAN MOTOR

Input	W	126
RLA	A	1.18
Speed	r/min	800 / 700 / 600
Air Flow	CFM	4,500
Noise Level	dBA	64

OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	37-1/2 x 16-3/10 x 52-1/2
Packaging (W x D x H)	In	43-1/10 x 19-1/2 x 58-1/4
Net/Gross Weight	Lbs	223.77 / 255.07

ELECTRICAL DATA

Min. Circuit Ampacity	A	35
Max. Fuse	A	50
Refrigerant Precharge	Ft	98
Additional Charge/Ft	Oz	0.161
Design Pressure	PSIG	550 / 340
Power Supply	Ph/V/Hz	1 / 208/230 / 60

*5 year warranty on parts. 7 year warranty on compressor.

