

# WP7-A WP8-A WP9-A

## Wall Pack, Outdoor



### Features

#### Housing

Die-formed Cold-rolled Steel with Epoxy Powder Coated Finish

#### Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

120V – 277V

#### Lamp

Integrate LED Module

More Color Temperature Option 4000K

#### Certification


ETL/cETL Listed, Suitable for Wet Locations

#### Warranty

5 Years Limited Warranty on Driver and LED

#### Options

- Bi Bi-Level Light Option
- EM Emergency Backup Light Option



### LED Type

| Model              | Input Voltage | Input Wattage | LED CT | CRI  | Lumen (TYP) | Finish | Shade   | Dimension (L x W X D) |
|--------------------|---------------|---------------|--------|------|-------------|--------|---------|-----------------------|
| WP7-A-05-15W-3000K | 120V ~ 277V   | 15W           | 3000K  | > 80 | 665         | Black  | Acrylic | 13.3" x 8.3" x 3.8"   |
| WP8-A-05-23W-3000K | 120V ~ 277V   | 23W           | 3000K  | > 80 | 1290        | Black  | Acrylic | 21.7" x 8.3" x 3.8"   |
| WP9-A-05-34W-3000K | 120V ~ 277V   | 34W           | 3000K  | > 80 | 2110        | Black  | Acrylic | 30.0" x 8.3" x 3.8"   |