



# INDOOR/OUTDOOR HYPER PRO MINI-SPLIT SYSTEM

## PREMIER SERIES

24,000 BTU

BZ33-HYP24WALL2-P



BZ33-HYP24HPOUT2-P



### FEATURES

- Two-way draining
- Extra low temperature heating
- Green Fin anti-corrosive coating
- Auto restart function
- Low and high ambient cooling
- Chassis and compressor heating belts
- Auto defrost
- 24-hour timer
- Wireless remote control included
- 208/230V, single phase

### TWO-WAY DRAINING

Piping, drainage, and connections are able to be installed on the right and left sides.

### AMBIENT HEATING & COOLING

Low ambient heating down to -22°F. Ambient cooling as low as -22°F and as high as 122°F.

### GREEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

### AUTO DEFROST

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

### AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

### 24-HOUR TIMER

Preset the unit to automatically turn on or off.



# INDOOR/OUTDOOR HYPER PRO MINI-SPLIT SYSTEM

**24,000 BTU**

UNIT	ID NO.	MODEL
Indoor	.3473426	BZ33-HYP24WALL2-P
Outdoor	.3478319	BZ33-HYP24HPOUT2-P

## COOLING

Capacity (Range)	BTU/H	24,000 (7,150 - 24,500)
Input	W	1,920
Rated Current	A	8.4
EER	BTU/W	13
SEER	BTU/W	20.5

## HEATING

Capacity (Range)	BTU/H	24,000 (7,500 - 29,740)
Input	W	2,500
Rated Current	A	10.9
COP	W/W	2.81
HSPF4	BTU/W	11.5
HSPF5	BTU/W	9.6

## COMPRESSOR

Type		Rotary
Capacity	W	24,345
Input	W	1,970
Rated Current (RLA)	A	14
Refrigerant Oil/Charge	mL	POE VG74 / 670

## REFRIGERANT PIPING

Liquid	In	3/8
Gas	In	5/8
Max. Refrigerant Pipe Length	Ft	164
Max. Different in Level	Ft	82

## ROOM TEMPERATURE

Indoor (Cooling/Heating)	°F	62~90 / 32~86
Outdoor (Cooling/Heating)	°F	-22~122 / -22~86

## SPECIFICATIONS

Application Area	Sq. Ft.	344 - 505
Refrigerant Type		R410A
Thermostat Type		Wireless Remote
Warranty		Yes*

\*5 year warranty on parts. 7 year warranty on compressor.

## INDOOR FAN MOTOR

Input	W	72
Output	W	60
RLA	A	0.23
Speed (High/Med/Low)	r/min	1,200 / 1,100 / 900
Air Flow (High/Med/Low)	CFM	695 / 624 / 485
Noise Level (High/Med/Low)	dBA	51.7 / 44.5 / 35.1

## INDOOR UNIT DIMENSIONS

Product (W x D x H)	In	46-7/10 x 10-1/10 x 13-2/5
Packaging (W x D x H)	In	49-4/5 x 16-1/2 x 13-2/5
Net/Gross Weight	Lbs	39.9 / 53.6

## OUTDOOR FAN MOTOR

Input	W	150
Output	W	120
RLA	A	0.5
Speed	r/min	810
Air Flow	CFM	2,354
Noise Level	dBA	60

## OUTDOOR UNIT DIMENSIONS

Product (W x D x H)	In	37-1/4 x 16-1/10 x 31-9/10
Packaging (W x D x H)	In	43 x 19-7/10 x 34-1/2
Net/Gross Weight	Lbs	135.58 / 148.81

## ELECTRICAL DATA

Min. Circuit Ampacity	A	20
Max. Fuse	A	30
Refrigerant Precharge	Ft	25
Additional Charge/Ft	Oz	0.32
Design Pressure	PSIG	550 / 340
Connection Wiring		16AWG*4, Stranded, Unshielded
Power Supply	Ph/V/Hz	1 / 208/230 / 60

