


PREMIER SERIES

30,000 BTU**BZ33-HYP30WALL2-G2-P**

FEATURES

- Multi-zone only
- Two-way draining
- Golden Fin anti-corrosive coating
- Auto restart function
- 24-Hour timer
- Occupancy and humidity sensor
- Wireless remote control included
- Compatible with BZ33-WCON1 and BZ33-WCON1-G2
- 208/230V, single phase

TWO-WAY DRAINING

Piping, drainage and connections are able to be installed on the right and left sides.

FOLLOW ME MODE

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

GOLDEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

24-HOUR TIMER

Preset the unit to automatically turn on or off.

AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.



INDOOR HYPER PRO MINI SPLIT

UNIT	ID NO.	MODEL
Indoor	.3547997	BZ33-HYP30WALL2-G2-P

SPECIFICATIONS

Series	Premier
Warranty	Yes*

COOLING

Capacity (Range)	BTU/H	30,000 (9,070 - 30,700)
Input	W	2,605
Rated Current	A	11.4
EER2	BTU/W	11.5
SEER2	BTU/W	20

HEATING

Capacity (Range)	BTU/H	30,000 (8,600 - 34,800)
Input	W	3,380
Rated Current	A	14.7
COP	W/W	2.6
HSPF2-4	BTU/W	9.2
HSPF2-5	BTU/W	7.1

REFRIGERANT PIPE

Design Pressure	PSIG	550/340
Refrigerant Type	Oz	R410A
Refrigerant Precharge	Ft	25
Additional Charge/Ft	Oz	0.32
Liquid	In	3/8
Gas	In	5/8
Max. Refrigerant Pipe Length	Ft	164
Max. Difference in Level	Ft	82

OPERATING TEMPERATURE

Indoor (Cooling/Heating)	°F	60~90 / 32~86
Outdoor (Cooling/Heating)	°F	5~122 / 5~75

INDOOR FAN MOTOR

Input	W	58
Output	W	58
RLA	A	0.5
Speed (High/Med/Low)	r/min	1,050 / 880 / 630
Air Flow (High/Med/Low)	CFM	646.5 / 505.3 / 382.4
Noise Level (High/Med/Low)	dBA	46 / 40.5 / 33

INDOOR UNIT DIMENSIONS

Product (W x D x H)	In	46-7/8 x 11-3/16 x 14-5/8
Packing (W x D x H)	In	50-3/8 x 14-3/16 x 17-15/16
Weight (Net/Gross)	Lbs	43.7 / 55

ELECTRICAL DATA

Min. Circuit Ampacity	A	3
Max. Fuse	A	15
Connection Wiring		14*4 AWG
Power Supply	Ph/V/Hz	1 / 208/230 / 60

*7 years. 10 years if product is registered within thirty days from installation.

All G2 models are backwards compatible excluding Air Handler units.

Due to continuing product improvements, specifications may change without notice.
Visit breeze33.com for current product information.

breeze33.com



INVERTERS & A COILS

Indoor Unit	MSC24A-J	MSC24B-J	MSC36B-J	MSC36C-J	MSC48C-J	MSC60D-J
Outdoor Unit (Single-Zone)	INV24OUT2-J	INV18OUT2-J	INV30OUT2-J	INV30OUT2-J	INV48OUT2-J	INV60OUT2-J
		INV24OUT2-J	INV36OUT2-J	INV36OUT2-J		

WALL MOUNTS - COMFORT SERIES

Indoor Unit	HP09WALL1-G2-C*	HP12WALL1-G2-C*	HP18WALL2-G2-C*	HP24WALL2-G2-C*	HP30WALL2-G2-C*	HP36WALL2-G2-C*
Outdoor Unit (Single-Zone)	HP09OUT1-G2-C*	HP12OUT1-G2-C*	HP18OUT2-G2-C*	HP24OUT2-G2-C*	HP30OUT2-G2-C*	HP36OUT2-G2-C*

WALL MOUNTS - PREMIER SERIES

Indoor Unit	HYP06WALL2-G2-P	HYP09WALL2-G2-P*	HYP12WALL2-G2-P*	HYP18WALL2-G2-P*	HYP24WALL2-G2-P*	HYP30WALL2-G2-P	HYP36WALL2-G2-P
Outdoor Unit (Single-Zone)	HYP06OUT2-G2-P	HYP09OUT2-G2-P*	HYP12OUT2-G2-P*	HYP18OUT2-G2-P*	HYP24OUT2-G2-P*		
Outdoor Unit (Multi-Zone)	HP182Z2-G2-P*						
	HP273Z2-G2-P*						
	HP364Z2-G2-P*						
				HP485Z2-G2-P*			
	HYP182Z2-G2-P*						
	HYP273Z2-G2-P*						
	HYP364Z2-G2-P*						
				HYP485Z2-G2-P*			

WALL MOUNT - PREMIER SERIES

Indoor Unit	HYP33WALL2-G2-P
Outdoor Unit (Single-Zone)	HYP33OUT2-G2-P

CEILING CASSETTES

Indoor Unit	CASS09-P	CASS12-P	CASS18-P	CASS24-G2-P*	CASS36-G2-P
Outdoor Unit (Single-Zone)	HYP09OUT2-G2-P*	HYP12OUT2-G2-P*	HYP18OUT2-G2-P*	HYP24OUT2-G2-P*	HYP36OUT2-G2-P
Outdoor Unit (Multi-Zone)	HP182Z2-G2-P*				
	HP273Z2-G2-P*				
	HP364Z2-G2-P*				
	HP485Z2-G2-P*				
	HYP182Z2-G2-P*				
	HYP273Z2-G2-P*				
	HYP364Z2-G2-P*				
	HYP485Z2-G2-P*				

CONSOLES

Indoor Unit	ICM12-G2-P
Outdoor Unit (Single-Zone)	HYP12OUT2-G2-P*
Outdoor Unit (Multi-Zone)	HP182Z2-G2-P*
	HP273Z2-G2-P*
	HP364Z2-G2-P*
	HP485Z2-G2-P*
	HYP182Z2-G2-P*
	HYP273Z2-G2-P*
	HYP364Z2-G2-P*
	HYP485Z2-G2-P*

DUCTED

Indoor Unit	DIDU9-P	DIDU12-P	DIDU18-P	DIDU24-P	DIDU36-P	DIDU48-P
Outdoor Unit (Single-Zone)	HYP09OUT2-G2-P*	HYP12OUT2-G2-P*	HYP18OUT2-G2-P*	HYP24OUT2-G2-P*	HYP36OUT2-G2-P	HYP48OUT2-G2-P
Outdoor Unit (Multi-Zone)	HP182Z2-G2-P*					
	HP273Z2-G2-P*					
	HP364Z2-G2-P*					
	HP485Z2-G2-P*					
	HYP182Z2-G2-P*					
	HYP273Z2-G2-P*					
	HYP364Z2-G2-P*					
	HYP485Z2-G2-P*					

ONE-WAY CASSETTES

Indoor Unit	OWCASS09-G2-P	OWCASS12-G2-P	OWCASS18-G2-P
Outdoor Unit (Single-Zone)	HYP09OUT2-G2-P*	HYP12OUT2-G2-P*	HYP18OUT2-G2-P*
Outdoor Unit (Multi-Zone)	HP182Z2-G2-P*		
	HP273Z2-G2-P*		
	HP364Z2-G2-P*		
	HP485Z2-G2-P*		
	HYP182Z2-G2-P*		
	HYP273Z2-G2-P*		
	HYP364Z2-G2-P*		
	HYP485Z2-G2-P*		

AIR HANDLERS

Indoor Unit	MSAHU18-G2-P	MSAHU24-G2-P*	MSAHU36-G2-P	MSAHU48-G2-P
Outdoor Unit (Single-Zone)	HYP18OUT2-G2-P*	HYP24OUT2-G2-P*	HYP36OUT2-G2-P	HYP48OUT2-G2-P
Outdoor Unit (Multi-Zone)	HP273Z2-G2-P*			
	HP364Z2-G2-P*			
	HP485Z2-G2-P*			
	HYP273Z2-G2-P*			
	HYP364Z2-G2-P*			
	HYP485Z2-G2-P*			

CEILING & FLOOR MOUNTS

Indoor Unit	IFMU18-P	IFMU24-G2-P	IFMU36-G2-P	IFMU48-G2-P
Outdoor Unit (Single-Zone)	HYP18OUT2-G2-P*	HYP24OUT2-G2-P*	HYP36OUT2-G2-P	HYP48OUT2-G2-P
Outdoor Unit (Multi-Zone)	HP273Z2-G2-P*			
	HP364Z2-G2-P*			
	HP485Z2-G2-P*			
	HYP273Z2-G2-P*			
	HYP364Z2-G2-P*			
	HYP485Z2-G2-P*			

* Available in G1 and G2 models. All G2 models are backwards compatible excluding Air Handler units.