

## PREMIER SERIES

36,000 BTU

BZ33-HYP36WALL2-G2-P



BZ33-HYP36OUT2-G2-P



### FEATURES

- Two-way draining
- Heating operation down to -22°F
- Low ambient cooling down to -22°F
- Golden Fin anti-corrosive coating
- Auto restart function
- Crank case & basepan heater included
- Auto defrost
- 24-Hour timer
- Wireless remote control included
- 208/230V, single phase

### TWO-WAY DRAINING

Piping, drainage, and connections are able to be installed on the right and left sides.

### FOLLOW ME MODE

Senses indoor temperature at handheld remote or Breeze33 wired controller, rather than at the indoor equipment.

### GOLDEN FIN COATING

Prevents corrosive build-up and improves efficiency while protecting the condenser from harsh weather and elements.

### AUTO DEFROST

In low temperatures, the auto defrost feature will keep the evaporator from freezing.

### AUTO RESTART

In the event of a power failure, the unit will remember and restart the previous settings when power returns.

### 24-HOUR TIMER

Preset the unit to automatically turn on or off.

All G2 models are backwards compatible.



# INDOOR/OUTDOOR HYPER PRO MINI SPLIT SYSTEM

| UNIT    | ID NO.   | MODEL                |
|---------|----------|----------------------|
| Indoor  | .3547998 | BZ33-HYP36WALL2-G2-P |
| Outdoor | .3548014 | BZ33-HYP36OUT2-G2-P  |

## SPECIFICATIONS

|                 |                 |
|-----------------|-----------------|
| Series          | Premier         |
| Thermostat Type | Wireless Remote |
| Warranty        | Yes*            |

## COOLING

|                  |       |                         |
|------------------|-------|-------------------------|
| Capacity (Range) | BTU/H | 36,000 (9,300 - 38,800) |
| Input            | W     | 4,235                   |
| Rated Current    | A     | 18.5                    |
| EER              | BTU/W | 8.5                     |
| SEER             | BTU/W | 17.5                    |

## HEATING

|                  |       |                          |
|------------------|-------|--------------------------|
| Capacity (Range) | BTU/H | 36,000 (11,570 - 37,000) |
| Input            | W     | 4,200                    |
| Rated Current    | A     | 18.3                     |
| COP              | W/W   | 2.51                     |
| HSPF4            | BTU/W | 9                        |
| HSPF5            | BTU/W | 7.4                      |

## COMPRESSOR

|                        |        |          |
|------------------------|--------|----------|
| Type                   | Rotary |          |
| Capacity               | BTU/H  | 27,621.3 |
| Input                  | W      | 2,200    |
| Rated Current (RLA)    | A      | —        |
| Refrigerant Oil/Charge | mL     | —        |

## REFRIGERANT PIPE

|                              |      |           |
|------------------------------|------|-----------|
| Design Pressure              | PSIG | 550 / 340 |
| Refrigerant Type             | Oz   | R410A     |
| Refrigerant Precharge        | Ft   | 25        |
| Additional Charge/Ft         | Oz   | 0.32      |
| Liquid                       | In   | 3/8       |
| Gas                          | In   | 5/8       |
| Max. Refrigerant Pipe Length | Ft   | 213       |
| Max. Difference in Level     | Ft   | 98        |

## ROOM TEMPERATURE

|                           |    |               |
|---------------------------|----|---------------|
| Indoor (Cooling/Heating)  | °F | 60~90 / 32~86 |
| Outdoor (Cooling/Heating) | °F | 5~122 / 5~75  |

## INDOOR FAN MOTOR

|                            |       |                       |
|----------------------------|-------|-----------------------|
| Input                      | W     | 58                    |
| Output                     | W     | —                     |
| RLA                        | A     | 0.5                   |
| Speed (High/Med/Low)       | r/min | 1,050 / 880 / 630     |
| Air Flow (High/Med/Low)    | CFM   | 639.4 / 505.9 / 382.4 |
| Noise Level (High/Med/Low) | dBA   | 47.5 / 42 / 35.5      |

## INDOOR UNIT DIMENSIONS

|                     |     |                           |
|---------------------|-----|---------------------------|
| Product (W x D x H) | In  | 46-9/10 x 11-1/5 x 14-3/5 |
| Packing (W x D x H) | In  | 50-2/5 x 14-1/5 x 17-9/10 |
| Weight (Net/Gross)  | Lbs | 43.7 / 54.9               |

## OUTDOOR FAN MOTOR

|             |       |                           |
|-------------|-------|---------------------------|
| Input       | W     | —                         |
| Output      | W     | —                         |
| RLA         | A     | —                         |
| Speed       | r/min | 1,150 / 1,050 / 900 / 850 |
| Air Flow    | CFM   | 2,235.3                   |
| Noise Level | dBA   | 61.5                      |

## OUTDOOR UNIT DIMENSIONS

|                     |     |                            |
|---------------------|-----|----------------------------|
| Product (W x D x H) | In  | 37-1/4 x 16-1/10 x 31-9/10 |
| Packing (W x D x H) | In  | 42-9/10 x 19-7/10 x 34-4/5 |
| Weight (Net/Gross)  | Lbs | 150.13 / 159               |

## ELECTRICAL DATA

|                       |         |                  |
|-----------------------|---------|------------------|
| Min. Circuit Ampacity | A       | 28               |
| Max. Fuse             | A       | 35               |
| Connection Wiring     |         | 14*4 AWG         |
| Power Supply          | Ph/V/Hz | 1 / 208/230 / 60 |

## RECOMMENDED ACCESSORIES

|                   |                                          |
|-------------------|------------------------------------------|
| <b>BZ33-WCON1</b> | <b>.3496301</b>                          |
| Description       | Wired Controller                         |
| Compatible with   | All Breeze33 Indoor Mini Split Equipment |

\*5 year warranty on parts. 7 year warranty on compressor.  
All G2 models are backwards compatible.

Due to continuing product improvements, specifications may change without notice.  
Visit [breeze33.com](http://breeze33.com) for current product information.

[breeze33.com](http://breeze33.com)

