

# PACKAGED TERMINAL

### **AIR CONDITIONER**

#### **COOL/HEAT PUMP**

## BZ33-PTACHP12-G2

ID# .3473459



#### **FEATURES**

- Cools and heats a room up to 500 sq. ft.
- Easy washable filter
- Quiet operation
- Auto defrost
- Auto restart
- Fresh air ventilation
- Auxiliary mode selection
- 20A Power cord included
- Electronic control

### 12,000 BTU

Quickly cool and heat spaces up to 500 square feet.

#### **ELECTRONIC CONTROL**

Precisely control the temperature of the space by easily choosing the temperature setting or fan speed.

#### **QUIET OPERATION**

The unit is constructed with a sturdy chassis to reduce vibration and sound transmission.

#### **AUTO RESTART**

In the event of a power failure, the unit will resume normal operation automatically when power returns.

#### **AUXILIARY MODE**

Provides customization, better temperature control, and more functional detail.

#### **WASHABLE FILTER**

Keep the air as fresh as possible and remove residue build-up with an easily washable filter.



# PACKAGED TERMINAL

## AIR CONDITIONER

UNIT	ID NO.	MODEL
PTAC	.3473459	BZ33-PTACHP12-G2

PERFORMANCE - COOLING		208/230	
Capacity	BTU/H	11,800 / 12,000	
EER	BTU/H/W	10.5	
Input	W	1,124 / 1,142	
Current	Α	5.4 / 5	

PERFORMANCE - HEATING (PTC)		208/230	
Capacity (3.4kW)	BTU/H	8,900 / 10,900	
Input	W	2,900 / 3,535	
Current	А	13.7 / 15.3	
MCA		20	

PERFORMANCE - HEATING (HEAT PUMP)		208/230	
Capacity	BTU/H	10,500 / 10,800	
Input	W	963 / 990	
Current	А	4.6 / 4.3	
COP	W/W	3.2	

#### **FEATURES**

Cooling/Heating	Yes / Yes
Control Type	Electronic
Energy Saver	No
ENERGY STAR®	No
Auto Restart	Yes
Sleep Mode	No
Filter Monitor	No
Timer	No
Fan Speeds	3
Slide-out Chassis	Yes
Washable Filter	Yes
Warranty	Yes*

#### **SPECIFICATIONS**

Fresh Air Intake (Hi/Med/Lo)	CFM	387 / 351 / 309
Dehumidification	Pt/Day	61
Indoor Level (Hi/Med/Lo)	dBA	52 / 51.5 / 51
Outdoor Level (Hi)	dBA	67
Cooling Area	Sq. Ft.	450-500
Refrigerant		R410A or R32 <sup>†</sup>


<sup>\*1</sup> year warranty on parts. 5 year warranty on compressor.

#### **ELECTRICAL DATA**

Power Supply	V/Hz/Ph	208-230 / 60 / 1
Plug Type		LCDI (6-20P)

#### **DIMENSIONS**

Product (W x D x H)	ln	42 x 23-7/8 x 16
Shipping (W x D x H)	In	44-1/2 x 24-5/8 x 19-1/4
Net/Gross Weight	Lbs	116 / 125.4



#### **RECOMMENDED ACCESSORIES**

BZ33-PTACWS		.3473461
Description		Wall Sleeve, White
Dimensions (W x D x H)	In	42 x 14-3/4 x 16
BZ33-PTACGRILL1		.3514045
Description		Standard Grille, White
Dimensions (W x D x H)	In	41-5/8 x 3/8 x 15-5/8
BZ33-PTACGRILL2		.3473463
Description		Extruded Architectural Grille, Grey
Dimensions (W x D x H)	In	41-3/4 x 1 x 15-1/4







<sup>†</sup> Refrigerant dependent on model generation.