













For Drain Guns, Sink Drums, and Small Line Sectional Machines









		Model	Length	Typical Application	Characteristics	Machines
$\frac{5}{16}$ " (8mm)		C-1 C-21	25' 50'	Drain Lines $\frac{3}{4}$ " to $1\frac{1}{2}$ ". Kitchen Sinks, Lavatory Sinks, Bathtub Drains, Drinking Fountains and Urinals.	Hollow core cables that provide maximum flexibility for severe bends and "P" Traps.	K-25/K-26 (25' only) K-45 K-40 K-50*
		C-2 C-22	25' 50'	Drain Lines $\frac{3}{4}$ " to $1\frac{1}{2}$ ". Drop Head leads into down drain pipes, especially good for back-to-back mounted fixtures and severe bends.		
		C-11C C-131C	25' 35'	Drain Lines $1\frac{1}{4}$ " to 2". Kitchen Sinks, Lavatory Sinks, Slop Sinks and Laundry Lines.	Inner core cables that provide good flexibility while resisting kinking.	K-25/K-26 (25' only) K-45, K-40 K-3800, K-50*
		C-21C C-231C	25' 35'	Drop Head leads into down drain pipes, especially good for back-to-back mounted fixtures and severe bends.		
$\frac{3}{8}$ " (10mm)		C-4 C-6 C-61C	25' 35' 35'	Drain Lines $1\frac{1}{4}$ " to $2\frac{1}{2}$ ". Kitchen Sinks, Lavatory Sinks, Slop Sinks, and Disposal Waste Lines.	Flexible, yet tough $\frac{3}{8}$ " cable most commonly used after traps have been removed. C-61C slightly stiffer than C-6.	K-45 K-40 K-50*
		C-5	35'	Drain Lines $1\frac{1}{4}$ " to $2\frac{1}{2}$ ". Kitchen Sinks, Lavatory Sinks, Slop Sinks, and Disposal Waste Lines.		

*See Page 12.25 for Proper Adapter or Sink Drum.

For Drum Machines

		Model	Length	Typical Application	Characteristics	Machines
$\frac{3}{8}$ " (10mm)		C-31, C-31IW C-32, C-32IW C-33, C-33IW	50' 75' 100'	Drain Lines $1\frac{1}{2}$ " to $2\frac{1}{2}$ ". Kitchen Sinks, Lavatory Sinks, Slop Sinks and Laundry Stacks.	Good flexibility. As torque builds, outer spring tightens on wire core causing cable to stiffen and transfer greater torque to cutter.	K-400 K-3800
$\frac{1}{2}$ " (12mm)		C-44, C-44IW C-45, C-45IW C-46	50' 75' 90'	Drain Lines 2" to 4". Laundry Stacks, Roof Vents and Indoor Floor Drains.	Same characteristics as above. Exceptional flexibility and toughness for a $\frac{1}{2}$ " inner core cable.	K-400 K-3800
$\frac{5}{8}$ " (16mm)		C-25, C-25HD C-26, C-26HD C-27, C-27HD C-24, C-24HD	25' 50' 75' 100'	Drain Lines 3" to 6". Floor Drains, Vents, and Laterals.	General purpose cable. Inner core provides greater stiffness under load.	K-750 K-6200 K-7500
		C-27HC C-24HC	75' 100'	Drain Lines 3" to 6". Floor Drains, Vents, and Laterals.	Hollow core cable is lighter in weight & more flexible. Helps operator negotiate difficult traps & bends in large lines.	K-750 K-7500
$\frac{3}{4}$ " (20mm)		C-28 C-29 C-75 C-100	25' 50' 75' 100'	Drain Lines 4" to 10". Main Lines including Laterals.	Powerful cable used for heavy-duty blockages such as tree roots. Cable tightens on core to provide extra stiffness under load, delivering power to cutter.	K-750 K-7500
		C-75HC C-100HC	75' 100'	Drain Lines 4" to 6". Main Lines including Laterals.	Hollow core cable is lighter in weight and more flexible. Helps operator negotiate difficult traps and bends in large lines.	K-750 K-7500

For Sectional Machines

		Model	Length	Typical Application	Characteristics	Machines
$\frac{5}{8}$ " (16mm)		C-7	7 $\frac{1}{2}$ '	2" and 3" Floor Drains.	Tight wind cable providing good rigidity in a hollow core cable. Not for tree roots.	K-50, K-60SP
		C-8	7 $\frac{1}{2}$ '	Drain Lines $1\frac{1}{4}$ " to 2". Ideal for proper cleaning of small lines.	Open wind cable that is more flexible than C-7. Open wind acts as an auger to thoroughly remove blockages in small lines.	K-50, K-60SP
		C-9	10'	Drain Lines 2" to 4". Ideal for Floor Drains and Stacks.	Heavy-Duty open wind cable ideal for long runs in indoor lines.	K-50, K-60SP
$\frac{7}{8}$ " (22mm)		C-10	15'	Drain Lines 2" to 4". Rooftop Vent Stacks.	Standard all-purpose open wind. Excellent flexibility.	K-60SP K-1500A/B*
$1\frac{1}{4}$ " (32mm)		C-11	15'	Drain Lines 3" to 8". Good for all around work. Easily negotiates 4" Traps.	Standard all-purpose open wind with $\frac{3}{8}$ " pitch. Flexible, yet rigid enough to do fast, tough root cutting.	K-1500A/B/ & SP
		C-12	15'	Drain Lines 4" to 10". Do not use through 4" "P" Traps.	Extra-heavy-duty open wind with $\frac{3}{8}$ " pitch. Designed for 4" to 10" long runs.	K-1500A/B/ & SP
		C-14	15'	Drain Lines 3" to 10". Do not use through 4" "P" Traps.	Heavy-duty open wind with $\frac{1}{2}$ " pitch. Especially good For 4" cleanout or 8" elbow entering in 4" to 10" line.	K-1500A/B/ & SP
		C-15	15'	Drain Lines 3" to 6". Ideal for 4" Traps.	Extra-flexible open wind with $\frac{1}{2}$ " pitch. Lighter than C-11, slightly stiffer.	K-1500A/B

*See Page 12.29 for Proper Jawset.