



880-82



881-13



881-02H



881-02A

Always use a 5/8" poly ferrule (supplied) when attaching compression fittings to the Grip Tip™.




Remove Tip



Air Test



Water Test

Ground-Rough
Head Tests

Saw Off Cap

Knock Out &
Remove Plug

Grip Tip™

Test Cap & Test Plug

Patent # 6,769,291

- Tip acts as a handle while applying glue and can be snipped to allow filling and bleeding with water or air for testing
- Deeper glue surface ensures a good seal, especially on unevenly cut pipe
- Durable, ABS may be glued to pipe with all-purpose glue
- High-visibility models make installed plugs and caps easy to see for ensured removal
- Test nipple is 5/8" O.D. for connection to compression fittings



Caps and plugs are available in magenta (hot pink) for better visibility



Item No	Description	Color	Pkg	Min Qty	Case Qty
TEST CAP					
880-81	1½" test cap	white	B	25	200
880-82	2" test cap	white	B	25	100
880-83	3" test cap	white	B	10	50
880-84	4" test cap	white	B	10	50
880-81C	1½" test cap	magenta	B	25	200
880-82C	2" test cap	magenta	B	25	100
880-83C	3" test cap	magenta	B	10	50
880-84C	4" test cap	magenta	B	10	50
880-81PK	1½" test cap	white	C*	50	50
880-82PK	2" test cap	white	C*	50	50
880-83PK	3" test cap	white	C*	25	25
880-84PK	4" test cap	white	C*	25	25
TEST PLUG					
881-10	1½" test plug	white	C*	25	200
881-12	2" test plug	white	C*	25	100
881-13	3" test plug	white	C*	10	50
881-14	4" test plug	white	C*	10	50
881-10C	1½" test plug	magenta	C*	25	200
881-12C	2" test plug	magenta	C*	25	100
881-13C	3" test plug	magenta	C*	10	50
881-14C	4" test plug	magenta	C*	10	50
TESTING ACCESSORIES					
881-02A	Air test fitting, 15 PSI gauge 5/8" O.D. comp × air filler valve		B	1	10
881-02H	Water test valve 5/8" O.D. comp × female swivel hose thread		B	1	25
881-02FP	Replacement 5/8" poly ferrule		B	100	1000