

Breeze33 Multi-Position Cased Coils

BZ33-XCCM Series Indoor A-Coil

Cooling capacity: 30-60 kBtu/h



Contents:

1 PRODUCT LINEUP.....	2
2 NOMENCLATURE.....	2
3 SPECIFICATIONS.....	3
4 DIMENSIONAL DRAWING.....	5
5 AIRFLOW PERFORMANCE.....	6



Standard Features:

- Equipped with a refrigerant sensor, suitable for R454b system .
- AHRI certificated.
- High efficiency and energy saving, AHRI energy efficiency certificated .
- Multi-position installation accommodated a variety of installation scenarios .
- Broad cooling range from 55 °F to 120 °F.
- Optional factory installed Thermostatic Expansion Valve .
- All aluminum coil for corrosion-resistance.
- 100% insulation, reduces operating sound and enhance thermal insulation.
- Perfect match with Breeze33 gas furnace, no need extra kit for R454b system.

1 Product lineup

Model	BZ33-XCCM3036A, BZ33-XCCM3036B BZ33-XCCM3036C, BZ33-XCCM3642B BZ33-XCCM3642C, BZ33-XCCM3642D BZ33-XCCM4248B, BZ33-XCCM4248C BZ33-XCCM4248D, BZ33-XCCM4860C BZ33-XCCM4860D
Appearance	

2 Nomenclature

BZ33	-	X	CC	M	3036	A
1		2	3	4	5	6

Legend		
No.	Code	Remarks
1	BZ33	Brand: Breeze33
2	X	P: Piston X: TXV
3	CC	Cased Coil
4	M	Multi Position
5	3036	Capacity: 18: 18 kBtu/h; 24: 24 kBtu/h; 30: 30 kBtu/h; 36: 36 kBtu/h;
6	A	Cabinet Width


3 Specifications

	BZ33-XCCM3036A	BZ33-XCCM3036B	BZ33-XCCM3036C	BZ33-XCCM3642B
INSTALLATION	Multiple position	Multiple position	Multiple position	Multiple position
AIR OUTLET (W × H) (in.)	13 × 19	16 × 19	19-1/2 × 19	16 × 19
NOMINAL RATING				
Max. Cooling (BTU/h)	30,000/36,000	30,000/36,000	30,000/36,000	36,000/42,000
EVAPORATOR COIL				
Type	Tube & Fin	Tube & Fin	Tube & Fin	Tube & Fin
Tube Material	Aluminum	Aluminum	Aluminum	Aluminum
Tube Size (in.)	9/32	9/32	9/32	9/32
REFRIGERANT CONNECTION SIZE				
Liquid Line Size (O.D.) (in.)	3/8	3/8	3/8	3/8
Suction Line Size (O.D.) (in.)	3/4	3/4	3/4	3/4
DIMENSIONS				
Net dimensions (W × H × D) (in.)	14-1/2 × 20 × 21	17-1/2 × 20 × 21	21 × 20 × 21	17-1/2 × 26 × 21
Packed dimensions (W × H × D) (in.)	24-15/16 × 24-3/16 × 22-1/4	24-15/16 × 20-5/8 × 22-1/4	24-15/16 × 24-3/16 × 22-1/4	24-15/16 × 20-5/8 × 28-1/8
WEIGHT				
Net weight (lbs.)	45	47	49	57
Shipping weight (lbs.)	54	57	55	64

	BZ33-XCCM3642C	BZ33-XCCM3642D	BZ33-XCCM4248B	BZ33-XCCM4248C
INSTALLATION	Multiple position	Multiple position	Multiple position	Multiple position
AIR OUTLET (W × H) (in.)	19-1/2 × 19	23 × 19	16 × 19	19-1/2 × 19
NOMINAL RATING				
Max. Cooling (BTU/h)	36,000/42,000	36,000/42,000	42,000/48,000	42,000/48,000
EVAPORATOR COIL				
Type	Tube & Fin	Tube & Fin	Tube & Fin	Tube & Fin
Tube Material	Aluminum	Aluminum	Aluminum	Aluminum
Tube Size (in.)	9/32	9/32	3/8	3/8
REFRIGERANT CONNECTION SIZE				
Liquid Line Size (O.D.) (in.)	3/8	3/8	3/8	3/8
Suction Line Size (O.D.) (in.)	3/4	3/4	3/4	3/4
DIMENSIONS				
Net dimensions (W × H × D) (in.)	21 × 21 × 26	21 × 24-1/2 × 26	21 × 17-1/2 × 30	21 × 21 × 30
Packed dimensions (W × H × D) (in.)	24-15/16 × 24-3/16 × 28-1/8	24-15/16 × 27-9/16 × 28-1/8	24-15/16 × 20-5/8 × 32-5/16	24-15/16 × 24-3/16 × 32-5/16
WEIGHT				
Net weight (lbs.)	59	64	73	73
Shipping weight (lbs.)	66	70	79	79

	BZ33-XCCM4248D	BZ33-XCCM4860C	BZ33-XCCM4860D
INSTALLATION	Multiple position	Multiple position	Multiple position
AIR OUTLET (W × H) (in.)	23 × 19	19-1/2 × 19	23 × 19
NOMINAL RATING			
Max. Cooling (BTU/h)	42,000/48,000	48,000/60,000	48,000/60,000
EVAPORATOR COIL			
Type	Tube & Fin	Tube & Fin	Tube & Fin
Tube Material	Aluminum	Aluminum	Aluminum
Tube Size (in.)	3/8	3/8	3/8
REFRIGERANT CONNECTION SIZE			
Liquid Line Size (O.D.) (in.)	3/8	3/8	3/8
Suction Line Size (O.D.) (in.)	3/4	3/4	3/4
DIMENSIONS			
Net dimensions (W × H × D) (in.)	24-1/2 × 30 × 21	21 × 30 × 21	24-1/2 × 30 × 21
Packed dimensions (W × H × D) (in.)	24-15/16 × 27-9/16 × 32-5/16	24-15/16 × 24-3/16 × 32-5/16	24-15/16 × 27-9/16 × 32-5/16
WEIGHT			
Net weight (lbs.)	75	82	86
Shipping weight (lbs.)	82	88	93

4 Dimensional Drawing



MODELS	Unit Dimensions IN. [mm]					WEIGHT (LBS. [kg])
	UNIT HEIGHT "H"	UNIT WIDTH "W"	SUPPLY DUCT "A"	"W1"	LIQUID LINE/ VAPOR LINE	
BZ33-XCCM3036A	20 [508]	14-1/2 [368]	13 [330]	13-1/2 [343]	3/8 / 3/4	44 [20]
BZ33-XCCM3036B	20 [508]	17-1/2 [445]	16 [407]	16-1/2 [419]	3/8 / 3/4	46 [21]
BZ33-XCCM3036C	20 [508]	21 [533]	19-1/2 [495]	20 [508]	3/8 / 3/4	49 [22]
BZ33-XCCM3642B	26 [660]	17-1/2 [445]	16 [407]	16-1/2 [419]	3/8 / 3/4	57 [26]
BZ33-XCCM3642C	26 [660]	21 [533]	19-1/2 [495]	20 [508]	3/8 / 3/4	59 [27]
BZ33-XCCM3642D	26 [660]	24-1/2 [622]	23 [584]	23-1/2 [597]	3/8 / 3/4	64 [29]
BZ33-XCCM4248B	30 [762]	17-1/2 [445]	16 [407]	16-1/2 [419]	3/8 / 3/4	73 [33]
BZ33-XCCM4248C	30 [762]	21 [533]	19-1/2 [495]	20 [508]	3/8 / 3/4	73 [33]
BZ33-XCCM4248D	30 [762]	24-1/2 [622]	23 [584]	23-1/2 [597]	3/8 / 3/4	75 [34]
BZ33-XCCM4860C	30 [762]	21 [533]	19-1/2 [495]	20 [508]	3/8 / 3/4	82 [37]
BZ33-XCCM4860D	30 [762]	24-1/2 [622]	23 [584]	23-1/2 [597]	3/8 / 3/4	86 [39]

5 Airflow Performance

Pressure drop characteristics for cooling (SCFM)								
Model	Pressure drop (Inches of water gauge)							
	0.05	0.1	0.15	0.2	0.25	0.3	0.35	0.4
BZ33-XCCM3036A	307	485	618	729	823	911	991	1063
BZ33-XCCM3036B	327	527	682	810	925	1024	1122	1217
BZ33-XCCM3036C	360	585	748	893	1019	1132	1238	1348
BZ33-XCCM3642B	401	600	773	916	1045	1160	1256	1357
BZ33-XCCM3642C	457	663	856	1019	1156	1277	1394	1502
BZ33-XCCM3642D	496	718	924	1102	1259	1398	1530	1651
BZ33-XCCM4248B	456	638	810	953	1077	1191	1284	1390
BZ33-XCCM4248C	505	726	932	1098	1244	1375	1494	1604
BZ33-XCCM4248D	533	857	1105	1319	1509	1675	1824	1956
BZ33-XCCM4860C	439	699	906	1071	1224	1362	1487	1589
BZ33-XCCM4860D	466	764	978	1157	1313	1466	1590	1695

Data based on wet coil with entering air at 80 deg F DB / 67 deg F WB without air filter.

The maximum allowable pressure drop is 0.4 in. WC.

The maximum CFM is the data at 0.4 in. WC. pressure

BREEZE33 PRODUCTS, LLC

breeze33.com

Due to continuing product improvements, specifications may change without notice.
Visit breeze33.com for current product information.

