



Tankless Water Heater Comparison Chart

Tankless Water Heaters

FEATURES

	Stream33® Tankless Water Heater		Competitor A	Competitor B	Competitor C			
	Model	Recirculation Pump						
	S33-95TWH199P-NG	Yes				—	—	—
	S33-95TWH199-NG	—						
	S33-95TWH199P-LP	Yes						
S33-95TWH199-LP	—							
Installation Location	Indoor		Indoor/Outdoor	Indoor	Indoor/Outdoor			
Piping Connection Location	Bottom Connection		Bottom Connection	Top Connection	Bottom Connection			
Efficiency	95%		95%	95%	95%			
Max. BTU	199,000		199,000	199,000	199,000			
Min. BTU	20,000		18,000	9,000	13,300			
Temperature	95~140°F		95~185°F	100~140°F	97~185°F			
Flow Rate (GPM) 45° F Temperature Rise	8.5+		8.5+	8.5+	8.5+			
Flow Rate (GPM) 90° F Temperature Rise	4.2+		4.2+	4.2+	4.2+			
Propane (LP) Compatability	Separate Model (S33-95TWH199P-LP, S33-95TWH199-LP)		Separate Model	Conversion Kit Included	Conversion Kit Included			
Flue Diameter	2" or 3"		2" or 3"	2" or 3"	2" or 3"			
Vent Length Max	2" = 60'		2" = 60'	2" = 60'	2" = 75'			
Product Dimensions (H x W x D)	26-5/8" x 17-5/16" x 11"		27-1/2" x 17-1/4" x 15"	31-1/2" x 18-1/2" x 9-3/4"	28" x 17-1/4" x 13-1/4"			
Warranty	15-Year Heat Exchanger/ 5-Year Parts		15-Year Heat Exchanger/ 5-Year Parts	15-Year Heat Exchanger/ 5-Year Parts	15-Year Heat Exchanger/ 5-Year Parts			
Heat Exchanger	Dual, Stainless Steel		Stainless Steel	Copper	Dual, Stainless Steel			
Weight (with Recirculation Pump)	70.5 lbs		85 lbs	80 lbs	77 lbs			
Weight (without Recirculation Pump)	70.5 lbs		78 lbs	79 lbs	73 lbs			