



FEATURES

- Stainless steel, enamel coated heating elements
- Factory installed heat trap
- 2" Insulation thickness
- 3/4" NPT water connection
- Voltages: 208V/240V
- Optional top and side T&P valve
- 3/4" Hex head magnesium anode rod with longer lifespan
- Meets or exceeds the following:
 - UL
 - CSA
 - AHRI



Model	ID	Type	Tank Capacity (Gal)	Energy Factor (UEF)	Dimensions (Dia. x Height)
S33-30LEWH-4500	.3621663	Low	30	0.92	20" x 32-13/16"
S33-40LEWH-4500	.3621664		40		23" x 34-7/8"

WARRANTY

6-Year warranty for Tank and Parts when used in residential applications. Visit stream33.com for details.

Model	Rated Capacity (Gal)	First Hour Rating (Gal)	Recovery Rate at 90° Temp. Rise (GPH)	Element Wattage*	Floor to Top of Heater (A)	Jacket Diameter (B)	Floor to Water Connection (C)	Floor to T&P Valve (D)	Water Connection NPT	Gross Weight (lbs.)
S33-30LEWH-4500	26	44	21	4500W	30-1/16"	20"	31-13/16"	32-13/16"	3/4" NPT	81.5
S33-40LEWH-4500	35	51			32-1/8"	22-7/8"	33-15/16"	34-7/8"		108

*Element Wattage based on 240V/208V

