

WB-PA6 Front Wind Baffle



Job Name:

System Reference:

Date:



FEATURES

- Front Wind Baffles allow outdoor units to operate at full capacity down to the temperature ranges shown in the table below.
- Prevents wind from reversing outdoor fan rotation when unenergized.
- Durable and low maintenance construction.

SPECIFICATIONS

Color	Surface Treatment	Material	Weight
Matches Outdoor Unit (Ivory Munsell 3Y 7.8/1.1)	Polyester Powder Coating	Alloy Hot-Dip Zinc Coated Carbon Steel Sheet	8 Lbs. 8 Oz.
Model Series	Operation Range Without Wind Baffles	Front Wind Baffles	Front + Advanced Side + Advanced Rear Wind Baffles
PUY	23°F - 115°F	0°F	-40°F
PUZ	23°F - 115°F	0°F	N/A
MXZ	23°F - 115°F	0°F	N/A

NOTES

- Install outdoor units with the back surface facing wall side to eliminate the effects of external wind.
- Outdoor units should not be installed in an orientation or site where the wind blows directly at the back of the unit.
- Wind baffle should not be used where there is any obstacle at either side or above the outdoor unit as the discharged air will be blocked.
- Refer to outdoor unit for detailed installation instructions.

WB-PA6

Front Wind Baffle



DIMENSIONS

ALL DIMENSIONS IN INCHES
ALL DIMENSIONS $\pm 1/32$ "

