



HAND PROTECTION

Mechanics Style Rubber Coated Gloves with Cut, Abrasion, and Puncture Resistance

DESCRIPTION

These general-purpose gloves are palm-dipped with black etched rubber on a seamless 10-gauge red polyester/cotton shell. They have a hook-and-loop closure on a knit wrist to provide an excellent fit. These gloves offer outstanding gripping power and better wear than mechanic-type gloves for a fraction of the cost. Each pair is individually hang-tagged for retail sale.

INDUSTRY

Industrial	Construction
Mechanical	Warehousing
Tool Handling	Building
Parts Handling	Manufacturing



ITEM 300RV

SIZES 8(M)-10(XL)

FEATURES

- Puncture-resistant, etched-rubber palm retains flexibility and grip in low temperatures
- Polyester/cotton 10-gauge shell for comfort
- Hook-and-loop closure secures gloves to wrist to prevent loss or slipping
- EN 388 Levels: 2143X

Meets ANSI/ISEA 105-2016 standard

- Cut Level A2 (palm), Level A1 (back of hand)
- ASTM F2992-15 Results = Palm: 677 grams, Back of Hand: 416 grams
- Abrasion Level 3
- Puncture Level 4
- Puncture Results: 111 Newtons



SPECIFICATIONS

SHELL	SHELL COLOR	COATING	COATING TYPE	COATING COLOR	GAUGE	FINISH	CUFF	RETAIL READY
Polyester/Cotton	Red	Rubber	Palm	Black	10-Gauge	Etched	Hook-and-Loop	Yes
CUT		ASTM F2992-15 RESULTS			ABRASION	PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS
Palm = Level A2, Back of Hand = Level A1		Palm = 677 Grams, Back of Hand = 416 Grams			Level 3	Level 4	111 Newtons	2143X

PACKAGING

	QUANTITY	8(M)	9(L)	10(XL)
PAIR UPC	1	856187001138	856187001114	856187001121
INNER PACK UPC	12/PACK	810292028008	810292028015	810292028022
CASE GTIN	6 PK/CASE	10810292028005	10810292028012	10810292028029
CASE WEIGHT (IN POUNDS)		19	20	19.2

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com


Global Glove
& Safety Manufacturing, Inc.