



ENERGY SAVING PRODUCTS

The EZS air switch line is the future of universal air pressure switches. Three line items allow you to replace any switch in the range of 0.08" – 10.0" W.C. The "EZ Set" feature allows you to easily set EZS air switches without monometers, meters, or any tool other than the included allen wrench. Simply turn the dial and set it using the sight glass on the underside of the switch.

Out of the box, the switch comes in the historic RSS physical profile. If you have space limitations, or need to fit the NS2 profile area, once pressure is set, simply remove the outer case, and you have a set NS2 profile switch

Availability:

EZS-495 and EZS-498: August 1, 2025

EZS-492: October 1, 2025



	EZS Series			RSS Series		NS2 Series
Part Number	EZS-492-09	EZS-495-11	EZS-498-13	RSS-495-11	RSS-498-13	NS2-0000-03
Setpoint Range (in. W.C.)	.08" to 1.0"	0.15" to 2.0"	2.0" to 10.0"	0.15" to 1.0"	1.0" to 4.0"	0.10" to 10.0"
Positive, Negative Differential Pressure	✓	✓	✓	✓	✓	✓
UL, CUL, CSA, CE, AGA Approval	✓	✓	✓	✓	✓	✓
-40 F to 190 F Temperature Range	✓	✓	✓	✓	✓	✓
SPDT contacts rated for 100,000 cycles min.	✓	✓	✓	✓	✓	✓
Contains Orifices for Time Delay Applications	✓	✓	✓			✓
No Need to Select and Insert Spring	✓	✓	✓	✓	✓	
'EZ' Set - No Tools Required	✓	✓	✓			
Fits Both RSS and NS2 Physical Profile	✓	✓	✓			
Future Availability	✓	✓	✓			✓



Information
and Install
Video:

