



SPORT WALK

COMMUNICATION IS NOW POSSIBLE ON ANY SPORTIVE EVENT

SportWalk can be used for short and midterm applications. The material is applicable outdoor on various surfaces. The foil consists of a dimension stable film with a textured resilient surface. The reverse side is coated with a pressure sensitive adhesive covered by a removable liner. The product provides a resilient, durable, slip resistant surface for a large variety of applications.

The foil is characterized by an extremely secure and slip-resistant surface, a chemical resistance and longevity. Moreover, the quick and easy portable product is extremely foot friendly. The waterproof adhesive and the therewith associated durability of the foil guarantee a versatile usability.



Uses

- Short term outdoor sports events - Marathons
- Road shows

Features & Benefits

- Extremely secure with its slip-resistant surface
- Can be cut to shape
- Robust against abrasion
- Good chemical resistance
- Anti bacterial surface
- No lamination required





SPORT WALK

COMMUNICATION IS NOW POSSIBLE ON ANY SPORTIVE EVENT

Durability

The durability depends on the way the product has been applied as well as on the condition of the surface and the amount and type of traffic on the area. SportWalk may be used for short term outdoor application (1 - 2 weeks).

If you are using SportWalk indoor you may see (dependent on the surface) adhesive residues. In such cases we recommend citrus cleaner to remove such residues.

Storage

It is recommended to store the product in a closed packaging at a temperature of +15°C to +30°C humidity 45% to 60%. The product has a shelf life of 24 month after purchasing the material.

Warranty

Since further circumstances such as application of the foil are not controllable, all product warranty automatically ends as soon as the product has been applied to any surface.

Printing method

The material can be colour printed digital (solvent and UVC). We recommend UVC printing.

Waste handling

It is recommended to handle the used material as industrial waste.

- Liquid varnish may extend life cycle

Technical information

Size	Width: 1.30 m	Length: 30.48 m	
Material	vinyl foam		450μ +/- 5μ
Adhesive	clear acrylic adhesive		50μ +/- 5μ
Certificates	Slip-resistance		R10
Application	minimum application temperature		+10°C / +50°F

Peel Adhesion to:	Stainless Steel	Polyethylene	Powder coated surfaces *
15 minute dwell	55oz/in (66N/100 mm)	20oz/in (22N/100 mm)	40oz/in (44N/100 mm)
24 hours dwell	75oz/in (82N/100 mm)	25oz/in (27N/100 mm)	55oz/in (60N/100 mm)

Further data

Coefficient of Friction (Kinetic) Dry / Wet	Rubber: 0,9 / 1,0 Leather: 0,3 / 1,0
Minimum application temperature	+10°C / +50°F**
Service temperature minimum and maximum	-28°C/-20°F / +104°C/+220°F
Flammability	to be tested

Chemical resistance

Water	R	Diesel Fuel	R
10% Salt Water	R	Hydraulic Fluid	R
Bleach	R	50% Anti-freeze in water	R
Trichloroethylene	NR	Methyl Ethyl Ketone	NR
25% Sulphuric Acid	I	Mineral Spirits	R
1% Sodium Hydroxide	R	99% IPA	R
Gasoline unleaded	R		

R = recommended for non continuous immersion; (I) = recommended for intermittent exposure only ; NR = not recommended

* Colour and lot variances of coated surfaces including paints, powder coatings, lacquers, stains, and other treatments may vary the performance of the tape and should be evaluated for the compatibility of the tape to the specific surface.

**At temperatures below +10 °C the surface has to be pre-treated with a gas burner.