

***EVERGREEN MEMORIAL PARK CEMETERY
MARKER REGULATIONS
JANUARY 1, 2011***

1. All markers in the cemetery must be entirely composed of granite.
2. Flat markers must have sawn sides and top side polished.
3. Only one marker is allowed per grave and the marker must be flat for a single grave.
4. Flat markers for single graves must be 2' by 1' or 30" by 18", and must have a concrete foundation (see concrete foundation drawings).
5. Two side by side graves may have a single flat double stone. This stone must be 4' in length and 1' in width or 4' in length and 18" in width and must be set in concrete (see concrete foundation drawing).
6. The cemetery reserves the right to disapprove a monument or flat marker if its shape or design is contrary or injurious to the demeanor of the cemetery.
7. All flat markers must be 3" to 4" in depth.

CREMATION GRAVES

1. All cremation grave markers must be flat and 3" to 4" in depth.
2. Cremation graves must have, a 30" by 18" flat marker or a 48" by 18" flat marker, and cannot be set in concrete. These markers must be set on a 2" bed of sand to the contours of the cemetery. The markers must have an L.M.P. Edge.

UPRIGHT MARKERS

1. All upright markers must have an all polished granite base and an all polished granite die.
2. Bases must be at least 6" high and no more than 48" in length and 14" in width.
3. The width of the die must be 8" shorter at its base than the width of the base.
4. All upright markers must be placed on graves 1 & 2, or 3 & 4 or 5 & 6.
5. Bases can be no more than 8" tall and dies may be no more than 4'6" tall.
6. Bases must be set on a concrete foundation (see concrete foundation drawings).

BABY GRAVES

1. Baby markers can be no larger than 20" by 10" in the Baby Section at the Cemetery.
2. Baby markers must be a flat marker and set in concrete (see concrete foundation drawings).

CONCRETE FOUNDATIONS

1. All foundations for both flat and upright markers must contain at least 1/8" rebar for reinforcement (see concrete foundation drawings).
2. Foundations for flat markers must have 2 inches of concrete under the stone and 6 inches of concrete around the stone.
3. If a vase is included in the foundation, the foundation on the vase side of the marker must have 9" of concrete. (see drawing)

VASES

Vases must be granite, bronze or zinc metals. Vases that are not set on concrete foundation must be set in concrete block at least 12" by 12" by 6".

