




RL 5728


ASSEMBLY & INSTALLATION GUIDE



- To assemble safety cables:
1. Join fixture safety cables with safety cable from ceiling.
 2. Wrap both safety cable around the cable lock nut.
 3. Secure by tightening both hex nuts until tight.



CAUTION: Connection hooks can be hung one way **ONLY!**



WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING * SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.**

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

1. Carefully remove all parts from the carton.
2. Hook (N) to the light fixture (O).
3. Hook one end of (L) to part (M), one end of (L) to part (K).
4. Remove (I) by unscrewing (H), attach one end of chain (G) to top loop (D), one end of chain (G) to hanging loop (J) and secure by replacing (I) and tightening screws (H).
5. Unscrew canopy ring (F) and slide canopy ring (F) and canopy (E) on the chain (G).
6. Attach mounting plate (A) to ceiling outlet box and secure with mounting screws (C) provided.
7. Attach mounting loop (D) to nipple (B).
8. Attach fixture steel safety cable to structural member in the ceiling.
9. Attach the bare copper ground from the fixture to the ground junction box wire (usually green or copper), fasten together with a plastic wire connector. Tighten wrap the wire connector with electrical tape. Be sure no wire strands are exposed. **IT IS IMPERATIVE THAT THE OUTLET BOX IN YOUR HOME BE PROPERLY GROUNDED.**
10. Connect neutral wire from fixture (ridges molded wire) to the neutral wire from the junction box (usually white). Fasten both wires together with a plastic wire connector and tightly wrap the wire connector with electrical tape. Be sure no wire strands are exposed.
11. Connect the hot wires from the fixture (smooth wire) to the hot wire (usually black) from the junction box. Fasten each together with a plastic wire connector and wrap the connection with electrical tape. **DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OTHERWISE SAFETY WILL BE UNCOMPROMISED.**
12. Tuck wire connections neatly into ceiling outlet box.
13. Slip canopy (E) to ceiling and secure with canopy ring (F).
14. Insert the specified light bulbs into sockets.
15. Restore power and test fixture. Installation is completed.

*** Clean with a dry, soft cloth only. Use no harsh abrasives or chemical agents.



RALPH LAUREN