



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____



S11745 - 14 Watt; 4Ft LED T8; 5000K; 347V Canada Only; G13 Base; Type B Ballast Bypass; Double Ended Wiring

- Flicker Free
- Rated for Enclosed Fixture



ELECTRICAL

| | |
|---------------------------|--|
| Technology: | LED |
| Watts: | 14W |
| Volts: | 347V |
| Lumens: | 1800L |
| CRI: | 82 |
| CCT (Kelvins): | 5000K |
| Temperature: | Natural Light |
| Beam Spread : | 210 |
| Hours Rated: | 50000 |
| Dimmable: | Non-Dimmable |
| Fluorescent Equivalent : | 32W |
| Operating Temperature : | -20C (-4F) to +45C (+113F) |
| Ballast Bypass/Direct: | Ballast Bypass |
| Ballasting Requirements : | Ballast Bypass |
| Lamp Ballast Type A/B/C : | Type B |
| Lamp End Type : | Double Ended |
| THD: | 20% |
| Power Factor : | 0.9 |
| Light Source: | LED |
| Warranty: | 5 Year Limited - T8 LED Bulbs - Ballast Bypass |

PACKAGING

| | |
|------------------|---------------------|
| Each UPC: | 045923117459 |
| Each Quantity: | 1 |
| Each Dimensions: | 48.00 x 1.10 x 1.10 |
| Case UPC: | 10045923117456 |
| Case Quantity: | 25 |
| Case Dimensions: | 58.00 x 6.00 x 6.00 |

PHYSICAL

| | |
|-----------------|---------------|
| ANSI Base: | G13 |
| Base: | Medium Bi Pin |
| Shape: | T8 |
| Finish: | Gloss White |
| Lens Finish: | Frost |
| Lens Material: | Glass |
| MOD (In.): | 1.00 |
| MOL (In.): | 47.78 |
| Nominal Length: | 48.00 |
| Weight (Lbs.): | 0.44 |
| Material: | Plastic |
| Housing Color: | White |

COMPLIANCE

| | |
|-----------------------------|---|
| Safety Listing: | cUL - Classified; cUL - Certified; cRU - Recognized Component |
| Location Rating: | Damp |
| Indoor/Outdoor: | Indoor and Outdoor |
| Energy Star Qualified: | No |
| DLC Approved: | Yes |
| DLC Classification: | Standard |
| DLC ID: | S-6GMKJ8 |
| DLC Primary Use: | Internal Driver/Line Voltage (UL Type B) Lamps |
| UL/ETL File Listing: | CN - E356817; CN - E335148 |
| UL/ETL Standard: | CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993 |
| Enclosure Rating: | Enclosed Rated Lamp |
| Rated For Enclosed Fixture: | Yes |
| FCC Compliant: | Yes |
| NSF Approved: | Yes |
| RoHS Compliant: | Yes |
| SDS Class: | LED_Lamp |
| Restrictions: | No Restrictions |

INFO

Additional Info: _____ CANADA ONLY

Min Compartment Size: _____ Length: 48.43 in. Width: 13.39 in. Height: 1.77 in.

Tube Guard Use:

|

Yes