




Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_



**S11746** - 17 Watt; 4Ft LED T8; 4000K; 347V Canada Only; G13 Base;  
Type B Ballast Bypass; Double Ended Wiring

- Flicker Free
- Rated for Enclosed Fixture



## ELECTRICAL

Technology:	LED
Watts:	17W
Volts:	347V
Lumens:	2200L
CRI:	82
CCT (Kelvins):	4000K
Temperature:	Cool White
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Non-Dimmable
Fluorescent Equivalent :	32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballast Bypass/Direct:	Ballast Bypass
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - T8 LED Bulbs - Ballast Bypass

## PACKAGING

Each UPC:	045923117466
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10
Case UPC:	10045923117463
Case Quantity:	25
Case Dimensions:	58.00 x 6.00 x 6.00

## PHYSICAL

ANSI Base:	G13
Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss White
Lens Finish:	Frost
Lens Material:	Glass
MOD (In.):	1.00
MOL (In.):	47.78
Nominal Length:	48.00
Weight (Lbs.):	0.44
Material:	Plastic
Housing Color:	White

## COMPLIANCE

Safety Listing:	cUL - Classified; cUL - Certified; cRU - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-MWC31Y
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL/ETL File Listing:	CN - E356817; CN - E335148
UL/ETL Standard:	CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

## INFO

Additional Info:	CANADA ONLY
------------------	-------------

Min Compartment Size:	Length: 48.43 in. Width: 13.39 in. Height: 1.77 in.
-----------------------	---

SATCO.COM | 800-437-2826

© Satco Products, Inc.  
All rights reserved 2022

