



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21201 - 3 Watt G16.5 LED; Clear; Candelabra base; 90 CRI; 4000K; 120 Volt

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	3W
Volts:	120V
Lumens:	200L
CRI:	90
Rg Value :	57
CCT (Kelvins):	4000K
Temperature:	Cool White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable
Incandescent Equivalent :	25W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	>0.7
Light Source:	LED
Warranty:	3 Year Limited

PACKAGING

Each UPC:	045923205163
Each Quantity:	1
Each Dimensions:	2.16 x 2.16 x 3.54
Inner UPC:	20045923205167
Inner Quantity:	6
Inner Dimensions:	6.97 x 4.72 x 4.29
Case UPC:	10045923205160
Case Quantity:	24
Case Dimensions:	14.69 x 10.20 x 5.47

PHYSICAL

ANSI Base:	E12
Base:	Candelabra
Shape:	G16.5
Finish:	Clear
MOD (In.):	1.97
MOL (In.):	3.11
Weight (Lbs.):	0.037
Material:	Glass / Nickel Plated Aluminum

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Leviton 6672

Leviton 6674

Leviton 66ELV

Legrand ADTP703TU

Lutron AYCL-153P

Lutron CTRP-253P

Cooper DALo6P-C2

Leviton DDMX1

Leviton DG6HD

Leviton DH6HD

Leviton DL6HD

Leviton DSEo6-10Z

Leviton DSLo6

Leviton DSLo6-1LZ

Leviton DSM10

Cooper DULo6P-C2

Lutron DVCL-153P

Lutron DVRP-253P

Leviton DW6HD

Leviton DZ6HD

Leviton IPEo4-1L

Leviton IPLo6

Lutron LECL-153PH

Lutron MA-PRO

Lutron MACL-153M

Lutron MSCL-OP153M

Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL
Cooper	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Cooper	TAL06P-C2
Leviton	TSL06
Leviton	TSM10
Cooper	VSULO6D