



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21210 - 5.5 Watt G16.5 LED; Clear; Candelabra base; 90 CRI; 3000K; 120 Volt

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	5.5W
Volts:	120V
Lumens:	500L
CRI:	90
Rg Value :	56
CCT (Kelvins):	3000K
Temperature:	Soft White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	>0.7
Light Source:	LED
Warranty:	3 Year Limited

PACKAGING

Each UPC:	045923205255
Each Quantity:	1
Each Dimensions:	2.16 x 2.16 x 3.54
Inner UPC:	20045923205259
Inner Quantity:	6
Inner Dimensions:	6.97 x 4.72 x 4.29
Case UPC:	10045923205252
Case Quantity:	24
Case Dimensions:	14.69 x 10.20 x 5.47

PHYSICAL

ANSI Base:	E12
Base:	Candelabra
Shape:	G16.5
Finish:	Clear
MOD (In.):	1.97
MOL (In.):	3.11
Weight (Lbs.):	0.037
Material:	Glass / Nickel Plated Aluminum

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2398728
Energy Star Lamp Category:	Decorative
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions



S21210 - 5.5 Watt G16.5 LED; Clear; Candelabra base; 90 CRI; 3000K; 120 Volt

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Satco	86/103
Lutron	AYCL-153P
Lutron	CTRP-253P
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSE06-10Z
Leviton	DSL06
Leviton	DSL06-1LZ
Leviton	DSM10
Cooper	DUL06P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX

Lutron	PD-6WCL
Lutron	RCL-153PNL
Cooper	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Cooper	SUF7
Cooper	TAL06P-C2
Leviton	TSL06
Leviton	TSM10
Cooper	VSUL06D