



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21270 - 4 Watt B11 LED; Frost; Candelabra base; 90 CRI; 3000K; 120 Volt

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	4W
Volts:	120V
Lumens:	350L
CRI:	90
Rg Value :	55
CCT (Kelvins):	3000K
Temperature:	Soft White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	>0.7
Light Source:	LED
Warranty:	3 Year Limited

PACKAGING

Each UPC:	045923205859
Each Quantity:	1
Each Dimensions:	1.65 x 1.65 x 4.13
Inner UPC:	20045923205853
Inner Quantity:	6
Inner Dimensions:	5.43 x 3.70 x 4.84
Case UPC:	10045923205856
Case Quantity:	24
Case Dimensions:	11.61 x 8.15 x 6.02

PHYSICAL

ANSI Base:	E12
Base:	Candelabra
Shape:	B11
Finish:	Frost
MOD (In.):	1.38
MOL (In.):	3.97
Weight (Lbs.):	0.035
Material:	Glass / Nickel Plated Aluminum

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2398720
Energy Star Lamp Category:	Decorative
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Leviton 6672

Leviton 6674

Satco 86/103

Lutron AYCL-153P

Lutron CTRP-253P

Cooper DALo6P-C2

Leviton DDMX1

Leviton DG6HD

Leviton DH6HD

Leviton DL6HD

Leviton DSLo6

Leviton DSLo6-1LZ

Leviton DSM1o

Cooper DULo6P-C2

Lutron DVCL-153P

Lutron DVRP-253P

Leviton DW6HD

Leviton DZ6HD

Leviton IPLo6

Lutron LECL-153PH

Lutron MA-PRO

Lutron MACL-153M

Lutron MSCL-OP153M

Lutron NTCL-250

Lutron NTRP-250

Lutron PD-1oWX

Lutron	PD-6WCL
Lutron	RCL-153PNL
Cooper	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Cooper	SUF7
Leviton	TSL06
Leviton	TSM10
Cooper	VSUL06D