



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21295** - 3 Watt CA10 LED; Frost; Candelabra base; 90 CRI; 2700K; 120 Volt

- Rated for Enclosed Fixture



### ELECTRICAL

|                           |                            |
|---------------------------|----------------------------|
| Technology:               | LED                        |
| Watts:                    | 3W                         |
| Volts:                    | 120V                       |
| Lumens:                   | 200L                       |
| CRI:                      | 90                         |
| Rg Value :                | 53                         |
| CCT (Kelvins):            | 2700K                      |
| Temperature:              | Warm White                 |
| Beam Spread :             | 300                        |
| Hours Rated:              | 15000                      |
| Dimmable:                 | Yes-Dimmable               |
| Incandescent Equivalent : | 25W                        |
| Operating Temperature :   | -20C (-4F) to +45C (+113F) |
| Power Factor :            | >0.7                       |
| Light Source:             | LED                        |
| Warranty:                 | 3 Year Limited             |

### PACKAGING

|                   |                     |
|-------------------|---------------------|
| Each UPC:         | 045923206108        |
| Each Quantity:    | 1                   |
| Each Dimensions:  | 1.65 x 1.65 x 4.96  |
| Inner UPC:        | 20045923206102      |
| Inner Quantity:   | 6                   |
| Inner Dimensions: | 5.43 x 3.70 x 5.67  |
| Case UPC:         | 10045923206105      |
| Case Quantity:    | 24                  |
| Case Dimensions:  | 11.61 x 8.15 x 6.85 |

### PHYSICAL

|                |                                |
|----------------|--------------------------------|
| ANSI Base:     | E12                            |
| Base:          | Candelabra                     |
| Shape:         | CA10                           |
| Finish:        | Frost                          |
| MOD (In.):     | 1.38                           |
| MOL (In.):     | 4.72                           |
| Weight (Lbs.): | 0.035                          |
| Material:      | Glass / Nickel Plated Aluminum |

### COMPLIANCE

|                             |                     |
|-----------------------------|---------------------|
| Safety Listing:             | cETLus              |
| Location Rating:            | Wet                 |
| Indoor/Outdoor:             | Indoor              |
| Energy Star Qualified:      | Yes                 |
| Energy Star Unique ID:      | ESID-2398709        |
| Energy Star Lamp Category:  | Decorative          |
| Enclosure Rating:           | Enclosed Rated Lamp |
| Rated For Enclosed Fixture: | Yes                 |
| FCC Compliant:              | Yes                 |
| NSF Approved:               | No                  |
| RoHS Compliant:             | Yes                 |
| SDS Class:                  | LED_Lamp            |
| Restrictions:               | No Restrictions     |



**S21295** - 3 Watt CA10 LED; Frost; Candelabra base; 90 CRI; 2700K;  
120 Volt

#### DIMMER COMPATIBILITY

|         |             |
|---------|-------------|
| Leviton | 6672        |
| Leviton | 6674        |
| Leviton | 66ELV       |
| Legrand | ADTP703TU   |
| Lutron  | AYCL-153P   |
| Lutron  | CTRP-253P   |
| Cooper  | DAL06P-C2   |
| Leviton | DDMX1       |
| Leviton | DG6HD       |
| Leviton | DH6HD       |
| Leviton | DL6HD       |
| Leviton | DSE06-10Z   |
| Leviton | DSL06       |
| Leviton | DSL06-1LZ   |
| Leviton | DSM10       |
| Cooper  | DUL06P-C2   |
| Lutron  | DVCL-153P   |
| Lutron  | DVRP-253P   |
| Leviton | DW6HD       |
| Leviton | DZ6HD       |
| Leviton | IPE04-1L    |
| Leviton | IPL06       |
| Lutron  | LECL-153PH  |
| Lutron  | MA-PRO      |
| Lutron  | MACL-153M   |
| Lutron  | MSCL-OP153M |

|                |            |
|----------------|------------|
| <b>Lutron</b>  | NTCL-250   |
| <b>Lutron</b>  | NTRP-250   |
| <b>Lutron</b>  | PD-10WX    |
| <b>Lutron</b>  | PD-6WCL    |
| <b>Lutron</b>  | RCL-153PNL |
| <b>Cooper</b>  | RF9640-ND  |
| <b>Legrand</b> | RHCL450PTC |
| <b>Leviton</b> | RNL06-10Z  |
| <b>Lutron</b>  | RRD-6CL    |
| <b>Lutron</b>  | RRD-PRO    |
| <b>Satco</b>   | S11268     |
| <b>Cooper</b>  | TAL06P-C2  |
| <b>Leviton</b> | TSL06      |
| <b>Leviton</b> | TSM10      |
| <b>Cooper</b>  | VSUL06D    |