



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21303 - 4 Watt CA10 LED; Frost; Candelabra base; 90 CRI; 5000K; 120 Volt

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	4W
Volts:	120V
Lumens:	350L
CRI:	90
Rg Value :	69
CCT (Kelvins):	5000K
Temperature:	Natural Light
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	>0.7
Light Source:	LED
Warranty:	3 Year Limited

PACKAGING

Each UPC:	045923206184
Each Quantity:	1
Each Dimensions:	1.65 x 1.65 x 4.96
Inner UPC:	20045923206188
Inner Quantity:	6
Inner Dimensions:	5.43 x 3.70 x 5.67
Case UPC:	10045923206181
Case Quantity:	24
Case Dimensions:	11.61 x 8.15 x 6.85

PHYSICAL

ANSI Base:	E12
Base:	Candelabra
Shape:	CA10
Finish:	Frost
MOD (In.):	1.38
MOL (In.):	4.72
Weight (Lbs.):	0.035
Material:	Glass / Nickel Plated Aluminum

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2398726
Energy Star Lamp Category:	Decorative
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions



S21303 - 4 Watt CA10 LED; Frost; Candelabra base; 90 CRI; 5000K;
120 Volt

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Satco	86/103
Lutron	AYCL-153P
Lutron	CTRP-253P
Cooper	DALo6P-C2
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSL06
Leviton	DSL06-1LZ
Leviton	DSM10
Cooper	DULO6P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX

Lutron	PD-6WCL
Lutron	RCL-153PNL
Cooper	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Cooper	SUF7
Leviton	TSL06
Leviton	TSM10
Cooper	VSUL06D