



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21339 - 8 Watt BT15 LED; White; Medium base; 90 CRI; 5000K; 120 Volt

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	8W
Volts:	120V
Lumens:	800L
CRI:	90
Rg Value :	72
CCT (Kelvins):	5000K
Temperature:	Natural Light
Beam Spread :	320
Hours Rated:	15000
Dimmable:	Yes-Dimmable
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	>0.7
Light Source:	LED
Warranty:	3 Year Limited

PACKAGING

Each UPC:	045923206467
Each Quantity:	1
Each Dimensions:	1.89 x 1.89 x 4.53
Inner UPC:	20045923206461
Inner Quantity:	6
Inner Dimensions:	6.14 x 4.17 x 5.24
Case UPC:	10045923206464
Case Quantity:	24
Case Dimensions:	13.03 x 9.09 x 6.42

PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	BT15
Finish:	White
MOD (In.):	1.81
MOL (In.):	4.06
Weight (Lbs.):	0.055
Material:	Glass / Nickel Plated Aluminum

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Pending
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Leviton 6672

Leviton 6674

Satco 86/103

Lutron AYCL-153P

Lutron CTRP-253P

Leviton DDMX1

Leviton DG6HD

Leviton DH6HD

Leviton DL6HD

Leviton DSE06-10Z

Leviton DSL06

Leviton DSL06-1LZ

Leviton DSM10

Cooper DUL06P-C2

Lutron DVCL-153P

Lutron DVRP-253P

Leviton DW6HD

Leviton DZ6HD

Leviton IPL06

Lutron LECL-153PH

Lutron MA-PRO

Lutron MACL-153M

Lutron MSCL-OP153M

Lutron NTCL-250

Lutron NTRP-250

Lutron PD-10WX

Lutron	PD-6WCL
Lutron	RCL-153PNL
Cooper	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Cooper	SAL06P
Cooper	SUF7
Leviton	TSL06
Leviton	TSM10
Cooper	VSUL06D