



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21369 - 4 Watt B11 LED; Clear; Medium base; 90 CRI; 3000K; 120 Volt; 3-Pack

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	4W
Volts:	120V
Lumens:	350L
CRI:	90
Rg Value :	57
CCT (Kelvins):	3000K
Temperature:	Soft White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	>0.7
Light Source:	LED
Warranty:	3 Year Limited

PACKAGING

Each UPC:	045923206764
Each Quantity:	1
Each Dimensions:	4.92 x 1.57 x 4.06
Inner UPC:	20045923206768
Inner Quantity:	6
Inner Dimensions:	10.24 x 5.20 x 4.80
Case UPC:	10045923206761
Case Quantity:	24
Case Dimensions:	10.94 x 11.18 x 10.79

PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	B11
Finish:	Clear
MOD (In.):	1.38
MOL (In.):	3.58
Weight (Lbs.):	0.132
Material:	Glass / Nickel Plated Aluminum

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2398733
Energy Star Lamp Category:	Decorative
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Leviton 6672

Leviton 6674

Satco 86/103

Lutron AYCL-153P

Lutron CTRP-253P

Cooper DALo6P-C2

Leviton DDMX1

Leviton DG6HD

Leviton DH6HD

Leviton DL6HD

Leviton DSLo6

Leviton DSLo6-1LZ

Leviton DSM1o

Cooper DULo6P-C2

Lutron DVCL-153P

Lutron DVRP-253P

Leviton DW6HD

Leviton DZ6HD

Leviton IPLo6

Lutron LECL-153PH

Lutron MA-PRO

Lutron MACL-153M

Lutron MSCL-OP153M

Lutron NTCL-250

Lutron NTRP-250

Lutron PD-1oWX

Lutron	PD-6WCL
Lutron	RCL-153PNL
Cooper	RF9640-ND
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-6CL
Lutron	RRD-PRO
Satco	S11268
Cooper	SUF7
Leviton	TSL06
Leviton	TSM10
Cooper	VSUL06D