



Project/Job Name: _____
 Location: _____
 Fixture Type: _____
 Notes: _____

S23143 - 80/63/54 Wattage Selectable; LED HID Replacement; CCT Selectable; Extended Mogul base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable
- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	80W/63W/54W
Volts:	100V-277V
Lumens:	11200L/8820L/7560L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Dimmable only via the wattage/lumen selectable dial included on lamp
HID Equivalent :	320W/250W/200W
Operating Temperature :	-40C (-40F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Number of LEDs :	400
Burning Position :	Base Up or Down
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Light Source:	LED
Warranty:	5 Year Limited - 12 hr per day

PACKAGING

Each UPC:	045923231438
Each Quantity:	1
Each Dimensions:	11.61 x 5.51 x 5.51
Inner UPC:	20045923231432
Inner Quantity:	0
Inner Dimensions:	0.00 x 0.00 x 0.00
Case UPC:	10045923231435
Case Quantity:	4
Case Dimensions:	12.01 x 11.61 x 11.81

PHYSICAL

ANSI Base:	EX39
Base:	Mogul Extended
Finish:	White
Lens Material:	Plastic
MOD (In.):	5.11
MOL (In.):	9.96
Weight (Lbs.):	2.68
Housing Color:	Dark Gray

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-7YQW1Z
DLC Primary Use:	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)
UL/ETL File Listing:	US/CN - E356817; US/CN - E335148
UL/ETL Standard:	ANSI/UL 1598C; ANSI/UL 1993; CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

INFO

Additional Info:	Power selectable
Min Compartment Size:	Length: 9.85 in. Width: 9.85 in. Height: 10.95 in.

