



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S23148 - 27/22/18 Wattage Selectable; LED HID Replacement; CCT Selectable; Medium base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable
- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	27W/22W/18W
Volts:	100V-277V
Lumens:	3780L/3080L/2520L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Dimmable only via the wattage/lumen selectable dial included on lamp
HID Equivalent :	125W/100W/75W
Operating Temperature :	-40C (-40F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Number of LEDs :	228
Burning Position :	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Light Source:	LED
Warranty:	5 Year Limited - 12 hr per day

PACKAGING

Each UPC:	045923231483
Each Quantity:	1
Each Dimensions:	8.86 x 2.83 x 2.83
Inner UPC:	20045923231487
Inner Quantity:	12
Inner Dimensions:	12.20 x 9.25 x 9.45
Case UPC:	10045923231480
Case Quantity:	24
Case Dimensions:	19.37 x 12.99 x 10.55

INFO

Additional Info:	Power selectable
------------------	------------------

PHYSICAL

ANSI Base:	E26
Base:	Medium
Finish:	White
Lens Material:	Plastic
MOD (In.):	2.32
MOL (In.):	6.89
Weight (Lbs.):	0.66
Housing Color:	Dark Gray

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
UL/ETL File Listing:	US/CN - E356817; US/CN - E335148
UL/ETL Standard:	ANSI/UL 1598C; ANSI/UL 1993; CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions