



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S23149 - 36/27/18 Wattage Selectable; LED HID Replacement;
CCT Selectable; Medium base; 100-277 Volt; ColorQuick
Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable
- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	36W/27W/18W
Volts:	100V-277V
Lumens:	5040L/3780L/2520L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Dimmable only via the wattage/lumen selectable dial included on lamp
HID Equivalent :	150W/125W/75W
Operating Temperature :	-40C (-40F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Number of LEDs :	224
Burning Position :	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Light Source:	LED
Warranty:	5 Year Limited - 12 hr per day

PACKAGING

Each UPC:	045923231490
Each Quantity:	1
Each Dimensions:	9.80 x 3.66 x 3.66
Inner UPC:	20045923231494
Inner Quantity:	12
Inner Dimensions:	15.55 x 11.61 x 10.39
Case UPC:	10045923231497
Case Quantity:	24
Case Dimensions:	24.02 x 16.34 x 11.42

INFO

Additional Info:	Power selectable
------------------	------------------

PHYSICAL

ANSI Base:	E26
Base:	Medium
Finish:	White
Lens Material:	Plastic
MOD (In.):	3.35
MOL (In.):	8.27
Weight (Lbs.):	1.34
Housing Color:	Dark Gray

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
UL/ETL File Listing:	US/CN - E356817; US/CN - E335148
UL/ETL Standard:	ANSI/UL 1598C; ANSI/UL 1993; CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions