



#### ELECTRICAL

Technology:	LED
Watts:	63W/54W/45W
Volts:	100V-277V
Lumens:	8820L/7560L/6300L
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	Dimmable only via the wattage/lumen selectable dial included on lamp
HID Equivalent :	250W/200W/175W
Operating Temperature :	-40C (-40F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Number of LEDs :	308
Burning Position :	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Light Source:	LED
Warranty:	5 Year Limited - 12 hr per day

#### PACKAGING

Each UPC:	045923231506
Each Quantity:	1
Each Dimensions:	11.57 x 3.66 x 3.66
Inner UPC:	20045923231500
Inner Quantity:	6
Inner Dimensions:	11.54 x 7.95 x 12.17
Case UPC:	10045923231503
Case Quantity:	12
Case Dimensions:	16.73 x 12.28 x 13.15

#### INFO

Additional Info:	Power selectable
Min Compartment Size:	Length: 7.88 in. Width: 7.88 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

**S23150** - 63/54/45 Wattage Selectable; LED HID Replacement; CCT Selectable; Extended Mogul base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable
- Rated for Enclosed Fixture



#### PHYSICAL

ANSI Base:	EX39
Base:	Mogul Extended
Finish:	White
Lens Material:	Plastic
MOD (In.):	3.35
MOL (In.):	10.28
Weight (Lbs.):	1.80
Housing Color:	Dark Gray

#### COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-ZHMICR
DLC Primary Use:	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)
UL/ETL File Listing:	US/CN - E356817; US/CN - E335148
UL/ETL Standard:	ANSI/UL 1598C; ANSI/UL 1993; CSA-C22.2 No. 250.1; CSA-C22.2 No. 1993
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

