SATCO® | NUVO®



Project/Job Name:

Location:

Fixture Type:

Notes:

S39720 - 25 Watt T5 LED; Miniature bi-pin base; 6500K; 50000 Average rated hours; 3400 Lumens; 120-277 Volt; Type B; Ballast Bypass; Single or Double Ended Wiring

- Rated for Enclosed Fixture

ELECTRICAL

Technology:	LED
Watts:	25W
Volts:	120V-277V
Lumens:	3400L
CRI:	83
CCT (Kelvins):	6500K
Temperature:	Daylight
Beam Spread :	180
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Fluorescent Equivalent :	54W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballast Bypass/Direct:	Ballast Bypass
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended, Double Ended
Number of LEDs :	144
THD:	<25
Power Factor :	0.9
Light Source:	LED
Warranty:	5 Year Limited - T5 LED Bulbs - Ballast Bypass

PACKAGING

Each UPC:	045923397202
Each Quantity:	1
Each Dimensions:	46.00 x 1.00 x 1.00
Case UPC:	10045923397209
Case Quantity:	25
Case Dimensions:	46.00 x 5.20 x 5.20

PHYSICAL

ANSI Base:	G5
Base:	Miniature Bi Pin
Shape:	T5
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Glass
MOD (In.):	0.83
MOL (In.):	46.00
Nominal Length:	48.00
Weight (Lbs.):	0.20
Material:	Aluminum
Housing Color:	Silver

COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified
Location Rating:	Damp
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PILKXR6N
DLC Primary Use:	Internal Driver/Line Voltage (UL Type B) Lamps
UL/ETL File Listing:	US/CN - E356817
UL/ETL Standard:	ANSI/UL 1598C; CSA-C22.2 No. 250.1
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

INFO

Tube Guard Use:	Not Approved

© Satco Products, Inc.
All rights reserved 2022

© Satco Products, Inc.
All rights reserved 2022