



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S39836 - 9.8 Watt; A19 LED; Omni-directional; 3000K; Medium base; 220 deg. Beam Angle; 120 Volt

- Rated for Enclosed Fixture



ELECTRICAL

Technology:	LED
Watts:	9.8W
Volts:	120V
Lumens:	800L
CRI:	80
CCT (Kelvins):	3000K
Temperature:	Soft White
Beam Spread :	220
Hours Rated:	25000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase
Incandescent Equivalent :	60W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Number of LEDs :	8
Power Factor :	0.81
Light Source:	LED
Warranty:	5 Year Limited - 10 hr per day

PACKAGING

Each UPC:	045923398360
Each Quantity:	1
Each Dimensions:	2.44 x 2.44 x 4.80
Inner UPC:	20045923398364
Inner Quantity:	6
Inner Dimensions:	7.80 x 5.20 x 5.12
Case UPC:	10045923398367
Case Quantity:	24
Case Dimensions:	11.22 x 8.46 x 11.30

PHYSICAL

ANSI Base:	E26
Base:	Medium
Shape:	A19
Finish:	White
MOD (In.):	2.36
MOL (In.):	4.33
Weight (Lbs.):	0.06
Material:	Plastic

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2389075
Energy Star Lamp Category:	Omnidirectional
UL/ETL File Listing:	US/CN - E335148
UL/ETL Standard:	ANSI/UL 1993; CSA-C22.2 No. 1993
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	Not For Sale In: CA



S39836 - 9.8 Watt; A19 LED; Omni-directional; 3000K; Medium base; 220 deg. Beam Angle; 120 Volt

DIMMER COMPATIBILITY

Lutron	AYCL-153P
Lutron	AYCL-253P
Lutron	CTCL-153P
Lutron	DVCL-153P
Lutron	DVCL-253P
Lutron	LECL-153P
Lutron	MACL-153M
Lutron	MACL-LFQ
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	RCL-153PNL
Lutron	SCL-153P
Lutron	STCL-153M
Lutron	TGCL-153PH
Lutron	TTCL-100H