

Automatic 12V 25A 7 Stage Battery Charger

A highly advanced automatic charger for those serious about portable power, the IC2500 can be set to suit the battery's chemistry type and features adjustable charge rate to perfectly match the size of your batteries. your batteries.



SPECIFICATIONS

PRODUCT DETAILS	
PART NO.	IC2500
TYPE	7 stage
INPUT	240VAC, 50Hz, 792W
OUTPUT	12V
OUTPUT CURRENT	2, 6, 12, 25A
MINIMUM START VOLTAGE	2.5V
BACK DRAIN	5mA
APPROVALS	Electrical Safety, EMC
CHARGE VOLTAGE	14.1V (GEL), 14.4V (AGM), 14.7V (WET), 16.0V (Calcium)

L.E.D CHARGE INDICATION			
SCREEN	Back lit LCD screen		
RED LIGHT ON	Power on		
BLUE LIGHT ON	Charging		
GREEN LIGHT ON	Fully charged and maintaining, no need to turn the charger off		
BATTERY CHARGE TIMES			
	Voltage	Battery size	Charge time
AUTOMOTIVE	12V	80-300CCA	7-24 hrs
MARINE	12V	110-4200MCA	7-24 hrs
DEEP CYCLE	12V	14-500Ah	7-24 hrs

APPLICATIONS



REPLACEMENT PARTS

- ICTEMP Temperature compensation probe
- ICREMOTE Remote control

DOCUMENTS



IC2500 Instruction Manual > [Click here](#)