



FN 15™ Patrol Carbine SBR 10.5"

Owner's Manual Addendum (36328/ 36329 LE)



We are pleased that you have chosen an FNH USA FN 15™ Patrol Carbine SBR 10.5". The FN 15™ Patrol Carbine SBR 10.5" shares the same reliability, durability, accuracy and many of the operating features as the standard FN 15™ Carbine. However, it has additional special features such as a flip up rear sight. This addendum will cover the operation of those specific features where they differ from the standard FN 15™ Carbine. The common operations and features are covered in the FN 15™ Owner's Manual supplied with your FN 15™ Patrol Carbine SBR 10.5".

WARNING

Before inspecting or making any adjustments on the FN 15™ Patrol Carbine SBR 10.5", fully read and understand completely the Owner's Manual as well as this Addendum. Place the "safety" in the on safe position, remove the magazine, open the action and ensure the chamber is empty as explained in Section 15.1 of your Owner's Manual. Always keep the muzzle pointed in a safe direction. Failure to follow these warnings may result in serious injury or death.

1. Contents of the Storage Case

- FN 15™ Patrol Carbine SBR 10.5"
- Safety lock and two keys
- One 30-round magazine
- Owner's Manual and this Addendum

WARNING


Before manipulating or making any sight adjustments, place the “safety” in the on safe position, remove the magazine, open the action and ensure the chamber is empty as explained in Section 15.1 of your Owner’s Manual. Always keep the muzzle pointed in a safe direction. Failure to follow these warnings may result in serious injury or death.

2.1 Deploying and folding the Rear Sight

2.1.1 Deploying; To deploy the rear sight from the folded position, simply rotate the sight assembly up and forward. It will lock into the deployed position. The large aperture will initially be visible. Like the rear sight aperture on the basic carbine, the rear sight can be used with either the large aperture or the small aperture for more precise aiming. See Section 17.3 in your Owner’s Manual.



2.1.2 Folding; To fold or stow the rear sight, first ensure the large aperture is up. Then push in on the button on the left side of the sight and fold the sight assembly down and back until it locks into the stowed position.



2.2 Zeroing; The Samson Manual Flip-Up rear sight is adjustable for windage only. Elevation adjustments are made on the front sight as explained in Sections 17.2 and 17.3 of your Owner’s Manual. The front sight should be zeroed at the desired distance with the small aperture up on the rear sight.

2.2.1 Rear Sight Adjustment; Windage adjustments to the Samson Manual Flip-Up rear sight are done by rotating the windage knob located on the right side of the sight assembly. Rotating the windage knob clockwise will move the point of impact right. Rotating the windage knob counterclockwise moves the point of impact left. Each click on the windage knob equals approximately $\frac{1}{4}$ MOA. See Table 1 on Page 36 of your Owner’s Manual for details.



2. Rear Sight Use and Adjustment; The Samson Manual Flip-Up rear sight is provided as a primary sighting system or back-up sighting system if an optic is also being used. The Samson Flip-Up sight will fold down when not in use and can be quickly deployed when needed. It is adjustable for windage and has two apertures, one for close engagements and one for more distant targets.

WARNING

Before removing, moving or reattaching the rear sight, place the “safety” in the on safe position, remove the magazine, open the action and ensure the chamber is empty as explained in Section 15.1 of your Owner’s Manual. Always keep the muzzle pointed in a safe direction. Failure to follow these warnings may result in serious injury or death.

2.3 Rear Sight Removal; Removal or moving of the rear sight is easily accomplished with a 5/32nd inch hex wrench (not included). First, place the “safety” in the on safe position and completely clear the carbine as explained in Section 15.1 in your Owner’s Manual. The rear sight is meant to be mounted in the rear-most position on the receiver top rail.



2.3.1 Sight Removal; Insert a 5/32nd inch hex wrench in the locking screw located on the left side of the sight assembly. Turn the screw counterclockwise to loosen. It is not necessary to completely remove the screw in order to remove the sight.

2.3.2 Sight Installation; To install the rear sight, ensure the locking screw is loose and the locking lug on the right side is extended. Rotate the sight onto the rail from the left side, ensuring the locking screw aligns with one of the T-slots on the receiver. Record which rail T-slot for future reference. Rotate the sight onto the rail until it sits level on the rail. Tighten the locking screw on the left side using a 5/32nd inch hex wrench ensuring the locking lug on the right side grabs the rail and secures the sight to the rail. Do not over tighten the locking screw.



WARNING

Before installing any sights, lasers or other devices on the carbine, place the “safety” in the on safe position, remove the magazine, open the action and ensure the chamber is empty as explained in Section 15.1 of your Owner’s Manual. Always keep the muzzle pointed in a safe direction. Failure to follow these warnings may result in serious injury or death.

4. Technical Specifications

Specification	FN 15™ Patrol Carbine SBR 10.5"
SKU / Product Number	36328/36329 (LE)
Caliber	5.56mm NATO
Barrel length (effective)	10.5"
Twist Rate	1:7" RH
Barrel Material	4140 Alloy Steel, button broached, chrome plated
Muzzle device	A2-style compensator
Sights	A2-style front (F height), Samson Mfg. Manual Flip-Up Rear FRS-A2
Sight Radius	14 ¾"
Stock	Collapsible, 6-position, Black
Forearm	Standard Carbine hand guard w/ heat shield
Weight (with empty magazine and sight)	5.92 lbs
Length	26.5" – 30"
Width	2.75"
Height (with magazine and sight deployed)	10.¼"
Length of Pull	10¼" – 13.5"
Magazine (one each)	GI pattern 30-roundaluminum
Trigger Pull	4.75-7.75 lbs

*All measurements are approximate

If you have any questions about your FN 15™ Patrol Carbine SBR 10.5" or these instructions, please feel free to contact us at 1.855.536.4872 or by email at: customerservice@fnhusa.com

FNH-FN15™ SBR 10.5" Patrol Carbine – 150601 - P/N: 36169-03