

FN 15® SRP Tactical Owner's Manual Addendum 36369-02



We are pleased that you have chosen an FN 15® SRP Tactical. The FN 15® SRP Tactical shares the same reliability, durability, accuracy and many of the operating features as the standard FN 15® Carbine. This addendum will cover the operation of those specific features, if needed, where they differ from the standard FN 15® Carbine. The common operations and features are covered in the FN 15® Owner's Manual supplied with your FN 15® SRP Tactical.

WARNING

Before inspecting or making any adjustments on the FN 15® SRP Tactical fully read and understands completely the Owner's Manual as well as this Addendum. Place the "safety" in the on safe position, remove the magazine, open the action and ensure the chamber is empty as explained in Section 15.1 of your Owner's Manual. Always keep the muzzle pointed in a safe direction. Failure to follow these warnings may result in serious injury or death.

1. Contents of the Storage Case

- ♣ FN 15® SRP Tactical
- One 30-round magazine
- Owner's Manual and this Addendum
- Safety lock and two

2. Free Float Hand-guard

M-LOK compatible featuring five quick detach sling swivel sockets. The Midwest Industries, Inc. SSM M-LOK ™ 12" lightweight free-float forearm/rail assembly is installed on the FN 15® SRP Tactical in place of the standard round handguards. The SSM M-LOK™ rail assembly extends over a low-profile gas block. It allows for mounting of additional grips, sights, laser devices and other accessories onto a rigid, free-float forearm. Limited top mount Mil-Std M-1913 rails at the front and back of the forearm allow for mounting of sights at the normal F1 height. M-LOK™ slots fill the rest of the top rail. M-LOK™ mounting accessories and options are available directly from Magpul®. (www.magpul.com) Please refer to your individual accessory's instructions for correct mounting

3. Tactical Carbine with a pinned and welded compensator



WARNING

Before installing any sights, lasers or other devices on the carbine, place the "safety" in the on safe position, remove the magazine, open the action and ensure the chamber is empty as explained in Section 15.1 of your Owner's Manual. Always keep the muzzle pointed in a safe direction. Failure to follow these warnings may result in serious injury or death.

3. Technical Specifications

| Specification | FN 15® SRP Tactical Carbine | | |
|------------------------------|--|--|--|
| SKU / Product Number | 36369-02 LE | | |
| Caliber | 5.56x45MM NATO | | |
| Barrel length (effective) | 16" with a Pinned – Welded Compensator | | |
| | 1:7" RH | | |
| Barrel Material | 4140 Alloy Steel, button broached, chrome plated | | |
| Muzzle device | A2-style compensator | | |
| Sights | N/A, Optics ready | | |
| Sight Radius | N/A, Optics ready | | |
| Stock | Collapsible, 6 position, Black | | |
| Forearm | MI-SSM M-LOK 12" w/ Picatinny rail at 12 o'clock position. T – | | |
| | marked for accessory location | | |
| Weight (with empty magazine) | 6.025 lbs. | | |
| Length | 30.75" – 34" | | |
| Width | 2.75" | | |
| Height (with magazine) | 8.75" | | |
| Length of Pull | 10¼" – 13.5" | | |
| Magazine (one each) | GI pattern 30 rd aluminum | | |
| Trigger Pull | 4.75-7.75 lbs. | | |

^{*}All measurements are approximate

If you have any questions about your FN 15® SRP Tactical or these instructions, please free to contact us at 1.800.635.1321 or by email at customerservice@fnamerica.com

FN 15® SRP Tactical – AUG092017_JPR - P/N: 36369-22

<u>Notes</u>

THIS PAGE LEFT BLANK INTENTIONALLY