


LightStack™ UHD Plug and Play Fiber Enclosure

Available In - Europe | Eurasia | India | Middle East | Africa | Latin America | Asia Pacific | China

The LightStack UHD Fiber Enclosure is a cost-effective and space-saving solution for ultra high density plug and play fiber applications. This compact enclosure packs 144 fibers in 1U with MTP-to-LC connectivity all in a 5 in. (128mm) deep unit. The simplified, self-contained design optimizes shipping, handling, and installation especially in space-limited environments. The LightStack UHD Enclosure provides low loss performance to accommodate a wide range of channel configurations for both Multimode and Singlemode applications. The integrated shuttered LC adapters feature an internal door that opens without touching the connector end face and springs back to the closed position automatically, protecting empty ports from dust and debris. Optional front and rear cable managers are available to control and protect cables. The front cable manager features an integrated door which is removable to allow full access to the LC connectivity. The door swings open to allow visibility to the integrated labeling strip. The rear cable manager simply hooks into the back of the enclosure to support incoming MTP cable assemblies.



Features

- Ultra high density 144 fibers in 1U
- Compact LC to MTP transition enclosure
- Low loss optical performance
- Base-8 and Base-12 versions
- Optional cable management
- Singlemode and Multimode options Available




Patch Cords

Siemon's LC BladePatch® push-pull patch cords are highly recommended to provide optimal accessibility. An extraction tool is required when using traditional LC connectors.



Front Cable Management

Removable front door on optional front cable manager allows full access to LC ports



Rear Cable Management

Optional rear cable manager with toolless attachment



Easy Access MTP Ports

MTP ports on back for trunk connections



Space Saving Design

Compact footprint with 5 in. (128mm) depth to fit shallow applications

Product Information

Mechanical Specifications and Compliance


Height (nominal)	1U
Height (actual)	1.74 in. (4.24mm)
Enclosure Dimensions	5.10 in. (128.7mm) D x 19 in. (482.6mm) W x 1.74 in. (4.24mm) H
Label Size	8.05 in. x .925 in. (204.5mm x 23.5mm)
Rack Mounting Brackets	2 horizontal positions
Mounting	CEA-310-E 19 in. (482.6mm) rack
Front Cable Manager Dimensions	5.6 in. (143.4mm) D x 19 in. (482.6mm) W x 1.7 in. (43.2mm) H
Rear Cable Manager Dimensions	6.7 in. (170.6mm) D x 16.9 in. (428.8mm) W x 1.2 in. (30.5mm) H
Color (Enclosure)	Black (RAL 9005)
Color (Ports)	Multimode: Aqua LC, Aqua MTP method C, Gray MTP method B Singlemode: Blue LC, Black MTP
Panel Material	16 gauge cold rolled steel
Green Features	RoHS, Lead-Free, Halogen-Free, PVC Free
Compliance	ISO/IEC 11801-1 ED1.0, TIA-568.3-D

Optical Performance Specifications

	Insertion Loss (dB)		Return Loss (dB)	
	Multimode	Singlemode	Multimode	Singlemode
MTP	0.20	20	0.60	60
LC	0.15	30	0.40	55
MTP to LC Enclosure	0.35	20	1.00	55

Part Numbers

LightStack UHD Enclosures



Cable Managers

Cable managers help route cables while ensuring proper bend radius. Front manager attaches to rack screws, while rear manager has toolless connections to the back of the enclosure.

Part Number	Description
FHD-FCM-1U-01	Front cable manager with door
FHD-RCM-1U-01	Rear cable manager

Because we continuously improve our products, Siemon reserves the right to change specifications and availability without prior notice.

North America P: (1) 860 945 4200	Asia Pacific P: (61) 2 8977 7500	Latin America P: (571) 657 1950/51/52	Europe P: (44) 0 1932 571771	China P: (86) 215385 0303	India, Middle East & Africa P: (971) 4 3689743
---	--	---	--	-------------------------------------	--

Siemon Interconnect Solutions
P: (1) 860 945 4213
www.siemon.com/SIS

WWW.SIEMON.COM

SS_Fiber_LightStackUHDPlugandPlayFiberEnclosure_INT_RevD 05/21

