

4 Port USB to RS232 Serial DB9 Adapter Hub

Add four RS232 serial ports to any notebook or desktop computer using a single USB port

Model No.: 4XRS232-B

Version: v1.0

The flykantech.com 4XRS232-B is a versatile 4-port USB to RS-232 serial interface converter designed for seamless connectivity between USB-enabled computers and RS-232 serial devices. It supports a wide range of serial data formats including 5, 6, 7, and 8 bits, with baud rates from 50bps up to 921.6Kbps. Each of its four serial ports features a 1024-byte FIFO for upstream data and a 512-byte FIFO for downstream data, ensuring efficient and reliable data transfer. Compatible with both Windows and Linux operating systems, the 4XRS232-B offers flexibility in integration across various platforms.



Features

- 4-port USB to RS232 serial adapter
- Fully compliant with USB 1.1; USB 2.0 compatible
- No IRQ, DMA, I/O address resources required
- Baud Rate up to 921.6 Kbps
- No external power adapter required
- Compatible with Windows 11, & Linux

Applications

- Ideal for PLC Starters or Professional Ones.
- Perfect for controlling/diagnosing manufacturing machines(CNC, Process Control Equipment, Bar Code Scanners)
- Connect, and control industrial/automotive sensors and equipment
- Connect a satellite receiver, serial modem, or PDA with serial sync
- Connect & program LED and Digital signage boards w/ serial ports

Technical Specifications

Connector A	1 x USB Type-A (4 pin) USB 2.0
Connector B	4 x DB-9 (9 pin, D-Sub), Male
Chipset ID	AX78140
LED indicators	4 x LEDs
Industry Standards	USB 1.1/2.0 / RS232
Serial Protocol	RS-232
Max Baud Rate	921.6 Kbps
Data Bits & FIFO	4, 5, 6, 7, 8 192 Bytes
Flow Control	None, Xon/ Xoff, Hardware
Parity	None, Even, Odd, Mark, Space
Stop Bits	1, 1.5, or 2 stop bits
Material	ABS
Cable Length	Abt. 1m (Note 1)

Related Products

USB232A-B	1-Port USB to RS232 w/ 3 LED	2016
USB232A-E	1-Port USB to RS232 w/ 9 LED	2021
4XRS232	4-Port USB to RS232 Hub	2021
RS Gender Changer		
RD232F2F	RS232 Gender Changer (F/F)	-
RD232M2M	RS232 Gender Changer (M/M)	-
Console Cable		
U2RJ45-FT181	USB RJ45 Cisco console cable	2020
Null Modem		
NM232F2F/NM232M2M		-

Accessories

1 X 4XRS232-B

Note 1 - The total USB cable length should not be > 5m due to USB 2.0's Limitation.

Note 2 - Cannot be used with serial mouse or keyboard.

Note 3 - The 4XRS232-B doesn't support all Printers w/ Serial Interface. (Some branded has their own configurations.)

Fly Kan Tech Co., Limited (HK) | Shenzhen VTOP Electronic Co., Limited(Mainland)

Tel: +86-755-85288085 Fax: +86-755-85288085 Email: sales@flykantech.com

4XRS232-B

<https://www.flykantech.com>

Updated on 2023/02/18