

HDMI to RCA Converter Box with Audio

Composite Video Adapter | NTSC/PAL | 1080p |

Model No.: HD2R01-P2

Version: v2.0

| HDMI to Composite Converter Box | NTSC/PAL | 1920 x 1080 | mini USB Power | 480i |

The HD2R01-P2 HDMI to RCA Converter Box with Audio – a sleek solution that seamlessly connects digital HDMI sources to analog RCA TVs and displays. It supports both NTSC and PAL systems. Experience superior image quality with advanced features like noise reduction, frame rate conversion, and adaptive contrast enhancement, ensuring a visually stunning display. Capable of handling high-definition resolutions up to 1080p, this RCA adapter effortlessly transforms HDMI signals into crystal-clear composite video and audio for an immersive viewing experience.

With its lightweight and portable design, the HD2R01-P2 offers versatile usage in any setting, providing flexibility beyond the living room. This RCA converter box is broadly compatible with various HDTV and PC input resolutions, making it ideal for integrating cutting-edge devices with existing legacy displays. Unlock the potential of HDMI-equipped devices on older TVs without costly upgrades. This cost-effective solution ensures a seamless integration experience. Designed for simplicity, the HD2R01 HDMI to RCA Converter allows hassle-free installation and operation – just plug in and enjoy.



Applications

- Convert your HDMI signal to RCA composite video
- Ideal for presentations that use dated projection systems
- Stream your new home videos onto your older TVs/displays

Main Features

- Converts HDMI into analog RCA video and audio.
- Max. supported resolution - 1920 x 1080p
- Supports NTSC/PAL formats - 480i(720x480)
- Powered by mini-USB Cable
- Plug-and-play installation.
- No driver installation is required



**Product appearance and specifications are subject to change without notice.*

Specifications

Connector(s)	1 - HDMI (19 pin)
	1 - Composite Video (1 x RCA)
	1 - Stereo Audio (2 x RCA)
Supported Resolutions	Max. 1920x1080
Audio Support	Analog 2-channel (2 x RCA)
Compatible Signals	NTSC/PAL
Housing/Jacket Material	ABS/PVC
Operating Temperature	0°C to 40°C
Storage Temperature	0°C to 45°C
Humidity	20%-90%
Dimensions (approx.)	W60xD55xH20mm
Product Weight	Abt. 40g

Importants

1. Cannot convert Composite signals into HDMI signals.
2. This product is primarily designed for use with computers. HDMI devices other than computers, such as DVD players, BD players, and smartphones, may experience abnormal output.
3. Requires connection to a USB power cable for normal operation.
4. The display quality itself will be equivalent to 480i (equivalent to SD quality) resolution.