

INDUCTION CHARGER TABLE



Item Numbers

- ☐ DXICTABLEM
(Mobile, with casters)
- ☐ DXICTABLE
(Stationary)

Application

The Dinex® Induction Charger Table is designed to hold the Power•Therm, Smart•Therm STSII and Turbo•Temp Chargers as well as two stacks of bases. Dinex® offers stationary and mobile units (with and without casters).

Construction

Top is constructed of 14-gauge type 304 stainless steel with a No. 4 finish and has a full marine "V" edge. Top has 14-gauge under brace hat channels welded in place for additional support.

Legs are 1.625" (4cm) 16-gauge stainless steel round tubing fully welded to top hat channel under brace support and under shelf.

Under shelf is constructed of 16-gauge type 304 stainless steel with a No. 4 finish welded to legs.

Mobile units come with four 4" (10cm) swivel polyurethane casters, two with brakes.


Warranty

One year parts and labor.


DINEX®

Building 2, Suite 106
628 Hebron Avenue
Glastonbury, CT 06033
800.523.9752 Fax: 860.652.3135
www.dinex.com


INDUCTION CHARGER TABLE




Top View




Top View




Front View



Side View



Front View



Side View

Items and Dimensions

ITEM NUMBER	MODEL NUMBER	LENGTH	DEPTH	HEIGHT	FREIGHT CLASS	SHIP WEIGHT	SHIP CUBE
DXICTABLEM	ICTABLEM	30" (76cm)	24" (61cm)	30.12" (76.5cm)	125	210 lb. (95.3kg)	14.7
DXICTABLE	ICTABLE	30" (76cm)	24" (61cm)	30.12" (76.5cm)	125	210 lb. (95.3kg)	14.7



Please confirm that you have the most current specification sheet by visiting www.dinex.com.
Dinex® reserves the right to change specifications and product design without notice.
Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

Printed in USA

DINEX®

Building 2, Suite 106
628 Hebron Avenue
Glastonbury, CT 06033
800.523.9752 Fax: 860.652.3135
www.dinex.com

115-REV 10/09