# **BUNN**°

# 12 Cup Dual-Voltage Automatic Coffee Brewer with 3 Warmers

ITEM#	
PROJECT	
11100201	



#### **Model CWTF-DV**

(2 top warmers) (decanters sold separately) Dimensions: 18.9" H x 8.5" W x 17.8" D (48cm H x 21.6cm W x 45.2cm D)

### Features

### **Dual-Voltage Automatic Coffee Brewer**

- Brews 3.8 to 7.5 (14.4 to 28.4 liters) gallons of perfect coffee per hour.
- Model is space-saving 8.5" (21.6 cm) wide.
- All stainless steel construction.
- Hot water faucet and pourover feature on all models.
- SplashGard® funnel deflects hot liquids away from the hand.

\*Dual voltage adaptable, can operate at 120V/15amp or 208-240V/20amp.



#### **Model CWTF-DV**

DATE

(3 lower warmers) (decanters sold separately) Dimensions: 17" H x 16.5" W x 17.7" D (43.2cm H x 41.9cm W x 45cm D)

For current specification sheets and other information, go to www.bunn.com.

# Related Products

Easy Clear® EQ-17-TL

Product No.: 30200.1000

Dimensions:

 $12\frac{7}{16}$ " H x  $2\frac{1}{2}$ " W x 3" D 31.6 cm H x 6.35 cm W x 7.62 cm D

Easy Clear® ED-17-TL

Product No.: 30201.1001 Dimensions:  $8\frac{1}{4}$ " H x  $2\frac{5}{16}$ " Dia.

20.95 cm H x 5.87 cm Dia.



#### **Paper Filter Pack**

Product No.: 20115.0000 Packed per case: 1,000

Dimensions:  $4\frac{1}{4}$ " Base x  $2\frac{3}{4}$ " Sidewall

10.8 cm Base x 6.98 cm Sidewall

Easy Pour® black decanter Product No.: 06100.0101

Quantity: 1 (also packaged in

quantities of 2, 3, 6, 12, & 24)

### 1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No.: 12487.00013 RWS1 Product No.: 12203.0010 \*Also available with side handles

or black decor

RWS1A Product No.: 12203.0011

### Easy Pour® orange decanter (for decaf)

Product No.: 06101.0101 Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



Model	Agency Listing	International Model	Agency Listing
CWTF-DV	(Ui) (NSF)	No International model	

# Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CWTF-DV	12950.0410	120	13.9	1320	1670	3.8 gal./hr.	4.0	35 lbs. (15.9 kg)	No
(2 upper, 1 low	er warmer)	120/208*	13.9	2288	2650	6.5 gal./hr.	4.0	35 lbs. (15.9 kg)	
		120/240*	15.6	3046	3400	7.5 gal./hr.	4.0	35 lbs. (15.9 kg)	
CWTF-DV	12950.0409	120	13.9	1320	1670	3.8 gal./hr.	6.7	39 lbs. (17.7 kg)	No
(3 lower warm	ers)	120/208*	13.9	2288	2640	6.5 gal./hr.	6.7	39 lbs. (17.7 kg)	
	-	120/240*	15.6	3046	3400	7.5 gal./hr.	6.7	39 lbs. (17.7 kg)	


<sup>\*120/208-240</sup>V, 13.9-15.6A, 2640-3400W. "Factory wired" products utilize same product numbers on dataplate to calculate tank heater range. **Brewing capacity:** based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Electrical: If wired for 120V, requires 2-wires plus ground service rated 120V, single phase, 60 Hz.

If wired for 120/208V or 120/240V, requires 3-wires plus ground service rated 120/208V

or 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 1/4" male flare fitting.



BUNN Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.