

**BIMAX® EOEMA****Safety Data Sheet 9015**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date: 07/05/2023

Revision date: 08/12/2026

Supersedes: 07/05/2023

Version: 2.0

SECTION 1: Identification**1.1. Identification**

Product name : BIMAX® EOEMA
 Product code : 9015
 Product form : Substance
 Physical state : Liquid
 Formula : C₈H₁₄O₃
 Chemical name : 2-ETHOXYETHYL METHACRYLATE

1.2. Recommended use and restrictions on use

Recommended use : Manufacture of substances
 Laboratory chemicals

1.3. Supplier

GELEST, INC.
 158 Industrial Road
 Glen Rock, PA 17327
 USA
 T 717-227-1774 - F 717-227-1775 (M-F): 8:00 AM - 5:30 PM EST
CS-Gelest@m-chem.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Flammable liquid, Category 4	H227	Combustible liquid.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Reproductive toxicity, Category 1B	H360	May damage fertility or the unborn child.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H227 - Combustible liquid
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H360 - May damage fertility or the unborn child

Precautionary statements (GHS US)

: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye and face protection.
P302+P352 - If on skin: Wash with plenty of soap and water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P332+P313 - If skin irritation occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use dry extinguishing powder, alcohol resistant foam, carbon dioxide (CO₂) to extinguish.
P403 - Store in a well-ventilated place.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards not otherwise classified (HNOC)

Other hazards which do not result in classification : Hazardous polymerization may occur if exposed to high temperature.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : BIMAX® EOEMA
CAS-No. : 2370-63-0

Name	Product identifier	%	GHS US classification
2-Ethoxyethyl methacrylate	CAS-No.: 2370-63-0	≥ 99	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Gently wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.
Chronic symptoms : May damage fertility or the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures**5.1. Suitable (and unsuitable) extinguishing media**

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Avoid the use of streaming water, as this may spread the fire.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.
Explosion hazard : No direct explosion hazard.
Reactivity : The product is non-reactive under normal conditions of use, storage and transport. Hazardous polymerization may occur if exposed to high temperature.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Combustion products may include the following: carbon oxides (CO, CO₂).

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

General measures : Stop leak if safe to do so. Absorb spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

BIMAX® EOEMA

Safety Data Sheet

Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Ensure good ventilation of the work station. Avoid breathing fume, mist, vapors, spray. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed in a dry and well-ventilated place away from heat sources. Store locked up.
Incompatible materials for storage	: Acids. Bases. Strong oxidizing agents. Peroxides.
Storage temperature	: < 32 °C
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless Liquid.
Molecular mass	: 158.2 g/mol
Color	: Colorless.
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 70 °C at 22 Torr
Flash point	: 69.5 °C Atm. press.: 1013 hPa
Auto-ignition temperature	: 205 °C
Decomposition temperature	: 185 °C
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 9.6 Pa at 20 °C
Relative vapor density at 20°C	: No data available

BIMAX® EOEMA

Safety Data Sheet

Relative density	: ≈ 0.963 at 20 °C
Density	: 0.9632 g/cm ³ at 20 °C
Solubility	: Water: 17.05 g/l
Partition coefficient n-octanol/water (Log Pow)	: 1.8 at 23.3 °C
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available
Particle characteristics	: Particle size : Not applicable

2-Ethoxyethyl methacrylate

Particle characteristics	Particle size : Not applicable
--------------------------	--------------------------------

9.2. Other information

Other properties : Self-accelerating Polymerization Temperature (SAPT) $\leq 75^{\circ}\text{C}$ (tested according to UN Test H.4).

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Hazardous polymerization may occur if exposed to high temperature.

10.2. Chemical stability

Stable under normal temperatures and pressures. Contains the following stabilizer: HQ. Polymerization can occur at elevated temperatures.

10.3. Possibility of hazardous reactions

Hazardous polymerization can occur at temperatures $\leq 75^{\circ}\text{C}$.

10.4. Conditions to avoid

Heat. flames. Light.

10.5. Incompatible materials

Acids. Bases. Strong oxidizing agents. Peroxides.

10.6. Hazardous decomposition products

No data available. In the event of fire: see section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Skin and eye contact
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-Ethoxyethyl methacrylate (2370-63-0)

LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified

BIMAX® EOEMA

Safety Data Sheet

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

2-Ethoxyethyl methacrylate (2370-63-0)

LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
---------------------------------------	---

Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Eye irritation.
Chronic symptoms	: May damage fertility or the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

2-Ethoxyethyl methacrylate (2370-63-0)

LC50 - Fish [1]	48.7 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 72h - Algae [1]	> 184.2 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	37 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

BIMAX® EOEMA

Safety Data Sheet

DOT	TDG	IMDG	IATA
14.1. UN number			
UN3532	UN3532	3532	3532
14.2. Proper Shipping Name			
Polymerizing substance, liquid, stabilized, n.o.s (2-Ethoxyethyl methacrylate)	POLYMERIZING SUBSTANCE LIQUID, STABILIZED, N.O.S. (2-ETHOXYETHYL METHACRYLATE)	POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (2-ETHOXYETHYL METHACRYLATE)	Polymerizing substance, liquid, stabilized, n.o.s. (2-Ethoxyethyl methacrylate)
Transport document description			
UN3532 Polymerizing substance, liquid, stabilized, n.o.s (2-Ethoxyethyl methacrylate), 4.1, III	UN3532 POLYMERIZING SUBSTANCE LIQUID, STABILIZED, N.O.S. (2-ETHOXYETHYL METHACRYLATE), 4.1, III	UN 3532 POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (2-ETHOXYETHYL METHACRYLATE), 4.1, III	UN 3532 Polymerizing substance, liquid, stabilized, n.o.s. (2-Ethoxyethyl methacrylate), 4.1, III
14.3. Transport hazard class(es)			
4.1	4.1	4.1	4.1
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

DOT

UN-No. (DOT)

: UN3532

BIMAX® EOEMA

Safety Data Sheet

DOT Special Provisions (49 CFR 172.102)	: 387 - When materials are stabilized by temperature control, the provisions of §173.21(f) of this subchapter apply. When chemical stabilization is employed, the person offering the material for transport shall ensure that the level of stabilization is sufficient to prevent the material as packaged from dangerous polymerization at 50 °C (122 °F). If chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required and is forbidden by aircraft. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging and the effect of any insulation present, the temperature of the material when offered for transport, the duration of the journey, and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g.requirements to protect from sources of heat, including other cargo carried at a temperature above ambient) and any other relevant factors. The provisions of this special provision will be effective until January 2, 2019, unless we terminate them earlier or extend them beyond that date by notice of a final rule in the Federal Register. 421 - This entry will no longer be effective on January 2, 2019 unless we terminate it earlier or extend it beyond that date by notice of a final rule in the Federal Register. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). IP19 - For UN identification numbers 3531, 3532, 3533, and 3534, IBCs must be designed and constructed to permit the release of gas or vapor to prevent a build-up of pressure that could rupture the IBCs in the event of loss of stabilization. N92 - Notwithstanding the provisions of §173.24(g) of this subchapter, packagings shall be designed and constructed to permit the release of gas or vapor to prevent a build-up of pressure that could rupture the packagings in the event of loss of stabilization. T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP4 - The maximum degree of filling for portable tanks must not exceed 90%. TP6 - The tank must be equipped with a pressure release device which prevent a tank from bursting under fire engulfment conditions (the conditions prescribed in CGA pamphlet S1.2 (see 171.7 of this subchapter) or alternative conditions approved by the Associate Administrator may be used to consider the fire engulfment condition), taking into account the properties of the hazardous material to be transported.
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 10 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 25 L
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat,52 - Stow "separated from" acids,53 - Stow "separated from" alkaline compounds
TDG UN-No. (TDG)	: UN3532

BIMAX® EOEMA

Safety Data Sheet

TDG Special Provisions

: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks.

2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act", 155 - (1) If these dangerous goods are stabilized by temperature control, they must be offered for transport, handled and transported in accordance with section 7.1.6 of the UN Recommendations. (2) If chemical stabilization is employed, the person offering the means of containment for transport must ensure that the level of stabilization will prevent a dangerous polymerization of the dangerous goods at a bulk mean temperature of 50°C in the case of a small means of containment or an intermediate bulk container (IBC) or, in the case of a large means of containment that is not an IBC, at a bulk mean temperature of 45°C. (3) If chemical stabilization may become ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In determining whether chemical stabilization may become ineffective at lower temperatures, the person offering the means of containment for transport must take at least the following factors into consideration: (a) the capacity and geometry of the means of containment and the effect of any insulation; (b) the temperature of the dangerous goods when offered for transport; (c) the duration of the transport and the seasonal ambient temperature conditions typically encountered during transport; and (d) the effectiveness and other physical or chemical properties of the stabilizer employed.

SOR/2017-137

Explosive Limit and Limited Quantity Index : 0
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 10 L
Emergency Response Guide (ERG) Number : 149P

IMDG

Special provision (IMDG) : 274, 386
Limited quantities (IMDG) : 0
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P001
Packing provisions (IMDG) : PP93
IBC packing instructions (IMDG) : IBC03
IBC special provisions (IMDG) : B19
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP4, TP6
EmS-No. (Fire) : F-J - FIRE SCHEDULE Juliet - NON-TEMPERATURE-CONTROLLED SELF-REACTIVES AND ORGANIC PEROXIDES
EmS-No. (Spillage) : S-G - SPILLAGE SCHEDULE Golf - FLAMMABLE SOLIDS AND SELF-REACTIVE SUBSTANCES
Stowage category (IMDG) : D
Stowage and handling (IMDG) : SW1
Segregation (IMDG) : SG35, SG36
Properties and observations (IMDG) : Polymerizes at elevated temperatures or in a fire. Burns vigorously. Immiscible with water. Contact with alkalis or acids may cause dangerous polymerization. The products of combustion or self-accelerating polymerization may be toxic by inhalation.

IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity (IATA) : Forbidden

BIMAX® EOEMA

Safety Data Sheet

PCA packing instructions (IATA)	: 459
PCA max net quantity (IATA)	: 10L
CAO packing instructions (IATA)	: 459
CAO max net quantity (IATA)	: 25L
Special provision (IATA)	: A209
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
2-Ethoxyethyl methacrylate	2370-63-0	Present	Active	

15.2. International regulations

CANADA

2-Ethoxyethyl methacrylate (2370-63-0)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements

H227	Combustible liquid
H315	Causes skin irritation
H319	Causes serious eye irritation
H360	May damage fertility or the unborn child

BIMAX® EOEMA

Safety Data Sheet

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



Issue date: 07/05/2023

Revision date: 08/12/2026

Supersedes: 07/05/2023

Version: 2.0

SDS US (GHS HazCom 2012) - Custom

Judgments as to the suitability of information herein are the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, Gelest, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information to the purchaser's intended purpose or for consequences of its use. All statements relate only to the specific material designated herein, as shipped, and do not relate to use in combination with any other material or process. This document was prepared to comply with the requirements for SDS documentation in the United States (Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and may not address other regulatory requirements, and we do not guarantee that hazards listed herein are the only existing hazards. Nothing herein shall be considered to be instructions for any use which infringes a valid patent nor shall it be considered a license under any patent or other intellectual property. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used and safe handling thereof. We are not responsible for SDS documentation not received directly from us.

© 2025 Gelest Inc. Glen Rock, PA 17327