

**BIMAX® HEMA-HP2**

Safety Data Sheet 9022HP2

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date: 03/09/2026

Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product name	: BIMAX® HEMA-HP2
Product code	: 9022HP2
Product form	: Substance
Physical state	: Liquid
Formula	: C6H10O3
Chemical family	: METHACRYLATE
Chemical name	: 2-HYDROXYETHYL METHACRYLATE

1.2. Recommended use and restrictions on use

Recommended use	: Chemical intermediate Laboratory chemicals
-----------------	---

1.3. Supplier

GELEST, INC.
158 Industrial Road
Glen Rock, PA 17327
USA
T 717-227-1774 - F 717-227-1775 (M-F): 8:00 AM - 5:30 PM EST
CS-Gelest@m-chem.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements (GHS US)

: P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye and face protection.
P302+P352 - If on skin: Wash with plenty of water.

BIMAX® HEMA-HP2

Safety Data Sheet

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards not otherwise classified (HNOC)

Other hazards which do not result in classification : Hazardous polymerization may occur if exposed to high temperature.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : BIMAX® HEMA-HP2
CAS-No. : 868-77-9

Name	Product identifier	%	GHS US classification
2-hydroxyethyl methacrylate	CAS-No.: 868-77-9	≥ 99.5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Ethylene glycol dimethacrylate	CAS-No.: 97-90-5	≤ 0.4	Skin Sens. 1, H317 STOT SE 3, H335
Diethylene glycol monomethacrylate	CAS-No.: 2351-43-1	≤ 0.4	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H336 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.
Chronic symptoms : Sensitization to this material has been observed with repeated use.

BIMAX® HEMA-HP2

Safety Data Sheet

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Avoid the use of streaming water, as this may spread the fire.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Hazardous polymerization may cause containers to rupture.
Storage conditions : Keep container tightly closed in a dry and well-ventilated place away from heat sources.
Incompatible materials : Free radical initiators. Oxidizing agents. Reducing agents. Iron.

BIMAX® HEMA-HP2

Safety Data Sheet

Storage temperature : < 32 °C (Recommended)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless Liquid.
Molecular mass	: 130.14 g/mol Source: ChemIDplus
Color	: Colorless.
Odor	: Ester-like.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 95 °C @ 10 mmHg
Flash point	: 97 °C Source: ICSC
Auto-ignition temperature	: 375 °C Source: ECHA
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 0.08 mm Hg Temp.: 20 °C
Relative vapor density at 20°C	: 4.5 Source: ICSC
Relative density	: 1.034 Source: HSDB
Density	: 1.073 g/cm ³ Temp.: 25 °C
Solubility	: Soluble. Water: 100000 mg/l
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: 6.337 mm ² /s
Viscosity, dynamic	: 6.8 cP @20C
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

BIMAX® HEMA-HP2

Safety Data Sheet

2-hydroxyethyl methacrylate

Particle characteristics	Particle size : Not applicable
--------------------------	--------------------------------

Ethylene glycol dimethacrylate

Particle characteristics	Particle size : Not applicable
--------------------------	--------------------------------

Diethylene glycol monomethacrylate

Particle characteristics	Particle size : Not applicable
--------------------------	--------------------------------

9.2. Other information

Other properties : Self-accelerating Polymerization Temperature (SAPT) = 75°C (tested according to UN Test H.4).

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Contains the following stabilizer(s): MEHQ.

10.3. Possibility of hazardous reactions

Hazardous polymerization can occur at temperatures ≤ 75 °C.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ultraviolet light.

10.5. Incompatible materials

Free radical initiators. Oxidizing agents. Reducing agents. Iron.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Dermal; Skin and eye contact
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-hydroxyethyl methacrylate (868-77-9)

LD50 oral rat	5564 mg/kg body weight Animal: rat
LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Animal sex: male

Ethylene glycol dimethacrylate (97-90-5)

LD50 oral rat	3300 mg/kg Source: National Library of Medicine
---------------	---

BIMAX® HEMA-HP2

Safety Data Sheet

Ethylene glycol dimethacrylate (97-90-5)

LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Remarks on results: other:
-----------------	--

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

2-hydroxyethyl methacrylate (868-77-9)

LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Remarks on results: other:

Ethylene glycol dimethacrylate (97-90-5)

LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
---------------------------------------	---

Aspiration hazard	: Not classified
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Chronic symptoms	: Sensitization to this material has been observed with repeated use.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

2-hydroxyethyl methacrylate (868-77-9)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): <i>Oryzias latipes</i>
EC50 - Crustacea [1]	380 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 72h - Algae [1]	836 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)
EC50 72h - Algae [2]	345 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)
LOEC (chronic)	49.6 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC (chronic)	24.1 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'

Ethylene glycol dimethacrylate (97-90-5)

LC50 - Fish [1]	15.95 mg/l Test organisms (species): <i>Danio rerio</i> (previous name: <i>Brachydanio rerio</i>)
EC50 - Crustacea [1]	44.9 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 72h - Algae [1]	17.3 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)
EC50 96h - Algae [1]	19 mg/l Test organisms (species): <i>Pseudokirchneriella subcapitata</i> (previous names: <i>Raphidocelis subcapitata</i> , <i>Selenastrum capricornutum</i>)

BIMAX® HEMA-HP2

Safety Data Sheet

Ethylene glycol dimethacrylate (97-90-5)

EC50 96h - Algae [2]	10.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	5.05 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-hydroxyethyl methacrylate (868-77-9)

Partition coefficient n-octanol/water (Log Pow)	0.42 Source: ICSC
---	-------------------

Ethylene glycol dimethacrylate (97-90-5)

Partition coefficient n-octanol/water (Log Pow)	1.87 Source: International Chemical Safety Cards
---	--

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.





SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN3532	UN3532	3532	3532
14.2. Proper Shipping Name			
Polymerizing substance, liquid, stabilized, n.o.s (2-Hydroxyethyl methacrylate)	POLYMERIZING SUBSTANCE LIQUID, STABILIZED, N.O.S. (2-HYDROXYETHYL METHACRYLATE)	POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (2-HYDROXYETHYL METHACRYLATE)	Polymerizing substance, liquid, stabilized, n.o.s. (2-Hydroxyethyl methacrylate)
Transport document description			
UN3532 Polymerizing substance, liquid, stabilized, n.o.s (2-Hydroxyethyl methacrylate), 4.1, III	UN3532 POLYMERIZING SUBSTANCE LIQUID, STABILIZED, N.O.S. (2-HYDROXYETHYL METHACRYLATE), 4.1, III	UN 3532 POLYMERIZING SUBSTANCE, LIQUID, STABILIZED, N.O.S. (2-HYDROXYETHYL METHACRYLATE), 4.1, III	UN 3532 Polymerizing substance, liquid, stabilized, n.o.s. (2-Hydroxyethyl methacrylate), 4.1, III
14.3. Transport hazard class(es)			
4.1	4.1	4.1	4.1

BIMAX® HEMA-HP2

Safety Data Sheet

DOT	TDG	IMDG	IATA
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Special precautions for user

DOT

UN-No. (DOT)

DOT Special Provisions (49 CFR 172.102)

: UN3532

: 387 - When materials are stabilized by temperature control, the provisions of §173.21(f) of this subchapter apply. When chemical stabilization is employed, the person offering the material for transport shall ensure that the level of stabilization is sufficient to prevent the material as packaged from dangerous polymerization at 50 °C (122 °F). If chemical stabilization becomes ineffective at lower temperatures within the anticipated duration of transport, temperature control is required and is forbidden by aircraft. In making this determination factors to be taken into consideration include, but are not limited to, the capacity and geometry of the packaging and the effect of any insulation present, the temperature of the material when offered for transport, the duration of the journey, and the ambient temperature conditions typically encountered in the journey (considering also the season of year), the effectiveness and other properties of the stabilizer employed, applicable operational controls imposed by regulation (e.g.requirements to protect from sources of heat, including other cargo carried at a temperature above ambient) and any other relevant factors. The provisions of this special provision will be effective until January 2, 2019, unless we terminate them earlier or extend them beyond that date by notice of a final rule in the Federal Register.

421 - This entry will no longer be effective on January 2, 2019 unless we terminate it earlier or extend it beyond that date by notice of a final rule in the Federal Register.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

IP19 - For UN identification numbers 3531, 3532, 3533, and 3534, IBCs must be designed and constructed to permit the release of gas or vapor to prevent a build-up of pressure that could rupture the IBCs in the event of loss of stabilization.

N92 - Notwithstanding the provisions of §173.24(g) of this subchapter, packagings shall be designed and constructed to permit the release of gas or vapor to prevent a build-up of pressure that could rupture the packagings in the event of loss of stabilization.

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP4 - The maximum degree of filling for portable tanks must not exceed 90%.

TP6 - The tank must be equipped with a pressure release device which prevent a tank from bursting under fire engulfment conditions (the conditions prescribed in CGA pamphlet S1.2 (see 171.7 of this subchapter) or alternative conditions approved by the Associate Administrator may be used to consider the fire engulfment condition), taking into account the properties of the hazardous material to be transported.

DOT Packaging Non Bulk (49 CFR 173.xxx)

: 203

DOT Packaging Bulk (49 CFR 173.xxx)

: 241

BIMAX® HEMA-HP2

Safety Data Sheet

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 10 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 25 L
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat,52 - Stow "separated from" acids,53 - Stow "separated from" alkaline compounds

TDG

UN-No. (TDG)	: UN3532
TDG Special Provisions	: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act",155 - (1)If these dangerous goods are stabilized by temperature control, they must be offered for transport, handled and transported in accordance with section 7.1.6 of the UN Recommendations. (2)If chemical stabilization is employed, the person offering the means of containment for transport must ensure that the level of stabilization will prevent a dangerous polymerization of the dangerous goods at a bulk mean temperature of 50°C in the case of a small means of containment or an intermediate bulk container (IBC) or, in the case of a large means of containment that is not an IBC, at a bulk mean temperature of 45°C. (3)If chemical stabilization may become ineffective at lower temperatures within the anticipated duration of transport, temperature control is required. In determining whether chemical stabilization may become ineffective at lower temperatures, the person offering the means of containment for transport must take at least the following the factors into consideration: (a)the capacity and geometry of the means of containment and the effect of any insulation;(b)the temperature of the dangerous goods when offered for transport; (c)the duration of the transport and the seasonal ambient temperature conditions typically encountered during transport; and (d)the effectiveness and other physical or chemical properties of the stabilizer employed. SOR/2017-137

Explosive Limit and Limited Quantity Index	: 0
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 10 L
Emergency Response Guide (ERG) Number	: 149P

Special provision (IMDG)	: 274, 386
Limited quantities (IMDG)	: 0
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P001
Packing provisions (IMDG)	: PP93
IBC packing instructions (IMDG)	: IBC03
IBC special provisions (IMDG)	: B19
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP4, TP6
EmS-No. (Fire)	: F-J - FIRE SCHEDULE Juliet - NON-TEMPERATURE-CONTROLLED SELF-REACTIVES AND ORGANIC PEROXIDES

BIMAX® HEMA-HP2

Safety Data Sheet

EmS-No. (Spillage)	: S-G - SPILLAGE SCHEDULE Golf - FLAMMABLE SOLIDS AND SELF-REACTIVE SUBSTANCES
Stowage category (IMDG)	: D
Stowage and handling (IMDG)	: SW1
Segregation (IMDG)	: SG35, SG36
Properties and observations (IMDG)	: Polymerizes at elevated temperatures or in a fire. Burns vigorously. Immiscible with water. Contact with alkalis or acids may cause dangerous polymerization. The products of combustion or self-accelerating polymerization may be toxic by inhalation.

IATA

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 459
PCA max net quantity (IATA)	: 10L
CAO packing instructions (IATA)	: 459
CAO max net quantity (IATA)	: 25L
Special provision (IATA)	: A209
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
2-hydroxyethyl methacrylate	868-77-9	Present	Active	
Ethylene glycol dimethacrylate	97-90-5	Present	Active	
Diethylene glycol monomethacrylate	2351-43-1	Not present	-	

15.2. International regulations

CANADA

2-hydroxyethyl methacrylate (868-77-9)

Listed on the Canadian DSL (Domestic Substances List)

Ethylene glycol dimethacrylate (97-90-5)

Listed on the Canadian DSL (Domestic Substances List)

Diethylene glycol monomethacrylate (2351-43-1)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

EU-Regulations

Ethylene glycol dimethacrylate (97-90-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

BIMAX® HEMA-HP2

Safety Data Sheet

National regulations

2-hydroxyethyl methacrylate (868-77-9)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Ethylene glycol dimethacrylate (97-90-5)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on Thailand Existing Chemicals Inventory (DIW)
Listed on the NCI (Vietnam - National Chemical Inventory)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



BIMAX® HEMA-HP2

Safety Data Sheet

SDS US (GHS HazCom 2012) - Custom

Judgments as to the suitability of information herein are the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, Gelest, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information to the purchaser's intended purpose or for consequences of its use. All statements relate only to the specific material designated herein, as shipped, and do not relate to use in combination with any other material or process. This document was prepared to comply with the requirements for SDS documentation in the United States (Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and may not address other regulatory requirements, and we do not guarantee that hazards listed herein are the only existing hazards. Nothing herein shall be considered to be instructions for any use which infringes a valid patent nor shall it be considered a license under any patent or other intellectual property. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used and safe handling thereof. We are not responsible for SDS documentation not received directly from us.

© 2025 Gelest Inc. Glen Rock, PA 17327

