

**BIMAX® CSEM-25/80****Safety Data Sheet 9052**

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date: 10/13/2023

Revision date: 04/04/2025

Supersedes: 07/01/2024

Version: 4.0

SECTION 1: Identification**1.1. Identification**

Product name	: BIMAX® CSEM-25/80
Product code	: 9052
Product form	: Mixture
Physical state	: Liquid
Synonyms	: POLY(OXY-1,2-ETHANEDIYL), A-(2-METHYL-1-OXO-2-PROPENYL)-Ω-HYDROXY-, C16-18-ALKYL ETHERS METHACRYLIC ACID ESTER OF AN ETHOXYLATED C16-C18-FATTY ALCOHOL MIXTURE
Chemical family	: ALKOXYLATED MONOMER
Chemical name	: CETYL STEARYL POLYETHOXY(25) METHACRYLATE

1.2. Recommended use and restrictions on use

Recommended use	: Laboratory chemicals Manufacture of substances
-----------------	---

1.3. Supplier

GELEST, INC.
158 Industrial Road
Glen Rock, PA 17327
USA
T 717-227-1774 - F 717-227-1775 (M-F): 8:00 AM - 5:30 PM EST
CS-Gelest@m-chem.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.
Full text of H statements : see section 16		

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H335 - May cause respiratory irritation

BIMAX® CSEM-25/80

Safety Data Sheet

Precautionary statements (GHS US) : P280 - Wear protective gloves, protective clothing, eye and face protection.
P271 - Use only outdoors or in a well-ventilated area.
P261 - Avoid breathing mist, spray, vapors.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P302+P352 - If on skin: Wash with plenty of soap and water.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER, a doctor.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
cetyl stearyl polyethoxy (25) methacrylate	CAS-No.: 70879-51-5	70 – 80	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Water	CAS-No.: 7732-18-5	15 – 25	Not classified
Methacrylic acid	CAS-No.: 79-41-4	0 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Hydroquinone monomethyl ether	CAS-No.: 150-76-5	0.29 – 0.33	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

BIMAX® CSEM-25/80

Safety Data Sheet

First-aid measures after skin contact	: In case of contact with substance, immediately flush skin with running water for at least 15 minutes. Wash skin with soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Specific hazards arising from the chemical

Reactivity	: No dangerous reactions known under normal conditions of use.
------------	--

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid breathing vapors, mist, spray. Avoid contact with skin and eyes.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing vapors, mist, spray. Avoid contact with skin and eyes. Wear personal protective equipment.
-------------------------------	--

BIMAX® CSEM-25/80

Safety Data Sheet

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Incompatible materials : Oxidizing agents. Peroxides. Free radical initiators.
Storage temperature : < 25 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

USA - ACGIH - Occupational Exposure Limits

Local name	Methacrylic acid
ACGIH OEL TWA	70 mg/m ³
	20 ppm
Remark (ACGIH)	TLV® Basis: Skin & eye irr
Regulatory reference	ACGIH 2025

USA - ACGIH - Occupational Exposure Limits

Local name	4-Methoxyphenol
ACGIH OEL TWA	5 mg/m ³
Remark (ACGIH)	TLV® Basis: Eye & Skin dam
Regulatory reference	ACGIH 2025

USA - NIOSH - Occupational Exposure Limits

NIOSH REL (TWA)	5 mg/m ³
-----------------	---------------------

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing. Where extensive dermal exposure may occur, either a chemical suit or chemical apron will be needed.

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : amber liquid.
Molecular mass : 1424 g/mol
Color : No data available
Odor : No data available

BIMAX® CSEM-25/80

Safety Data Sheet

Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 16 °C
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 1.06 g/ml at 25 °C
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal temperatures and pressures. Contains the following stabilizer(s): MEHQ.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Direct sunlight.

10.5. Incompatible materials

Oxidizing agents. Peroxides. Free radical initiators.

10.6. Hazardous decomposition products

No data available. In the event of fire: see section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

BIMAX® CSEM-25/80

Safety Data Sheet

Methacrylic acid (79-41-4)

LD50 oral rat	1320 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	500 – 1000 mg/kg body weight Animal: rabbit, Guideline: other:
LC50 Inhalation - Rat	7.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:

Hydroquinone monomethyl ether (150-76-5)

LD50 oral rat	1600 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: other:
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified

Methacrylic acid (79-41-4)

LOAEC (inhalation, rat, gas, 90 days)	350 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEC (inhalation, rat, gas, 90 days)	100 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study), Guideline: EPA OPPTS 870.3465 (90-Day Inhalation Toxicity), Guideline: other:

Hydroquinone monomethyl ether (150-76-5)

LOAEL (oral, rat, 90 days)	300 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
NOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

Methacrylic acid (79-41-4)

LC50 - Fish [1]	85 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 130 mg/l Test organisms (species): Daphnia magna

BIMAX® CSEM-25/80

Safety Data Sheet

Methacrylic acid (79-41-4)

EC50 72h - Algae [1]	45 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	20 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (chronic)	53 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	10 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '35 d'

Hydroquinone monomethyl ether (150-76-5)

LC50 - Fish [1]	84.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	3 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	28.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 72h - Algae [1]	54.7 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	19 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	54.7 mg/l Source: EHCA
LOEC (chronic)	1.45 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Water (7732-18-5)

Partition coefficient n-octanol/water (Log Pow)	-1.38
---	-------

Hydroquinone monomethyl ether (150-76-5)

Partition coefficient n-octanol/water (Log Pow)	1.34
---	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

BIMAX® CSEM-25/80

Safety Data Sheet

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
Not applicable	Not regulated	Not regulated	Not regulated
14.2. Proper Shipping Name			
Not applicable	Not applicable	Not applicable	Not applicable
Transport document description			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Water	7732-18-5	Present	Active	XU
cetyl stearyl polyethoxy (25) methacrylate	70879-51-5	Present	Active	XU
Methacrylic acid	79-41-4	Present	Active	
Hydroquinone monomethyl ether	150-76-5	Present	Active	T

BIMAX® CSEM-25/80

Safety Data Sheet

15.2. International regulations

CANADA

Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List)

cetyl stearyl polyethoxy (25) methacrylate (70879-51-5)

Listed on the Canadian DSL (Domestic Substances List)

Methacrylic acid (79-41-4)

Listed on the Canadian DSL (Domestic Substances List)

Hydroquinone monomethyl ether (150-76-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Hydroquinone monomethyl ether (150-76-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Water (7732-18-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Methacrylic acid (79-41-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Hydroquinone monomethyl ether (150-76-5)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Methacrylic acid (79-41-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

BIMAX® CSEM-25/80
Safety Data Sheet

Hydroquinone monomethyl ether (150-76-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information


according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Full text of hazard classes and H-statements

H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

Abbreviations and acronyms : Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Issue date: 10/13/2023 Revision date: 04/04/2025 Supersedes: 07/01/2024 Version: 4.0

SDS US (GHS HazCom 2012) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2023 Gelest Inc. Glen Rock, PA 17327