

**BIMAX® TDMA**

Safety Data Sheet 9271

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date: 12/17/2025

Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product name	: BIMAX® TDMA
Product code	: 9271
Product form	: Substance
Physical state	: Liquid
Formula	: C17H32O2
Synonyms	: 2-PROPENOIC ACID, 2-METHYL-, TRIDECYL ESTER METHACRYLIC ACID, TRIDECYL ESTER
Chemical name	: TRIDECYL METHACRYLATE

1.2. Recommended use and restrictions on use

Recommended use	: Laboratory chemicals Manufacture of substances
-----------------	---

1.3. Supplier

GELEST, INC.
158 Industrial Road
Glen Rock, PA 17327
USA
T 717-227-1774 - F 717-227-1775 (M-F): 8:00 AM - 5:30 PM EST
CS-Gelest@m-chem.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS US classification**

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS US labeling**

Hazard pictograms (GHS US)



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

BIMAX® TDMA

Safety Data Sheet

Precautionary statements (GHS US) : P261 - Avoid breathing fume, mist, spray, vapors.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, eye and face protection.
P302+P352 - If on skin: Wash with plenty of water.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a poison center or doctor if you feel unwell.
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards not otherwise classified (HNOC)

Other hazards which do not result in classification : Polymerization can occur at elevated temperature.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name : BIMAX® TDMA
CAS-No. : 2495-25-2

Name	Product identifier	%	GHS US classification
Tridecyl methacrylate	CAS-No.: 2495-25-2	> 98	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
Hydroquinone monomethyl ether	CAS-No.: 150-76-5	0.08 – 0.12	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

BIMAX® TDMA

Safety Data Sheet

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.
Chronic symptoms	: Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Avoid the use of streaming water, as this may spread the fire.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Reactivity	: No dangerous reactions known under normal conditions of use.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid breathing fume, mist, spray, vapors. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

BIMAX® TDMA

Safety Data Sheet

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing fume, mist, spray, vapors. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed in a dry and well-ventilated place away from heat sources. Store locked up.
Incompatible materials	: Oxidizing agents. Strong acids. Strong bases.
Storage temperature	: < 32 °C
Packaging materials	: Always store product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

USA - ACGIH - Occupational Exposure Limits	
Local name	4-Methoxyphenol
ACGIH® TLV® TWA	5 mg/m ³
Remark (ACGIH®)	TLV® Basis: Eye & Skin dam
Regulatory reference	ACGIH 2025
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	5 mg/m ³

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

BIMAX® TDMA

Safety Data Sheet

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, colorless Liquid.
Molecular mass	: 268.44 g/mol Source: International Programme on Chemical Safety
Color	: Colorless.
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 118 °C Source: CRC
Flash point	: 113 °C Source: National Institute of Technology and Evaluation
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.88 Source: National Emergency Management Agency
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available
Particle characteristics	: Particle size : Not applicable

Tridecyl methacrylate

Particle characteristics	Particle size : Not applicable
--------------------------	--------------------------------

Hydroquinone monomethyl ether

Particle characteristics	No data available
--------------------------	-------------------

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal temperatures and pressures. Contains the following stabilizer(s): MEHQ.

10.3. Possibility of hazardous reactions

Polymerization can occur at elevated temperature.

10.4. Conditions to avoid

Heat and light. Moisture.

BIMAX® TDMA

Safety Data Sheet

10.5. Incompatible materials

Oxidizing agents. Strong acids. Strong bases.

10.6. Hazardous decomposition products

No data available. In the event of fire: see section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation
Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydroquinone monomethyl ether (150-76-5)

LD50 oral rat	1600 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: other:
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.
STOT-repeated exposure : Not classified

Hydroquinone monomethyl ether (150-76-5)

LOAEL (oral,rat,90 days)	300 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
NOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Aspiration hazard : Not classified
Potential Adverse human health effects and symptoms : To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.
Chronic symptoms : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Tridecyl methacrylate (2495-25-2)

LC50 - Fish [1]	0.007 mg/l Source: Ecological Structure Activity Relationships
-----------------	--

BIMAX® TDMA

Safety Data Sheet

Hydroquinone monomethyl ether (150-76-5)

LC50 - Fish [1]	84.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	3 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	28.5 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 72h - Algae [1]	54.7 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	19 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
ErC50 algae	54.7 mg/l Source: EHCA
LOEC (chronic)	1.45 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.68 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Hydroquinone monomethyl ether (150-76-5)

Partition coefficient n-octanol/water (Log Pow)	1.34
---	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Disposal must be done according to official regulations.
Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Do not re-use empty containers.



SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated	Not regulated	3082	3082
14.2. Proper Shipping Name			
Not applicable	Not applicable	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TRIDECYL METHACRYLATE)	Environmentally hazardous substance, liquid, n.o.s. (Tridecyl methacrylate)

BIMAX® TDMA

Safety Data Sheet

DOT	TDG	IMDG	IATA
Transport document description			
Not applicable	Not applicable	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (TRIDECYL METHACRYLATE), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Tridecyl methacrylate), 9, III
14.3. Transport hazard class(es)			
Not applicable	Not applicable	9	9
			
14.4. Packing group			
Not applicable	Not applicable	III	III
14.5. Environmental hazards			
Not applicable	Not applicable	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

Special provision (IMDG) : 274, 335, 375, 969
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : LP01, P001
Packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG) : A

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L
Special provision (IATA) : A97, A158, A197, A215
ERG code (IATA) : 9L

BIMAX® TDMA

Safety Data Sheet

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
Tridecyl methacrylate	2495-25-2	Present	Active	
Hydroquinone monomethyl ether	150-76-5	Present	Active	T

15.2. International regulations

CANADA

Tridecyl methacrylate (2495-25-2)

Listed on the Canadian DSL (Domestic Substances List)

Hydroquinone monomethyl ether (150-76-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Hydroquinone monomethyl ether (150-76-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Hydroquinone monomethyl ether (150-76-5)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Hydroquinone monomethyl ether (150-76-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

BIMAX® TDMA

Safety Data Sheet

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Full text of hazard classes and H-statements	
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



Issue date: 12/17/2025

Version: 1.0

SDS US (GHS HazCom 2012) - Custom

Judgments as to the suitability of information herein are the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, Gelest, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information to the purchaser's intended purpose or for consequences of its use. All statements relate only to the specific material designated herein, as shipped, and do not relate to use in combination with any other material or process. This document was prepared to comply with the requirements for SDS documentation in the United States (Federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and may not address other regulatory requirements, and we do not guarantee that hazards listed herein are the only existing hazards. Nothing herein shall be considered to be instructions for any use which infringes a valid patent nor shall it be considered a license under any patent or other intellectual property. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used and safe handling thereof. We are not responsible for SDS documentation not received directly from us.

© 2025 Gelest Inc. Glen Rock, PA 17327