

**BORON METHOXIDE, 70% in methanol**

Safety Data Sheet AKB157.1

Date of issue: 28/11/2016 Version: 1.0

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Physical state	: Liquid
Product name	: BORON METHOXIDE, 70% in methanol
Product code	: AKB157.1
Formula	: C <sub>3</sub> H <sub>9</sub> BO <sub>3</sub>
Synonyms	: TRIMETHYL BORATE-METHANOL AZEOTROPE
Chemical family	: BORATE ESTER

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Use of the substance/mixture : Chemical intermediate

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet****GELEST, INC.**11 East Steel Road  
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)**GELEST INC.**Fritz-Klatte-Strasse 8  
65933 Frankfurt**Germany**

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

[info@gelestde.com](mailto:info@gelestde.com) - [www.gelestde.com](http://www.gelestde.com)**1.4. Emergency telephone number**

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Acute toxicity (oral), Category 3	H301
Acute toxicity (dermal), Category 3	H311
Acute toxicity (inhalation:vapour) Category 3	H331
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — single exposure, Category 1	H370
Full text of H statements : see section 16	

**Adverse physicochemical, human health and environmental effects**

No additional information available

**2.2. Label elements****Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02



GHS06



GHS08

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

Signal word (CLP)	: Danger
Hazardous ingredients	: Trimethyl borate; Methanol
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled H319 - Causes serious eye irritation. H370 - Causes damage to organs.
Precautionary statements (CLP)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground/bond container and receiving equipment. P260 - Do not breathe vapours. P264 - Wash hands thoroughly after handling. P308+P311 - IF exposed or concerned: Call a POISON CENTER.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Trimethyl borate	(CAS-No.) 121-43-7 (EC-No.) 204-468-9 (EC Index-No.) 005-005-00-1	65 - 70	Flam. Liq. 2, H225 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2, H319
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	30 - 35	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Methanol	(CAS-No.) 67-56-1 (EC-No.) 200-659-6 (EC Index-No.) 603-001-00-X	( 3 =<C < 10) STOT SE 2, H371 ( 10 =<C < 100) STOT SE 1, H370

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
First-aid measures after skin contact	: Wash with plenty of water/.... Immediately call a POISON CENTER/doctor.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. May cause drowsiness or dizziness. May cause irritation to the respiratory tract. Overexposure may cause: Nausea. Headache. Visual disturbances. Cough.
Symptoms/effects after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.
Chronic symptoms	: Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision. The solvent, methanol, probably determines toxicity. Ingestion of methanol can cause blindness and death.

### 4.3. Indication of any immediate medical attention and special treatment needed

Note to physician: Boron methoxide hydrolyzes to form methanol and boric acid. Treatment for exposure to methanol may be considered. At very high levels borates affect the CNS. NOTE TO PHYSICIAN: The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Alcohol-resistant foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: Avoid water spray as methanol will be generated.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Use special care to avoid static electric charges.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautions for safe handling	: Avoid all eye and skin contact and do not breathe vapour and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
Storage conditions	: Keep container tightly closed. Avoid contact with water. Keep in a cool place. Store locked up.
Incompatible materials	: Water.
Storage area	: Store in a well-ventilated place. Store away from heat.

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Trimethyl borate (121-43-7)</b>		
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	100 ppm
<b>Methanol (67-56-1)</b>		
EU	IOELV TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	200 ppm
Austria	MAK (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	1040 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	800 ppm
Belgium	Limit value (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	333 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	250 ppm
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Bulgaria	OEL TWA (ppm)	200 ppm
Cyprus	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Cyprus	OEL TWA (ppm)	200 ppm
France	VLE (mg/m <sup>3</sup> )	1300 mg/m <sup>3</sup>
France	VLE (ppm)	1000 ppm
France	VME (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup> (restrictive limit)
France	VME (ppm)	200 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	270 mg/m <sup>3</sup> (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	30 mg/l (Medium: urine - Time: end of shift - Parameter: Methanol) 30 mg/l (Medium: urine - Time: end of several shifts - Parameter: Methanol (for long-term exposures)
Gibraltar	Eight hours mg/m <sup>3</sup>	260 mg/m <sup>3</sup>
Gibraltar	Eight hours ppm	200 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	250 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	250 ppm
Italy	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	200 ppm
Latvia	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	6000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Spain	VLA-ED (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup> (indicative limit value)
Spain	VLA-ED (ppm)	200 ppm (indicative limit value)
Switzerland	KZGW (mg/m <sup>3</sup> )	1040 mg/m <sup>3</sup>

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

Methanol (67-56-1)		
Switzerland	KZGW (ppm)	800 ppm
Switzerland	MAK (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Switzerland	MAK (ppm)	200 ppm
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	133 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 8H (ppm)	100 ppm
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	266 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	333 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	250 ppm
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	250 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	270 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	330 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	250 ppm
Hungary	AK-érték	260 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	780 mg/m <sup>3</sup> (calculated)
Ireland	OEL (15 min ref) (ppm)	600 ppm (calculated)
Lithuania	IPRV (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	200 ppm
Malta	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	200 ppm
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	130 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	100 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	130 mg/m <sup>3</sup>
Norway	Grenseverdier (Korttidsverdi) (ppm)	100 ppm
Poland	NDS (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Romania	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	200 ppm
Romania	OEL STEL (ppm)	5 ppm
Slovakia	NPHV (priemerná) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	250 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	200 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Canada (Quebec)	VECD (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Canada (Quebec)	VECD (ppm)	250 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	200 ppm
Australia	TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
Australia	TWA (ppm)	200 ppm
Australia	STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
Australia	STEL (ppm)	250 ppm
Portugal	OEL TWA (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup> (indicative limit value)
Portugal	OEL TWA (ppm)	200 ppm (indicative limit value)
Portugal	OEL STEL (ppm)	250 ppm
Portugal	OEL chemical category (PT)	skin - potential for cutaneous exposure indicative limit value

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

### 8.2. Exposure controls

#### Appropriate engineering controls:

Provide local exhaust or general room ventilation.

#### Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Neoprene or nitrile rubber gloves

#### Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 103.91 g/mol
Colour	: Water white.
Odour	: slight.
Odour threshold	: No data available
Refractive index	: 1.3472
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: -29 °C
Boiling point	: 54 - 57 °C
Flash point	: -7 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Vapour pressure	: 205.5 mm Hg @ 25°C
Relative vapour density at 20 °C	: > 1
Relative density	: 0.883
% Volatiles	: > 90 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with air by reaction with moisture, liberating methanol and boric acid.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame.

### 10.5. Incompatible materials

Water.

### 10.6. Hazardous decomposition products

Organic acid vapors. Boron oxide fumes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.

#### BORON METHOXIDE, 70% in methanol (121-43-7)

ATE CLP (oral)	285.714 mg/kg bodyweight
ATE CLP (dermal)	554.622 mg/kg bodyweight
ATE CLP (vapours)	8.571 mg/l/4h

#### Trimethyl borate (121-43-7)

LD50 oral rat	7910 mg/kg 6140 mg/kg
LD50 dermal rabbit	1980 µl/kg
LC50 inhalation rat (ppm)	6400 ppm/4h
ATE CLP (oral)	7910 mg/kg bodyweight
ATE CLP (dermal)	1100 mg/kg bodyweight
ATE CLP (gases)	6400 ppmv/4h

#### Methanol (67-56-1)

LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE CLP (oral)	100 mg/kg bodyweight
ATE CLP (dermal)	300 mg/kg bodyweight
ATE CLP (vapours)	3 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation. Eye Irritation - rabbit: 500 mg: moderate irritation effect
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive toxicity	: Not classified
STOT-single exposure	: Causes damage to organs.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. May cause drowsiness or dizziness. May cause irritation to the respiratory tract. Overexposure may cause: Nausea. Headache. Visual disturbances. Cough.
Symptoms/effects after skin contact	: Toxic in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard. Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.
Chronic symptoms	: Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision. The solvent, methanol, probably determines toxicity. Ingestion of methanol can cause blindness and death.
Reason for classification	: Expert judgment

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute aquatic toxicity : Not classified  
Chronic aquatic toxicity : Not classified

Methanol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.  
Additional information : Handle empty containers with care because residual vapours are flammable.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### 14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR) : 1230  
UN-No. (IMDG) : 1230  
UN-No. (IATA) : 1230  
UN-No. (ADN) : 1230  
UN-No. (RID) : 1230

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : METHANOL  
Proper Shipping Name (IMDG) : METHANOL  
Proper Shipping Name (IATA) : Methanol  
Proper Shipping Name (ADN) : METHANOL  
Proper Shipping Name (RID) : METHANOL  
Transport document description (ADR) : UN 1230 METHANOL (METHANOL SOLUTION), 3 (6.1), II, (D/E)  
Transport document description (IMDG) : UN 1230 METHANOL (METHANOL SOLUTION), 3 (6.1), II (12°C c.c.)  
Transport document description (IATA) : UN 1230 Methanol (METHANOL SOLUTION), 3 (6.1), II  
Transport document description (ADN) : UN 1230 METHANOL (METHANOL SOLUTION), 3 (6.1), II  
Transport document description (RID) : UN 1230 METHANOL (METHANOL SOLUTION), 3 (6.1), II

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR) : 3 (6.1)  
Danger labels (ADR) : 3, 6.1



# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet



### IMDG

Transport hazard class(es) (IMDG) : 3 (6.1)

Danger labels (IMDG) : 3, 6.1



### IATA

Transport hazard class(es) (IATA) : 3 (6.1)

Hazard labels (IATA) : 3, 6.1



### ADN

Transport hazard class(es) (ADN) : 3 (6.1)

Danger labels (ADN) : 3, 6.1



### RID

Transport hazard class(es) (RID) : 3 (6.1)

Danger labels (RID) : 3, 6.1



## 14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

## 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

## 14.6. Special precautions for user

### - Overland transport

Classification code (ADR) : FT1

Special provisions (ADR) : 279

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T7
Portable tank and bulk container special provisions (ADR)	: TP2
Tank code (ADR)	: L4BH
Tank special provisions (ADR)	: TU15
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13, CV28
Special provisions for carriage - Operation (ADR)	: S2, S19
Hazard identification number (Kemler No.)	: 336
Orange plates	:

336

1230

Tunnel restriction code (ADR)	: D/E
EAC code	: •2WE
APP code	: A(fl)

### - Transport by sea

Special provisions (IMDG)	: 279
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP2
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-D
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Flash point (IMDG)	: 12°C c.c.

### - Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 352
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
Special provisions (IATA)	: A104, A113
ERG code (IATA)	: 3L

### - Inland waterway transport

Classification code (ADN)	: FT1
Special provisions (ADN)	: 279, 802
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, EX, TOX, A
Ventilation (ADN)	: VE01, VE02
Number of blue cones/lights (ADN)	: 2

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

### - Rail transport

Classification code (RID)	: FT1
Special provisions (RID)	: 279
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP2
Tank codes for RID tanks (RID)	: L4BH
Special provisions for RID tanks (RID)	: TU15
Transport category (RID)	: 2
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW28
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 336

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

% Volatiles : > 90 %

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Methanol is listed

##### Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# BORON METHOXIDE, 70% in methanol

## Safety Data Sheet

### SECTION 16: Other information

#### Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

#### Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
STOT SE 2	Specific target organ toxicity — Single exposure, Category 2
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H371	May cause damage to organs.

#### SDS EU (REACH Annex II) - Custom

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2019 Gelest Inc. Morrisville, PA 19067