

**LITHIUM t-BUTOXIDE 2M in tetrahydrofuran**

Safety Data Sheet AKL454.4

Date of issue: 15/03/2017

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Mixture
Physical state	: Liquid
Product name	: LITHIUM t-BUTOXIDE 2M in tetrahydrofuran
Product code	: AKL454.4
Formula	: C ₄ H ₉ LiO
Synonyms	: TERT-BUTOXYLITHIUM LITHIUM TERT-BUTYLATE LITHIUM 2-METHYLPROPAN-2-OLATE 2-METHYL-2-PROPANOL, LITHIUM SALT
Chemical family	: METAL ALCOHOLATE

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Use of the substance/mixture	: Chemical intermediate
------------------------------	-------------------------

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**GELEST, INC.**11 East Steel Road
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**GELEST INC.**Fritz-Klatte-Strasse 8
65933 Frankfurt**Germany**

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: Tetrahydrofuran

Hazard statements (CLP)

: H225 - Highly flammable liquid and vapour.
H314 - Causes severe skin burns and eye damage.
H335 - May cause respiratory irritation.
H351 - Suspected of causing cancer.

Precautionary statements (CLP)

: P202 - Do not handle until all safety precautions have been read and understood.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P264 - Wash hands thoroughly after handling.
P240 - Ground/bond container and receiving equipment.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P310 - Immediately call a POISON CENTER or doctor/physician

EUH-statements

: EUH019 - May form explosive peroxides.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Tetrahydrofuran	(CAS-No.) 109-99-9 (EC-No.) 203-726-8 (EC Index-No.) 603-025-00-0	70 - 75	Flam. Liq. 2, H225 Eye Irrit. 2, H319 Carc. 2, H351 STOT SE 3, H335
Lithium t-butoxide	(CAS-No.) 1907-33-1 (EC-No.) 217-611-5	25 - 30	Flam. Sol. 2, H228 Skin Corr. 1B, H314 Eye Dam. 1, H318

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Tetrahydrofuran	(CAS-No.) 109-99-9 (EC-No.) 203-726-8 (EC Index-No.) 603-025-00-0	(25 =<C < 100) Eye Irrit. 2, H319 (25 =<C < 100) STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.

First-aid measures after skin contact

: Wash with plenty of water/.... Get immediate medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion

: Never give anything by mouth to an unconscious person. Give a demulscent such as milk, olive oil, or margarine in small amounts, up to two or three tablespoons. Get medical advice/attention.

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage. May cause cancer.
Symptoms/effects after inhalation	: May cause respiratory irritation. Inhalation will cause sneezing, irritation and burns.
Symptoms/effects after skin contact	: Causes (severe) skin burns. Worker will notice a slippery feeling on washing.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Chronic symptoms	: TETRAHYDROFURAN: Mildly toxic by inhalation. Mutagenic data has been reported. Reported as causing injury to liver and kidneys.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry chemical. Dry soda ash. Dry sodium chloride.
Unsuitable extinguishing media	: Do not use water or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour. Irritating fumes and caustic vapors may develop when material is exposed to elevated temperatures or open flame.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Protect against caustic dust, smoke and water.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist. Wear pressure demand self-contained breathing apparatus with full facepiece and full protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Use special care to avoid static electric charges.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all eye and skin contact and do not breathe vapour and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
Storage conditions	: Keep container tightly closed. Keep in a cool place. Store locked up. Store under dry nitrogen or argon in sealed containers.
Incompatible materials	: Acids. alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Water.
Storage area	: Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tetrahydrofuran (109-99-9)		
EU	IOELV TWA (mg/m ³)	150 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	300 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
Austria	MAK (mg/m ³)	150 mg/m ³
Austria	MAK (ppm)	50 ppm
Austria	MAK Short time value (mg/m ³)	300 mg/m ³
Austria	MAK Short time value (ppm)	100 ppm
Belgium	Limit value (mg/m ³)	150 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	300 mg/m ³
Belgium	Short time value (ppm)	100 ppm
Bulgaria	OEL TWA (mg/m ³)	150 mg/m ³
Bulgaria	OEL TWA (ppm)	50 ppm
Bulgaria	OEL STEL (mg/m ³)	100 mg/m ³
Bulgaria	OEL STEL (ppm)	300 ppm
Cyprus	OEL TWA (mg/m ³)	150 mg/m ³
Cyprus	OEL TWA (ppm)	50 ppm
Cyprus	OEL STEL (mg/m ³)	300 mg/m ³
Cyprus	OEL STEL (ppm)	100 ppm
France	VLE (mg/m ³)	300 mg/m ³ (restrictive limit)
France	VLE (ppm)	100 ppm (restrictive limit)
France	VME (mg/m ³)	150 mg/m ³ (restrictive limit)
France	VME (ppm)	50 ppm (restrictive limit)
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	150 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	50 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	2 mg/l (Medium: urine - Time: end of shift - Parameter: Tetrahydrofuran)
Gibraltar	Eight hours mg/m ³	150 mg/m ³
Gibraltar	Eight hours ppm	50 ppm
Gibraltar	Short-term mg/m ³	300 mg/m ³
Gibraltar	Short-term ppm	100 ppm
Greece	OEL TWA (mg/m ³)	590 mg/m ³
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m ³)	735 mg/m ³
Greece	OEL STEL (ppm)	250 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	50 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	100 ppm
Italy	OEL TWA (mg/m ³)	150 mg/m ³
Italy	OEL TWA (ppm)	50 ppm
Italy	OEL STEL (mg/m ³)	300 mg/m ³
Italy	OEL STEL (ppm)	100 ppm
Latvia	OEL TWA (mg/m ³)	150 mg/m ³

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

Tetrahydrofuran (109-99-9)		
Latvia	OEL TWA (ppm)	50 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	735 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
Spain	VLA-ED (mg/m ³)	150 mg/m ³ (indicative limit value)
Spain	VLA-ED (ppm)	50 ppm (indicative limit value)
Spain	VLA-EC (mg/m ³)	300 mg/m ³
Spain	VLA-EC (ppm)	100 ppm
Switzerland	KZGW (mg/m ³)	300 mg/m ³
Switzerland	KZGW (ppm)	100 ppm
Switzerland	MAK (mg/m ³)	150 mg/m ³
Switzerland	MAK (ppm)	50 ppm
Netherlands	Grenswaarde TGG 8H (mg/m ³)	300 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	600 mg/m ³
United Kingdom	WEL TWA (mg/m ³)	150 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m ³)	300 mg/m ³
United Kingdom	WEL STEL (ppm)	100 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	150 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	150 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Finland	HTP-arvo (8h) (mg/m ³)	150 mg/m ³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	300 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Hungary	AK-érték	150 mg/m ³
Hungary	CK-érték	300 mg/m ³
Ireland	OEL (8 hours ref) (mg/m ³)	150 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m ³)	300 mg/m ³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Lithuania	IPRV (mg/m ³)	150 mg/m ³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m ³)	300 mg/m ³
Lithuania	TPRV (ppm)	100 ppm
Malta	OEL TWA (mg/m ³)	150 mg/m ³
Malta	OEL TWA (ppm)	50 ppm
Malta	OEL STEL (mg/m ³)	300 mg/m ³
Malta	OEL STEL (ppm)	100 ppm
Norway	Grenseverdier (AN) (mg/m ³)	150 mg/m ³
Norway	Grenseverdier (AN) (ppm)	50 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	150 mg/m ³
Norway	Grenseverdier (Korttidsverdi) (ppm)	50 ppm
Poland	NDS (mg/m ³)	150 mg/m ³
Poland	NDSch (mg/m ³)	300 mg/m ³
Romania	OEL TWA (mg/m ³)	150 mg/m ³
Romania	OEL TWA (ppm)	50 ppm

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

Tetrahydrofuran (109-99-9)		
Romania	OEL STEL (mg/m ³)	300 mg/m ³
Romania	OEL STEL (ppm)	100 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	150 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	50 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	300 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	150 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	250 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	80 ppm
Canada (Quebec)	VEMP (mg/m ³)	300 mg/m ³
Canada (Quebec)	VEMP (ppm)	100 ppm
Australia	TWA (mg/m ³)	295 mg/m ³
Australia	TWA (ppm)	100 ppm
Portugal	OEL TWA (mg/m ³)	150 mg/m ³ (indicative limit value)
Portugal	OEL TWA (ppm)	50 ppm (indicative limit value)
Portugal	OEL STEL (mg/m ³)	300 mg/m ³ (indicative limit value)
Portugal	OEL STEL (ppm)	100 ppm (indicative limit value)
Portugal	OEL chemical category (PT)	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, skin - potential for cutaneous exposure indicative limit value

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified caustic organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 80.55 g/mol
Colour	: Clear to dark amber.
Odour	: No data available
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: 66 °C initial (THF)
Flash point	: -14 °C
Auto-ignition temperature	: No data available

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapour.
Sublimation point	: 114 - 116 °C (sub)
Vapour pressure	: 144 mm Hg @ 15° (THF)
Relative vapour density at 20 °C	: 2.5 (THF)
Relative density	: 0.888
% Volatiles	: > 75 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.8 - 11.6 vol % (lower; upper: THF)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under nitrogen or argon in sealed containers.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water, possibly igniting.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Water.

10.6. Hazardous decomposition products

t-Butanol. Caustic organic vapors. Lithium hydroxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Tetrahydrofuran (109-99-9)

LD50 oral rat	1650 mg/kg
LC50 inhalation rat (ppm)	21000 ppm (Exposure time: 3 h)
ATE CLP (oral)	1650 mg/kg bodyweight

Lithium t-butoxide (1907-33-1)

LD50 oral mouse	1682 mg/kg RTECS Number: UB8520000
-----------------	------------------------------------

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer. This product contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH classification.

Tetrahydrofuran (109-99-9)

National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
--	---------------------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation. Inhalation will cause sneezing, irritation and burns.

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

Symptoms/effects after skin contact	: Causes (severe) skin burns. Worker will notice a slippery feeling on washing.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Chronic symptoms	: TETRAHYDROFURAN: Mildly toxic by inhalation. Mutagenic data has been reported. Reported as causing injury to liver and kidneys.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

Tetrahydrofuran (109-99-9)	
LC50 fish 1	1970 - 2360 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2700 - 3600 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Tetrahydrofuran (109-99-9)	
BCF fish 1	(will not bioconcentrate)
Log Pow	0.45 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 2924
UN-No. (IMDG)	: 2924
UN-No. (IATA)	: 2924
UN-No. (ADN)	: 2924
UN-No. (RID)	: 2924

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (IATA)	: Flammable liquid, corrosive, n.o.s.
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper Shipping Name (RID)	: FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Transport document description (ADR)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. ((LITHIUM t-BUTOXIDE 2M in tetrahydrofuran)), 3 (8), II, (D/E)
Transport document description (IMDG)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. ((LITHIUM t-BUTOXIDE 2M in tetrahydrofuran)), 3 (8), II
Transport document description (IATA)	: UN 2924 Flammable liquid, corrosive, n.o.s. ((LITHIUM t-BUTOXIDE 2M in tetrahydrofuran)), 3 (8), II

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

Transport document description (ADN)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. ((LITHIUM t-BUTOXIDE 2M in tetrahydrofuran)), 3 (8), II
Transport document description (RID)	: UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S. ((LITHIUM t-BUTOXIDE 2M in tetrahydrofuran)), 3 (8), II

14.3. Transport hazard class(es)

ADR	
Transport hazard class(es) (ADR)	: 3 (8)
Danger labels (ADR)	: 3, 8



IMDG	
Transport hazard class(es) (IMDG)	: 3 (8)
Danger labels (IMDG)	: 3, 8



IATA	
Transport hazard class(es) (IATA)	: 3 (8)
Hazard labels (IATA)	: 3, 8



ADN	
Transport hazard class(es) (ADN)	: 3 (8)
Danger labels (ADN)	: 3, 8



RID	
Transport hazard class(es) (RID)	: 3 (8)
Danger labels (RID)	: 3, 8



14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: FC
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP2, TP27
Tank code (ADR)	: L4BH
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 338
Orange plates	:

338

2924

Tunnel restriction code (ADR)	: D/E
-------------------------------	-------

- Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-C
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

- Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y340
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 352
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 363
CAO max net quantity (IATA)	: 5L
Special provisions (IATA)	: A3
ERG code (IATA)	: 3CH

- Inland waterway transport

Classification code (ADN)	: FC
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 1

- Rail transport

Classification code (RID)	: FC
Special provisions (RID)	: 274
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP2, TP27
Tank codes for RID tanks (RID)	: L4BH
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE7
Hazard identification number (RID)	: 338

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

% Volatiles	: > 75 %
-------------	----------

15.1.2. National regulations

Germany

Reference to AwSV	: Water hazard class (WGK) 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)
-------------------	---

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)
--	--

Netherlands

SZW-lijst van kankerverwekkende stoffen	: Tetrahydrofuran is listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed

Denmark

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
------------------------	---

LITHIUM t-BUTOXIDE 2M in tetrahydrofuran

Safety Data Sheet

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

	Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor
--	--

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Sol. 2	Flammable solids, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
EUH019	May form explosive peroxides.

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067