

LITHIUM t-BUTOXIDE

Safety Data Sheet AKL454

Date of issue: 03/15/2017

Version: 1.0

SECTION 1: Identification**1.1. Identification**

Product name	:	LITHIUM t-BUTOXIDE
Product code	:	AKL454
Product form	:	Substance
Physical state	:	Solid
Formula	:	C ₄ H ₉ LiO
Synonyms	:	TERT-BUTOXYLITHIUM LITHIUM TERT-BUTYLATE LITHIUM 2-METHYLPROPAN-2-OLATE 2-METHYL-2-PROPANOL, LITHIUM SALT
Chemical family	:	METAL ALCOHOLATE

1.2. Recommended use and restrictions on use

Recommended use	:	Chemical intermediate
-----------------	---	-----------------------

1.3. Supplier

GELEST, INC.
11 East Steel Road
Morrisville, PA 19067
USA
T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST
info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	:	CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---	---

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flammable solids Category 2	H228	Flammable solid
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements**GHS-US labeling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H228 - Flammable solid
H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, open flames, sparks
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P260 - Do not breathe dust.
P264 - Wash hands thoroughly after handling.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a doctor
P321 - Specific treatment (see first aid instructions on this label)
P363 - Wash contaminated clothing before reuse.

LITHIUM t-BUTOXIDE

Safety Data Sheet

P370+P378 - In case of fire: Use dry chemical, dry soda ash or dry sodium chloride to extinguish.
P405 - Store locked up.
P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : LITHIUM t-BUTOXIDE
CAS-No. : 1907-33-1

Name	Product identifier	%	GHS-US classification
Lithium t-butoxide	(CAS-No.) 1907-33-1	95 - 100	Flam. Sol. 2, H228 Skin Corr. 1B, H314 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Give a demulscent such as milk, olive oil, or margarine in small amounts, up to two or three tablespoons. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : Inhalation will cause sneezing, irritation and burns.

Symptoms/effects after skin contact : Causes (severe) skin burns. If skin and air are dry, powder on skin may not cause irritation or burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the powder can cause severe burns.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical. Dry soda ash. Dry sodium chloride.

Unsuitable extinguishing media : Do not use water or carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable solid. Irritating fumes and caustic vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Protect against caustic dust, smoke and water.

Protection during firefighting : Avoid contact with skin and eyes. Do not breathe dust. Do not enter fire area without proper protective equipment, including respiratory protection. Wear pressure demand self-contained breathing apparatus with full facepiece and full protective clothing.

LITHIUM t-BUTOXIDE

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe dust. Avoid dust formation. Ground containers when handling powder. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof electrical equipment.

Storage conditions : Keep container tightly closed. Store locked up. Store under dry nitrogen or argon in sealed containers.

Incompatible materials : Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Oxidizing agent. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles or face shield. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing. Long-sleeved fire-resistant lab uniform or coverall is recommended.

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified caustic organic vapor (black cartridge) respirator.

LITHIUM t-BUTOXIDE

Safety Data Sheet

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Molecular mass	: 80.05 g/mol
Color	: White to off-white.
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 110 °C @ 0.01 mm Hg sub
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable solid
Vapor pressure	: < 0.001 mm Hg @ 20°C
Relative vapor density at 20 °C	: No data available
Relative density	: 0.89
Solubility	: Reacts with water. Organic solvent:80 g/l Solubility, heptane
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under nitrogen or argon in sealed containers.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water, possibly igniting.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Oxidizing agent. Water.

10.6. Hazardous decomposition products

t-Butanol. Caustic organic vapors. Lithium hydroxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Lithium t-butoxide (1907-33-1)

LD50 oral mouse	1682 mg/kg RTECS Number: UB8520000
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified

LITHIUM t-BUTOXIDE

Safety Data Sheet

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
	None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Inhalation will cause sneezing, irritation and burns.
Symptoms/effects after skin contact	: Causes (severe) skin burns. If skin and air are dry, powder on skin may not cause irritation or burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the powder can cause severe burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on the ozone layer : No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 2925

DOT NA no. UN2925

14.2. UN proper shipping name

Transport document description : UN2925 Flammable solids, corrosive, organic, n.o.s. (LITHIUM t-BUTOXIDE), 4.1 (8), II

Proper Shipping Name (DOT) : Flammable solids, corrosive, organic, n.o.s.
(LITHIUM t-BUTOXIDE)

Class (DOT) : 4.1 - Class 4.1 - Flammable Solid 49 CFR 173.124

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 4.1 - Flammable solid
8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 212

DOT Packaging Bulk (49 CFR 173.xxx) : 242

LITHIUM t-BUTOXIDE

Safety Data Sheet

DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 134
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 15 kg
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 50 kg
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Lithium t-butoxide (1907-33-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Lithium t-butoxide (1907-33-1)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Lithium t-butoxide (1907-33-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Lithium t-butoxide (1907-33-1)

Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Full text of H-phrases::

H228	Flammable solid
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

Abbreviations and acronyms : Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

LITHIUM t-BUTOXIDE

Safety Data Sheet

Flammability	: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
Physical	: 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

Prepared by safety and environmental affairs.

Date of issue: 03/15/2017 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2018 Gelest Inc. Morrisville, PA 19067

