

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet AKT887.2

Date of issue: 19/10/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Physical state	: Liquid
Product name	: TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol
Product code	: AKT887.2
Formula	: C ₁₄ H ₂₀ O ₉ Ti
Synonyms	: TRIS(2-METHYL-2-PROPENOATO)METHOXYETHOXYETHOXYTITANATE
Chemical family	: METAL ESTER

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Chemical intermediate

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

GELEST INC.

Fritz-Klatte-Strasse 8
65933 Frankfurt

Germany

T +49 (0) 69 3535106-500 - F +49 (0) 69 3535106-501 - (M-F): 8:00 AM - 4:00 PM

info@gelestde.com - www.gelestde.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity, Category 2	H361
Full text of H statements : see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word (CLP) :

: Warning

Hazardous ingredients :

: Methoxyethoxyethanol

Hazard statements (CLP) :

: H315 - Causes skin irritation.
H319 - Causes serious eye irritation.

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

Precautionary statements (CLP) : H361 - Suspected of damaging fertility or the unborn child.
: P202 - Do not handle until all safety precautions have been read and understood.
: P280 - Wear protective gloves/protective clothing/eye protection/face protection.
: P264 - Wash hands thoroughly after handling.
: P405 - Store locked up.
: P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
: P308+P313 - IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Titanium triacrylate methoxyethoxyethoxide	(CAS-No.) 99749-57-2	89 - 90	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Methoxyethoxyethanol	(CAS-No.) 111-77-3	8 - 10	Repr. 2, H361d
Isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	0 - 3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a physician.

First-aid measures after skin contact : Wash with plenty of water/.... Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Suspected of damaging fertility or the unborn child.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapour and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all eye and skin contact and do not breathe vapour and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent formation of vapour. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up. Protect against sunlight. Avoid excessive heat.

Incompatible materials : Free radical initiators. Moist air. Oxidizing agent. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropanol (67-63-0)		
Austria	MAK (mg/m ³)	500 mg/m ³ (short time value for large casting)
Austria	MAK (ppm)	200 ppm (short time value for large casting)
Austria	MAK Short time value (mg/m ³)	2000 mg/m ³ 2000 mg/m ³ (STEL for large casting valid till 12/31/2013)
Austria	MAK Short time value (ppm)	800 ppm 800 ppm (STEL for large casting valid till 12/31/2013)
Belgium	Limit value (mg/m ³)	500 mg/m ³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m ³)	1000 mg/m ³
Belgium	Short time value (ppm)	400 ppm
Bulgaria	OEL TWA (mg/m ³)	980 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	1225 mg/m ³
France	VLE (mg/m ³)	980 mg/m ³
France	VLE (ppm)	400 ppm

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

Isopropanol (67-63-0)		
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	500 mg/m ³ (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	TRGS 903 Biological limit value	25 mg/l (Medium: whole blood - Time: end of shift - Parameter: Acetone) 25 mg/l (Medium: urine - Time: end of shift - Parameter: Acetone)
Greece	OEL TWA (mg/m ³)	980 mg/m ³
Greece	OEL TWA (ppm)	400 ppm
Greece	OEL STEL (mg/m ³)	1225 mg/m ³
Greece	OEL STEL (ppm)	500 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	200 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	400 ppm
Latvia	OEL TWA (mg/m ³)	350 mg/m ³
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
Spain	VLA-ED (mg/m ³)	500 mg/m ³ (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Spain	VLA-ED (ppm)	200 ppm (it is prohibited the partial or complete commercialization or use of this substance as a phytosanitary or biocide compound)
Spain	VLA-EC (mg/m ³)	1000 mg/m ³
Spain	VLA-EC (ppm)	400 ppm
Switzerland	KZGW (mg/m ³)	1000 mg/m ³
Switzerland	KZGW (ppm)	400 ppm
Switzerland	MAK (mg/m ³)	500 mg/m ³
Switzerland	MAK (ppm)	200 ppm
United Kingdom	WEL TWA (mg/m ³)	999 mg/m ³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m ³)	1250 mg/m ³
United Kingdom	WEL STEL (ppm)	500 ppm
Czech Republic	Expoziční limity (PEL) (mg/m ³)	500 mg/m ³
Denmark	Grænseværdie (langvarig) (mg/m ³)	490 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Finland	HTP-arvo (8h) (mg/m ³)	500 mg/m ³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	620 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
Hungary	AK-érték	500 mg/m ³
Hungary	CK-érték	2000 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Lithuania	IPRV (mg/m ³)	350 mg/m ³
Lithuania	IPRV (ppm)	150 ppm
Lithuania	TPRV (mg/m ³)	600 mg/m ³

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

Isopropanol (67-63-0)		
Lithuania	TPRV (ppm)	250 ppm
Norway	Grenseverdier (AN) (mg/m ³)	245 mg/m ³
Norway	Grenseverdier (AN) (ppm)	100 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m ³)	245 mg/m ³
Norway	Grenseverdier (Korttidsverdi) (ppm)	100 ppm
Poland	NDS (mg/m ³)	900 mg/m ³
Poland	NDSch (mg/m ³)	1200 mg/m ³
Romania	OEL TWA (mg/m ³)	200 mg/m ³
Romania	OEL TWA (ppm)	81 ppm
Romania	OEL STEL (mg/m ³)	500 mg/m ³
Romania	OEL STEL (ppm)	203 ppm
Slovakia	NPHV (priemerná) (mg/m ³)	500 mg/m ³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Slovakia	NPHV (Hraničná) (mg/m ³)	1000 mg/m ³
Sweden	nivågränsvärde (NVG) (mg/m ³)	350 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	600 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
Canada (Quebec)	VECD (mg/m ³)	1230 mg/m ³
Canada (Quebec)	VECD (ppm)	500 ppm
Canada (Quebec)	VEMP (mg/m ³)	985 mg/m ³
Canada (Quebec)	VEMP (ppm)	400 ppm
Australia	TWA (mg/m ³)	983 mg/m ³
Australia	TWA (ppm)	400 ppm
Australia	STEL (mg/m ³)	1230 mg/m ³
Australia	STEL (ppm)	500 ppm
Portugal	OEL TWA (ppm)	200 ppm
Portugal	OEL STEL (ppm)	400 ppm
Portugal	OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation.

Personal protective equipment:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Avoid all unnecessary exposure.

Hand protection:

Neoprene or nitrile rubber gloves

Eye protection:

Chemical goggles. Contact lenses should not be worn

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

Molecular mass	: 380.19 g/mol
Colour	: Dark red-amber.
Odour	: Characteristic odor of acrylates.
Odour threshold	: No data available
Refractive index	: No additional information available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 76 °C initial
Flash point	: 65 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.14
% Volatiles	: < 5 %
Solubility	: Reacts with water. Forms acidic solution.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 15 - 20 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur if heated. Material decomposes slowly in contact with moist air and rapidly in contact with water liberating acrylic acid.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Free radical initiators. Moist air. Oxidizing agent. Water.

10.6. Hazardous decomposition products

Acrylic acid. Organic acid vapors. Titanium oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Isopropanol (67-63-0)	
LD50 oral rat	1870 mg/kg
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat (mg/l)	72600 mg/m ³ (Exposure time: 4 h)
ATE CLP (oral)	4396 mg/kg bodyweight
ATE CLP (dermal)	12800 mg/kg bodyweight
Methoxyethoxyethanol (111-77-3)	
LD50 oral mouse	8222 mg/kg

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

Methoxyethoxyethanol (111-77-3)	
LD50 oral rabbit	9190 mg/kg
LD50 oral guinea pig	4160 mg/kg
LD50 intraperitoneal rat	2722 mg/kg
LD50 intravenous mouse	2611 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Isopropanol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified

Isopropanol (67-63-0)	
LC50 fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Log Pow	0.05 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Product/Packaging disposal recommendations	: Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

In accordance with ADR / RID / IMDG / IATA / ADN

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

14.1. UN number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: Not applicable
----------------------------------	------------------

IMDG

Transport hazard class(es) (IMDG)	: Not applicable
-----------------------------------	------------------

IATA

Transport hazard class(es) (IATA)	: Not applicable
-----------------------------------	------------------

ADN

Transport hazard class(es) (ADN)	: Not applicable
----------------------------------	------------------

RID

Transport hazard class(es) (RID)	: Not applicable
----------------------------------	------------------

14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons (450 liters). The product is not regulated for transport by the IATA, ADR/RID, ADN or the IMDG regulations.

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

Contains no REACH Annex XIV substances

% Volatiles : < 5 %

15.1.2. National regulations

Germany

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Methoxyethoxyethanol is listed

Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor

Other information : Prepared by safety and environmental affairs.

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2

TITANIUM TRIACRYLATE METHOXYETHOXYETHOXIDE, 90% in methoxydiethyleneglycol

Safety Data Sheet

STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.

SDS EU (REACH Annex II) - Custom

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

