

Safety Data Sheet AKV910 Date of issue: 10/09/2015 Versi Version: 1.0

SECTION 1: Identification			
1.1. Identification			
Product name	: VANADIUM TRIISOPROPOXIDE OXIDE		
Product code	: AKV910		
Product form	: Substance		
Physical state	: Liquid		
Formula	: C9H21O4V		
Synonyms	: VANADIUM OXIDE TRIISOPROPYLATE; VANADYL ISOPROPYLATE; OXOTRIS(PROPAN- 2-OLATO)VANADIUM		
Chemical family	: METAL COMPOUND		
1.2. Recommended use and restriction			
Recommended use	: Chemical intermediate		
1.3. Supplier			
<b>GELEST, INC.</b> 11 East Steel Road Morrisville, PA 19067 <b>USA</b> T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 info@gelest.com - www.gelest.com	AM - 5:30 PM EST		
1.4. Emergency telephone number			
Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)		
SECTION 2: Hazard(s) identification			
2.1. Classification of the substance or i	mixture		
GHS-US classification			
Flammable liquids Category 3 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Specific target organ toxicity (single exposure) ( Full text of H statements : see section 16	H226 Flammable liquid and vapor H315 Causes skin irritation H319 Causes serious eye irritation Category 3 H335 May cause respiratory irritation		
2.2. GHS Label elements, including pre	cautionary statements		
GHS US labeling			
Hazard pictograms (GHS US)			
Signal word (GHS US)	: Warning		
Hazard statements (GHS US)	: H226 - Flammable liquid and vapor H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation		
Precautionary statements (GHS US)	<ul> <li>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P312 - Call a doctor if you feel unwell</li> <li>P210 - Keep away from heat, open flames, sparks No smoking.</li> <li>P240 - Ground/Bond container and receiving equipment</li> <li>P241 - Use explosion-proof electrical equipment</li> <li>P242 - Use only non-sparking tools.</li> <li>P243 - Take precautionary measures against static discharge.</li> <li>P264 - Wash hands thoroughly after handling.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing</li> <li>P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower</li> <li>P332+P313 - If skin irritation occurs: Get medical advice/attention.</li> <li>P337+P313 - If eye irritation persists: Get medical advice/attention.</li> <li>P337+P313 - If eye irritation persists: Get medical advice/attention.</li> <li>P321 - Specific treatment (see first aid instructions on this label)</li> </ul>		
Print date: 04/11/2019	EN (English US) SDS ID: AKV910 Page 1		

Safety Data Sheet

	P362+P364 - Take off c P370+P378 - In case of P403+P233 - Store in a P403+P235 - Keep in a P405 - Store locked up. P501 - Dispose of conte	fire: Use water spray, fo well-ventilated place. Ke cool place	oam, carbon eep containe	dioxide, dry chemical to extinguish er tightly closed.
2.3. Hazards not otherwise classified	(HNOC)			
No additional information available				
2.4. Unknown acute toxicity (GHS US				
Not applicable				
SECTION 3: Composition/Informa	tion on ingredients			
3.1. Substances	<b>.</b>			
Substance type Name	: Mono-constituent : VANADIUM TRIISOPRO			
CAS-No.	: 5588-84-1			
Name		Product identifier	%	GHS-US classification
Vanadium triisopropoxide oxide		(CAS-No.) 5588-84-1	<b>70</b> 95 - 100	Flam. Lig. 3, H226
		(		Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of hazard classes and H-statements	: see section 16			
3.2. Mixtures				
Not applicable				
SECTION 4: First-aid measures				
4.1. Description of first aid measures				
First-aid measures general				ent or if you feel unwell, seek ). If possible show this sheet; if not
	available show packagir		ere possible	
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.			
-irst-aid measures after skin contact	: Wash with plenty of soa	p and water. Get medica	al advice/att	ention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses present and easy to do. Continue rinsing. Get medical advice/attention.			
First-aid measures after ingestion	: Never give anything by r	mouth to an unconsciou	s person. G	et medical advice/attention.
4.2. Most important symptoms and e				
Symptoms/effects after inhalation	: May cause respiratory irritation.			
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Causes skin irritation.			
Symptoms/effects after ingestion	<ul> <li>Causes serious eye irrita</li> <li>May be harmful if swallo</li> </ul>			
4.3. Immediate medical attention and No additional information available	special treatment, if necessa	ry		
SECTION 5: Fire-fighting measure 5.1. Suitable (and unsuitable) extingu				
Suitable extinguishing media	: Water spray. Foam. Car	bon dioxide. Dry chemic	cal.	
Unsuitable extinguishing media	: Do not use straight strea		~~!!	
5.2. Specific hazards arising from the	-			
Fire hazard				id vapors may develop when
5.3. Special protective equipment and	d precautions for fire-fighters			
Firefighting instructions	: Exercise caution when f	ighting any chemical fire	e. Use water	r spray to cool exposed surfaces.
Protection during firefighting	: Do not enter fire area wi Avoid all eye and skin co	thout proper protective of ontact and do not breath	equipment, ne vapor and	including respiratory protection. d mist.
SECTION 6: Accidental release m	easures			
6.1. Personal precautions, protective	equipment and emergency p	rocedures		
General measures	: Eliminate ignition source	es. Use special care to a	avoid static e	electric charges.
6.1.1. For non-emergency personnel				
Protective equipment	: Wear protective equipme	ent as described in Sect	tion 8.	
Print date: 0//11/2010	EN (English LIS)	-		10 2/

Safety Data Sheet

Emergency procedures	: Evacuate unnecessary personnel.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".		
6.2. Environmental precautions			
Prevent entry to sewers and public waters.	Notify authorities if liquid enters sewers or public waters.		
6.3. Methods and material for conta	inment and cleaning up		
For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.		
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.		
6.4. Reference to other sections			
See Heading 8. Exposure controls and pers	sonal protection.		
SECTION 7: Handling and storag	je		
7.1. Precautions for safe handling			
Additional hazards when processed	: Keep away from heat/sparks/open flames/hot surfaces No smoking.		
Precautions for safe handling	<ul> <li>Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoo or in a well-ventilated area. Use only non-sparking tools.</li> </ul>		
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.		
7.2. Conditions for safe storage, inc	cluding any incompatibilities		
Technical measures	: Use explosion-proof electrical equipment.		
Storage conditions	: Keep container tightly closed. Keep in a cool place. Store locked up.		
ncompatible materials	: Moist air. Water.		
	: Store in a well-ventilated place. Store away from heat.		
Incompatible materials Storage area	: Store in a well-ventilated place. Store away from heat.		
Storage area SECTION 8: Exposure controls/p	: Store in a well-ventilated place. Store away from heat.		
Storage area SECTION 8: Exposure controls/p 8.1. Control parameters	: Store in a well-ventilated place. Store away from heat.		
Storage area SECTION 8: Exposure controls/p 8.1. Control parameters Vanadium triisopropoxide oxide (5588-	: Store in a well-ventilated place. Store away from heat. personal protection 84-1)		
Storage area SECTION 8: Exposure controls/p 8.1. Control parameters Vanadium triisopropoxide oxide (5588-	: Store in a well-ventilated place. Store away from heat.		
Storage area         SECTION 8: Exposure controls/p         8.1.       Control parameters         Vanadium triisopropoxide oxide (5588-t         OSHA       OSHA PE	: Store in a well-ventilated place. Store away from heat. ersonal protection  84-1)  3L (TWA) (mg/m <sup>3</sup> ) 0.05 mg/m <sup>3</sup> for V205		
Storage area         SECTION 8: Exposure controls/p         8.1.       Control parameters         Vanadium triisopropoxide oxide (5588-1         OSHA       OSHA PE         8.2.       Appropriate engineering control	: Store in a well-ventilated place. Store away from heat. ersonal protection  84-1)  3L (TWA) (mg/m <sup>3</sup> ) 0.05 mg/m <sup>3</sup> for V205		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA         OSHA         8.2. Appropriate engineering controls	: Store in a well-ventilated place. Store away from heat. Dersonal protection  84-1)  3L (TWA) (mg/m <sup>3</sup> )  0.05 mg/m <sup>3</sup> for V205  1S  2 Provide local exhaust or general room ventilation.		
Storage area         SECTION 8: Exposure controls/p         8.1.       Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA       OSHA PE         8.2.       Appropriate engineering controls         8.3.       Individual protection measures	: Store in a well-ventilated place. Store away from heat. Dersonal protection  84-1)  3L (TWA) (mg/m <sup>3</sup> )  0.05 mg/m <sup>3</sup> for V205  1S  2 Provide local exhaust or general room ventilation.		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA       OSHA PE         8.2. Appropriate engineering controls         8.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence	: Store in a well-ventilated place. Store away from heat. Dersonal protection  84-1)  3L (TWA) (mg/m <sup>3</sup> )  0.05 mg/m <sup>3</sup> for V205  1S  2 Provide local exhaust or general room ventilation.		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA       OSHA PE         8.2. Appropriate engineering controls         8.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence	: Store in a well-ventilated place. Store away from heat.		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA         OSHA         B.2. Appropriate engineering controls         B.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence         exposure.         Hand protection:	: Store in a well-ventilated place. Store away from heat.		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA       OSHA PE         8.2. Appropriate engineering controls         8.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence         exposure.         Hand protection:         Neoprene or nitrile rubber gloves	: Store in a well-ventilated place. Store away from heat. Dersonal protection 84-1) AL (TWA) (mg/m <sup>3</sup> ) 0.05 mg/m <sup>3</sup> for V205 Dis : Provide local exhaust or general room ventilation. /Personal protective equipment		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA         OSHA         B.2. Appropriate engineering controls         B.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence         exposure.         Hand protection:         Neoprene or nitrile rubber gloves         Eye protection:	: Store in a well-ventilated place. Store away from heat.		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-t)         OSHA         OSHA         OSHA         OSHA         OSHA         OSHA         S.2. Appropriate engineering controls         8.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence         exposure.         Hand protection:         Neoprene or nitrile rubber gloves         Eye protection:         Chemical goggles. Contact lenses should not protect l	: Store in a well-ventilated place. Store away from heat.		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA         OSHA         B.2. Appropriate engineering controls         B.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence         exposure.         Hand protection:         Neoprene or nitrile rubber gloves         Eye protection:         Chemical goggles. Contact lenses should not shin and body protection:	: Store in a well-ventilated place. Store away from heat.		
Storage area SECTION 8: Exposure controls/p 8.1. Control parameters Vanadium triisopropoxide oxide (5588-4 OSHA OSHA PE 8.2. Appropriate engineering controls 8.3. Individual protection measures Personal protective equipment: Avoid all unnecessary exposure. Emergence exposure. Hand protection: Neoprene or nitrile rubber gloves Eye protection: Chemical goggles. Contact lenses should n Skin and body protection: Wear suitable protective clothing	: Store in a well-ventilated place. Store away from heat.		
Storage area SECTION 8: Exposure controls/p 8.1. Control parameters Vanadium triisopropoxide oxide (5588-4 OSHA OSHA PE 8.2. Appropriate engineering controls 8.3. Individual protection measures Personal protective equipment: Avoid all unnecessary exposure. Emergenc exposure. Hand protection: Neoprene or nitrile rubber gloves Eye protection: Chemical goggles. Contact lenses should n Skin and body protection: Wear suitable protective clothing Respiratory protection:	: Store in a well-ventilated place. Store away from heat.		
Storage area         SECTION 8: Exposure controls/p         8.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA       OSHA PE         8.2. Appropriate engineering controls         8.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence         exposure.         Hand protection:         Neoprene or nitrile rubber gloves         Eye protection:         Chemical goggles. Contact lenses should no         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:	: Store in a well-ventilated place. Store away from heat.		
Storage area SECTION 8: Exposure controls/p 8.1. Control parameters Vanadium triisopropoxide oxide (5588-4 OSHA OSHA PE 8.2. Appropriate engineering controls 8.3. Individual protection measures Personal protective equipment: Avoid all unnecessary exposure. Emergence exposure. Hand protection: Neoprene or nitrile rubber gloves Eye protection: Chemical goggles. Contact lenses should ne Skin and body protection: Wear suitable protective clothing Respiratory protection: Where exposure through inhalation may occ	Example 2 Store in a well-ventilated place. Store away from heat.          ersonal protection         84-1)         12. (TVVA) (mg/m³)         0.05 mg/m³ for V205         015         E         Provide local exhaust or general room ventilation.         //Personal protective equipment         y eye wash fountains and safety showers should be available in the immediate vicinity of any potential         ot be worn         cur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black		
Storage area         SECTION 8: Exposure controls/p         3.1. Control parameters         Vanadium triisopropoxide oxide (5588-4         OSHA         OSHA         S2. Appropriate engineering controls         8.2. Appropriate engineering controls         8.3. Individual protection measures         Personal protective equipment:         Avoid all unnecessary exposure. Emergence         axposure.         Hand protection:         Neoprene or nitrile rubber gloves         Eye protection:         Chemical goggles. Contact lenses should ne         Skin and body protection:         Wear suitable protective clothing         Respiratory protection:         Where exposure through inhalation may occordition         Where exposure through inhalation may occordition	<ul> <li>Store in a well-ventilated place. Store away from heat.</li> </ul> ersonal protection   84-1)   C1 (TWA) (mg/m³)   0.05 mg/m³ for V205   obs : Provide local exhaust or general room ventilation. //Personal protective equipment y eye wash fountains and safety showers should be available in the immediate vicinity of any potential ot be worn cur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cal properties		

Appearance

Molecular mass

: Clear liquid.

Safety Data Sheet

Color	: Clear to greenish. Turns orange-brown on exposure to moist air.			
Odor	: characteristic. n-Propanol.			
Odor threshold	: No data available			
Refractive index	: 1.481			
pH	: No data available			
Relative evaporation rate (butyl acetate=1)	: No data available			
Melting point	: No data available			
Freezing point	: -1114 °C			
Boiling point	∴ -1114 °C : 80 - 82 °C @ 2 mm Hg			
Flash point	: 80 - 82 °C @ 2 mm Hg : 58 °C			
Auto-ignition temperature				
	: No data available			
Decomposition temperature	: No data available			
Flammability (solid, gas)	: Flammable liquid and vapor			
Vapor pressure	: <1 mm Hg @ 25°C : >1			
Relative vapor density at 20 °C				
Relative density	: 1.029			
Solubility	: Reacts with water.			
Log Pow	: No data available			
Log Kow	: No data available			
Viscosity, kinematic	: No data available			
Viscosity, dynamic	: No data available			
Explosive properties	: No data available			
Oxidizing properties	: No data available			
Explosion limits	: No data available			
9.2. Other information				
No additional information available				
SECTION 10: Stability and reactivity	у			
10.1. Reactivity				
No additional information available				
10.2. Chemical stability				
Stable in sealed containers.				
<b>10.3. Possibility of hazardous reactions</b> Material reacts rapidly with water or moist air, li	borating isopropagal and vagadium oxide gol			
	beraing isoproparior and variation oxide ger.			
10.4. Conditions to avoid				
Heat. Open flame. Sparks.				
10.5. Incompatible materials				
Moist air. Water.				
10.6. Hazardous decomposition product	'S			
Organic acid vapors. Vanadium oxide fumes.				
SECTION 11: Toxicological informa	tion			
11.1. Information on toxicological effect				
	s . Not classified			
Acute toxicity				
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/irritation	: Causes serious eye irritation.			
Respiratory or skin sensitization	Not classified			
Germ cell mutagenicity	Not classified			
Carcinogenicity	: Not classified			
Reproductive toxicity	: Not classified			
Specific target organ toxicity – single exposure	: May cause respiratory irritation.			
Specific target organ toxicity – repeated exposure	: Not classified			
Aspiration hazard	: Not classified			

### Safety Data Sheet

Print date: 04/11/2019	EN (English US)	SDS ID: AKV910	5/7
Air transport DOT Quantity Limitations Passenger aircraft/rai (49 CFR 173.27)	il : 60 L		
Transport by sea DOT Vessel Stowage Location	: A - The material may be passenger vessel.	stowed "on deck" or "under deck" on a cargo vessel and on a	
Other information	: No supplementary inform		
		nation available	
14.3.         Additional information           Emergency Response Guide (ERG) Number	: 128		
	. G - Identities Poin requi		
DOT Packaging Exceptions (49 CFR 173.xxx) DOT Symbols	: 150 : G - Identifies PSN requi	ing a technical name	
DOT Packaging Bulk (49 CFR 173.xxx)	: 242		
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203		
	PLANTALE LIQUID		
Hazard labels (DOT)	: 3 - Flammable liquid		
Packing group (DOT)	: III - Minor Danger		
Class (DOT)		and combustible liquid 49 CFR 173.120	
Proper Shipping Name (DOT)	: Flammable liquids, n.o.s (VANADIUM TRIISOPR		
Transport document description		ids, n.o.s. (VANADIUM TRIISOPROPOXIDE OXIDE), 3, III	
14.2. UN proper shipping name			
DOT NA no.	UN1993		
UN-No.(DOT)	: 1993		
SECTION 14: Transport information 14.1. UN number			
Ecology - waste materials		ensed waste disposal facility.	
Product/Packaging disposal recommendations		er in accordance with local/national regulations. Dispose of	
13.1.         Disposal methods           Sewage disposal recommendations	: Do not dispose of waste	into sewer	
SECTION 13: Disposal consideratio	ns line line line line line line line line		
SECTION 42. Diseased as a side of the			
Effect on the ozone layer	: No additional informatio	n available	
12.5. Other adverse effects			
No additional information available			
12.4. Mobility in soil			
No additional information available			
12.3. Bioaccumulative potential			
12.2. Persistence and degradability No additional information available			
No additional information available			
12.1. Toxicity			
<b>SECTION 12: Ecological informatio</b>	n		
Reason for classification	: Expert judgment		
Symptoms/effects after ingestion	: May be harmful if swalld		
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Causes serious eye irrit	ation.	
	: Causes skin irritation.		

Safety Data Sheet

DOT Quantity Limitations Cargo aircraft only (49  $\pm$  220 L CFR 175.75)

### **SECTION 15: Regulatory information**

15.1. US Federal regulations

### Vanadium triisopropoxide oxide (5588-84-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### **15.2. International regulations**

CANADA

Vanadium triisopropoxide oxide (5588-84-1)

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### **EU-Regulations**

#### Vanadium triisopropoxide oxide (5588-84-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **National regulations**

#### Vanadium triisopropoxide oxide (5588-84-1)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List) Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Suparioso i oliticari relocioo and riansioi registe

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### **SECTION 16: Other information**

H226	Flammable liquid and vapor
H315	Causes skin irritation
- H319	Causes serious eye irritation
H335	May cause respiratory irritation
	Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling; APF: Assigned Protection Factor.
ard Rating	
alth	: 2 Moderate Hazard - Temporary or minor injury may occur
nmability	: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
sical	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at hig temperatures and pressures. Materials may react non-violently with water or underg

#### Prepared by safety and environmental affairs.

Date of issue: 10/09/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Safety Data Sheet

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2019 Gelest Inc. Morrisville, PA 19067

